



DMS SEAL TECHNOLOGY CO.,LIMITED

Design Manufacture Service

DMS SEALS was established in 2008. DMS Seals Technology Co., Limited is a Sci-tech enterprise which specialized in the research, manufacture, and sales of high polymer seals. DMS Seals covers an area of more than 10000 square meters. By now, we have more than 20 senior technicians and more than 100 sets of production equipments and advanced testing equipment. Meanwhile we have got many patents and own the leading production process. We passed the evaluation of ISO9001:2008 and TS16949:2009.

Our main products are polymer seals of PTFE, modified material, FKM, PCTFE, UPE, Special polyurethane and so on. They are the key parts of some mechanical equipment which required high temperature resistance, low temperature resistance, high pressure resistance, corrosion resistance and other special working conditions. They are widely used in the engineering machinery, car, automation equipment, petroleum, chemical engineering, aerospace, LNG and other field.

We insist on “First class design, First class manufacture, and First class service” as our mission. Strive to be a leading sealing solution supplier, and continue creating much more value for our customers.

DMS SEALS -- Provide you high quality products, quick service and leading technical support.

ISO 9001:2008

ISO/TS 16949:2009



Introduction of High polymer material

PTFE and filled PTFE

PCTFE

UHMWPE

PEEK

Introduction of Rubber material

NBR

FKM/FPM

EPDM

Introduction of high polymer material

1. PTFE and its filling modification

The melting point of PTFE is 327 °C, density is 2.18 ~ 2.3g/cm³, and shore hardness is D50 to D65, it has excellent chemical stability and self lubrication, it is the most widely used and the most variety of fluorine plastics. It has excellent overall performance. For example, resistant to high and low temperature, corrosion resistance, aging resistance, non adhesion, high insulation, high lubrication, no poison. However, PTFE has poor creep resistance, poor wear resistance, and large expansion coefficient. Therefore, it is usually necessary to overcome these defects by filling and modifying. Commonly used fillers are bronze, carbon fiber, glass fiber, graphite, MoS₂, polybenzoate, PEEK and so on. According to different conditions and uses, it can be filled with one or more of the material.

Pure PTFE products

Pure PTFE can be machined into support rings, back up rings, and other seals, with high temperature resistance, corrosion resistance, self-lubricating characteristics. But prone to creep and cause leakage under load, it's usually used in food, pharmaceutical and chemical industries.

Bronze filled PTFE products

Bronze is the most commonly used filler for PTFE, and the PTFE sealing modified by filling bronze has improved greatly in pressure resistance, wear resistance, thermal conductivity and creep resistance. For different performance requirements, different bronze composition, particle size and filling ratio can be chosen to meet the actual demand. The product is usually used to make wear rings, wear strips, oil cylinder seals and so on. The bronze may be corroded under strong acid conditions, so it is not recommended for use in strong acid conditions.

Carbon fiber filled PTFE products

The PTFE seal modified by carbon fiber has greatly improved the pressure resistance, wear resistance, creep resistance and tensile strength, meanwhile improved the hardness of the products, and suitable for rotary sealing, usually used for the production of spring energized seals, automobile transmission oil rings and so on. Carbon fibers may be oxidized and decomposed in a strong acid environment, so they are not recommended for use in strong acid conditions.

Glass fiber filled PTFE products

It has greatly improved in pressure resistance, wear resistance, creep resistance and tensile strength after filled the glass fiber for modified PTFE seal, meanwhile improved the hardness of the product, and suitable for rotary seal. Usually used for the production of back up rings, spring energized seals, automobile transmission oil rings and so on. Glass fiber may decompose in alkaline conditions, so it is not recommended for use in alkaline or water containing conditions.



Graphite or MoS₂ modified filled PTFE products

The main purpose of filling graphite or MoS₂ modification is to improve the pressure resistance, wear resistance, creep resistance and maintain the maximum low friction coefficient of PTFE and self lubrication characteristics. Usually filled with other fillers and can be individually filled, mainly used in the manufacture of spring energized seals, air cylinder seal, self-lubricating shaft sleeve and so on. Applicable to the condition of low friction coefficient or inconvenient to add lubricant.

Polybenzoate or PEEK filled PTFE products

It has greatly improved in pressure resistance, wear resistance, creep resistance and high temperature resistance after filled the Polybenzoate or PEEK, and especially has greatly improved the toughness and hardness in the high temperature environment. Suitable for the static seal, the dynamic seal and the self lubrication piston rings of the compressor for long time working in the high temperature environment.

2. PCTFE

The melting point of PCTFE is 210 ~ 230 °C, density is 2.1 ~ 2.18g/cm³, and shore hardness is D75 ~ D90, PCTFE has excellent rigidity and corrosion resistance, and its mechanical properties are superior to PTFE at room temperature, and it has high compression strength and small cold flow. It has a higher rebound rate at low temperature and has a good elastic restoring force, and maintain a certain degree of elasticity at -265 °C, it is one of the best material for ultra-low temperature combination property of polymers.

PCTFE is a crystalline polymer, so its mechanical properties are greatly affected by temperature, and it will be a certain difference base on different crystallinity and molecular weight, the tensile strength and hardness will increases with the advance of crystallization, but the elongation will decreases. Because of the poor fluidity of the melt, the grade with large molecular weight usually use compression molding and can't use extrusion molding.

PCTFE is an ideal sealing material under low temperature and high pressure conditions, it can be used for a long time in the range of -200 ~ 125 °C. PCTFE seals are of special use in the field of high and new technology, recommended for use in liquid oxygen, liquid nitrogen, liquefied natural gas and other low temperature conditions in the pipe, pumps, valves, joints and other fields.

Introduction of high polymer material

3. UHMWPE

The melting point of UHMWPE is 130 ~ 136 °C, density is 0.94g/cm³, and shore hardness is D40 ~ D60. It combines almost all of the advantages of plastic materials, impact resistance, wear resistance, chemical corrosion resistance, low friction coefficient, good self-lubricating performance. And it has excellent mechanical properties in ultra-low temperature environment, still has high impact property at -70 °C, still maintain toughness and strength at -196 °C, it hardly absorbent and non-swelling. It has better wear resistance and creep resistance than PTFE material, the mortar wear test proved that abrasion resistance of UHMWPE can reach 6.6 times of ordinary carbon steel.

The molecular weight of UHMWPE is less than 5 million and can be extruded molding after technical processing, the molecular weight of UHMWPE which is more than 5 million only can do compression molding.

The long term working temperature range of UHMWPE seals is -180 °C ~ 70 °C. Recommended for the working condition of high sliding performance requirements or poor lubrication, high wear resistance or prone to dry friction of water in mediums, also usually used in ultra-low temperature sealing environment. Its disadvantage is lack of tensile strength, poor high temperature resistance, low hardness and low thermal conductivity.

4. PEEK

The melting point of PEEK is 334 °C, density is 1.265 ~ 1.32g/cm³, and shore hardness is D82 ~ D90, tensile Strength is higher than 92MPa. PEEK is a kind of special polymer material. It has high mechanical strength, high temperature resistance, impact resistance, flame retardant, acid and alkali resistance, hydrolysis resistance, wear resistance, fatigue resistance, radiation resistance and good electrical insulation performance. PEEK resin has high temperature performance and high melting point. The continuous use temperature can reach 260 °C, and the load thermal deformation temperature up to 316 °C after adding glass fiber or carbon fiber. PEEK resin has good toughness and rigidity, and it has excellent fatigue tolerance to the strain force, which is comparable to the alloy material.

Because of its excellent resistance to high temperature, self lubrication, wear resistance and fatigue resistance, it has become one of the most popular high performance engineering plastics. It is mainly used in aerospace, automotive industry, electronic and electrical, medical equipment and other fields.

PEEK has good mechanical properties, high temperature resistance, wear resistance and high pressure resistance, so it is commonly used to make compressor valve plate, piston rings, high temperature seals, sliding bearings and so on.



1. NBR

NBR is a kind of synthetic rubber produced by low temperature emulsion polymerization of butadiene and acrylonitrile, it has excellent oil resistance, high wear resistance, water resistance, air tightness and good bonding properties. NBR used in the range of -30 °C ~ 100 °C, and the service life will decreases when it is used at 120 °C. It is widely used in the production of a variety of oil-resistant rubber products, O-Ring, washers, casing, cable plastic materials, etc. it is also an essential elastic material in the automotive, aviation, oil and other industries.

The disadvantages of NBR are low temperature resistance, poor ozone resistance, low insulation performance and low elasticity.

2. VITON (FKM/FPM)

Viton rubber is a synthetic rubber containing with fluorine atom. It has the characteristics of high temperature resistance, oil resistance, media resistance, and variety of chemical erosion resistance. And it has high chemical stability, which has the best performance for media resistant in one of the elastomer at present. The application for temperature ranges is from -20°C to 200°C. The low temperature ranges are from -15°C to -20°C for dynamic sealing. It's mainly used for producing oil seals, O-Rings, back up rings, O-Ring cords, rubber sheets, sealing rings and so on. The disadvantages of viton is poor performance for low temperature resistance and density is large.

3. EPDM

EPDM is a ternary polymer of Ethylene, Propylene, and Non-conjugated Diolefins. The main polymer chains are fully saturated, so that it can resist heat, light, oxygen, especially for ozone. It has high performances for oxidation resistance, weather resistance, electricity insulated, chemical corrosion resistance, attacked elasticity. It's mainly applied for the industry of oxygen resistant, water resistant, corrosion resistant and electrical insulation, for producing heat resistant conveyor belts, cables, antiseptic lining, sealing gaskets, door and window seals, and plastic modification and so on.

Rod Seals Series

| Type | Figure | Technical Data | | | Application | Material | Action | Page |
|-------|---|-------------------|---------------|------------------|---|----------------------|--------|--------------|
| | | Temp. Range °C | Speed ≤m/s | Pressure ≤MPa | | | | |
| GSJ |  | -45/+200 | 15 | 60 | Hydraulic equipment Standard cylinders General Machinery Machine tools | NBR/PTFE FKM/PTFE | Single | 12 |
| RSJ |  | -45/+200 | 15 | 60 | Hydraulic equipment Standard cylinders General Machinery | NBR/PTFE FKM/PTFE | Single | Refer to GSJ |
| GSI |  | -45/+200 | 15 | 60 | Hydraulic equipment Standard cylinders General Machinery Machine tools | NBR/PTFE FKM/PTFE | Double | 18 |
| GZT |  | -30/+200 | 15 | 60 | Injection machine Valve Machine tools | NBR/PTFE FKM/PTFE | Double | Refer to GSI |
| GSW |  | -30/+200 | 15 | 60 | Hydraulic equipment Standard cylinders Machine tools | NBR/PTFE FKM/PTFE | Single | 24 |
| GSJ-W |  | -30/+100 | 5 | 60 | Heavy duty cylinders General Machinery Machine tools | NBR/PTFE FKM/PTFE | Single | 27 |
| TDI |  | -30/+100 | 1 | 45 | Standard hydraulic cylinders | NBR/PTFE Polymer | Single | 31 |
| RDI |  | -30/+100 | 1 | 45 | Standard hydraulic cylinders | NBR/PTFE Polymer | Double | 34 |
| MDI |  | -30/+100 | 1 | 25 | Standard hydraulic cylinders | NBR/PTFE Polymer | Double | 38 |
| SPN |  | -30/+200 | 1.5 | 35 | Standard hydraulic cylinders Construction machinery | NBR/PTFE FKM/PTFE | Double | 41 |
| SPNC |  | -30/+200 | 1.5 | 35 | Standard hydraulic cylinders Construction machinery | NBR/PTFE FKM/PTFE | Double | 43 |
| SPNO |  | -30/+200 | 1.5 | 35 | Standard hydraulic cylinders Construction machinery | NBR/PTFE FKM/PTFE | Double | 47 |

Piston Seals Series

| Type | Figure | Technical Data | | | Application | Material | Action | Page |
|-------|---|----------------|-------------|----------------|---|----------------------|--------|----------------|
| | | Temp. Range °C | Speed ≤ m/s | Pressure ≤ MPa | | | | |
| GSF |  | -45/+200 | 15 | 60 | Hydraulic equipment Standard cylinders General Machinery Machine tools | NBR/PTFE FKM/PTFE | Double | 50 |
| GSD |  | -45/+200 | 15 | 60 | Hydraulic equipment Standard cylinders General Machinery Machine tools | NBR/PTFE FKM/PTFE | Single | 56 |
| DPT |  | -45/+200 | 15 | 60 | Hydraulic equipment Injection machine Machine tools | NBR/PTFE FKM/PTFE | Double | Refer to GSF |
| SPG |  | -30/+200 | 1.5 | 35 | Standard hydraulic cylinders Construction machinery | NBR/PTFE FKM/PTFE | Double | 61 |
| SPGC |  | -30/+200 | 1.5 | 35 | Standard hydraulic cylinder Construction machinery | NBR/PTFE FKM/PTFE | Double | 64 |
| SPGO |  | -30/+200 | 1.5 | 35 | Standard hydraulic cylinders Construction machinery | NBR/PTFE FKM/PTFE | Double | 68 |
| DPO |  | -30/+200 | 1.5 | 35 | Standard hydraulic cylinders Construction machinery | NBR/PTFE FKM/PTFE | Double | 71 |
| DAQ |  | -30/+200 | 2 | 40 | Standard hydraulic cylinders Accumulator Hydraulic press | NBR/PTFE FKM/PTFE | Double | 74 |
| DAQ2 |  | -30/+200 | 3 | 60 | Standard hydraulic cylinders Accumulator Hydraulic press | NBR/PTFE FKM/PTFE | Double | 78 |
| GSF-W |  | -30/+100 | 5 | 60 | Standard hydraulic cylinders Heavy duty cylinder | NBR/PTFE FKM/PTFE | Double | 81 |
| GSD-W |  | -30/+100 | 5 | 60 | Standard hydraulic cylinder Heavy duty cylinder | NBR/PTFE FKM/PTFE | Single | Refer to GSF-W |
| DDKK |  | -30/+200 | 1 | 45 | Standard hydraulic cylinders Heavy duty cylinder | NBR/PTFE Polymer | Double | 85 |

Piston Seals Series

| Type | Figure | Technical Data | | | Application | Material | Action | Page |
|-------------|---|-------------------|---------------|------------------|--|--------------------|--------|------|
| | | Temp. Range °C | Speed ≤m/s | Pressure ≤MPa | | | | |
| DKDF |  | -30/+200 | 1 | 45 | Standard hydraulic cylinders Heavy duty cylinders | NBR/PTFE Polymer | Double | 88 |
| DGDA |  | -30/+100 | 1 | 45 | Standard hydraulic cylinders | NBR/PTFE Polymer | Double | 91 |
| SPGW |  | -30/+100 | 1.5 | 40 | Standard hydraulic cylinders Construction machinery Heavy duty cylinders | NBR/PTFE Polymer | Double | 94 |
| TPM/ DBM |  | -30/+120 | 0.5 | 35 | Standard hydraulic cylinders | NBR/PTFE Polymer | Double | 97 |
| OK |  | -30/+110 | 1 | 80 | Heavy duty cylinders | NBR/therm - oplast | Double | 101 |
| DDA |  | -30/+100 | 1 | 45 | Standard hydraulic cylinders | NBR/PTFE Polymer | Single | 104 |
| DDMA |  | -30/+100 | 1 | 25 | Standard hydraulic cylinders | NBR/PTFE Polymer | Double | 107 |

Rotary Seals Series

| Type | Figure | Technical Data | | | Application | Material | Action | Page |
|------|---|-------------------|---------------|------------------|---|-------------------|--------|------|
| | | Temp. Range °C | Speed ≤m/s | Pressure ≤MPa | | | | |
| GNS |  | -30/+200 | 1 | 30 | Rotary distributor Standard hydraulic cylinder Machine tool | NBR/PTFE FKM/PTFE | Rotary | 110 |
| GRS |  | -30/+200 | 1 | 30 | Rotary distributor Standard hydraulic cylinder Machine tool | NBR/PTFE FKM/PTFE | Rotary | 114 |
| OI |  | -35/+100 | 0.5 | 35 | Rotary distributor Standard hydraulic cylinder Machine tool | NBR/PTFE FKM/PTFE | Rotary | 118 |
| OA |  | -35/+100 | 0.5 | 35 | Rotary distributor Standard hydraulic cylinder Machine tool | NBR/PTFE FKM/PTFE | Rotary | 121 |

Scraper Seals Series

| Type | Figure | Technical Data | | | Application | Material | Action | Page |
|------|---|-------------------|---------------|------------------|--|----------------------|--------|------|
| | | Temp. Range °C | Speed ≤m/s | Pressure ≤MPa | | | | |
| GSZ |  | -30/+200 | 5 | - | Hydraulic equipment Ceramic machinery machine tool | NBR/PTFE FKM/PTFE | Single | 124 |
| GSZ2 |  | -30/+200 | 5 | - | Hydraulic equipment Ceramic machinery machine tool | NBR/PTFE FKM/PTFE | Single | 128 |
| DPT1 |  | -30/+200 | 5 | - | Hydraulic equipment Injection machine | NBR/PTFE FKM/PTFE | Single | 132 |
| DPT2 |  | -30/+200 | 5 | - | Hydraulic equipment Injection machine | NBR/PTFE FKM/PTFE | Single | 136 |
| KZT |  | -50/+200 | 1.5 | - | Construction machinery | PTFE | Double | 139 |

Bearing Elements Series

| Type | Figure | Technical Data | | | Application | Material | Action | Page |
|------|---|-------------------|---------------|------------------|---|----------|---------|------|
| | | Temp. Range °C | Speed ≤m/s | Pressure ≤MPa | | | | |
| GST |  | -60/+230 | 15 | - | Standard hydraulic cylinder Ceramic machinery Heavy duty cylinder | PTFE | Guiding | 142 |
| DFI |  | -55/+255 | 3 | - | Hydraulic equipment Ceramic machinery | PTFE | Guiding | 144 |
| DFA |  | -55/+255 | 3 | - | Hydraulic equipment Ceramic machinery | PTFE | Guiding | 147 |
| DFAI |  | -55/+255 | 3 | - | Hydraulic equipment Ceramic machinery | PTFE | Guiding | 150 |

Variseals Series

| Standard Groove | | | | | Widen groove | | | | | | | | | | |
|-----------------|------|---|---|---|----------------|---|---|---|---|---|-----|---|------|---|------|
| Technical Data | | | | | Technical Data | | | | | | | | | | |
| Temp. Range °C | | Speed ≤m/s | | Pressure≤MPa | Temp. Range °C | | Speed ≤m/s | | Pressure≤MPa | | | | | | |
| -40/+260 | | 15 | | 45 | -40/+260 | | 15 | | 45 | | | | | | |
| Type | Code |  | APS |  | 103A |  | 400A | Type | Code |  | APS |  | 103A |  | 400A |
| Rod and Piston | DEPA |  |  |  | Rod and Piston | DEPB |  |  |  | | | | | | |
| Rod | DRPA |  |  |  | Rod | DRPB |  |  |  | | | | | | |
| Piston | DEGA |  |  |  | Piston | DEGB |  |  |  | | | | | | |
| Material | | PTFE and Spring | | | | | Material | | PTFE and Spring | | | | | | |
| Application | | Food machinery/General machinery | | | | | Application | | Food machinery/General machinery | | | | | | |
| Action | | Single | | | | | Action | | Single | | | | | | |
| Page | | 153 | | | | | | | | | | | | | |


| Rotary Variseal | | | | | Face variseal | | | | | | | | | | |
|-------------------------|------|---|---|---|----------------|---|---|---|---|---|-----|---|------|---|------|
| Technical Data | | | | | Technical Data | | | | | | | | | | |
| Temp. Range °C | | Speed ≤m/s | | Pressure≤MPa | Temp. Range °C | | Speed ≤m/s | | Pressure≤MPa | | | | | | |
| -40/+260 | | 15 | | 45 | -40/+260 | | - | | 45 | | | | | | |
| Type | Code |  | APS |  | 103A |  | 400A | Type | Code |  | APS |  | 103A |  | 400A |
| Equal Altitude Lips/Rod | DTVA |  |  |  | Inner Seal | DDVI |  |  |  | | | | | | |
| High and Low Lips/Rod | DTVB |  |  |  | Lateral Seal | DDVO |  |  |  | | | | | | |
| Material | | PTFE and Spring | | | | | Material | | PTFE and Spring | | | | | | |
| Application | | Standard hydraulic cylinder/General machinery | | | | | Application | | Seal joint/General machinery | | | | | | |
| Action | | Rotary | | | | | Action | | Static | | | | | | |
| Page | | 159 | | | | | | | | | | | | | |

O-Ring Series

| Type | Figure | Technical Data | | | Application | Material | Action | Page |
|------|---|-------------------|---------------|------------------|----------------------|------------------------------|--------|------|
| | | Temp. Range °C | Speed ≤m/s | Pressure ≤MPa | | | | |
| OR |  | -55/+250 | - | 40 | Mechanical equipment | NBR/FKM EPDM/ SILICONE | Double | 165 |



1. Installation Recommendation



2. Installation Sizes

| Rod Diameter d_N h9 | | | Groove Diameter | Groove Width | Radius | Radial Clearance S max. | | | O-Ring Cross- Section |
|--------------------------|----------------------|---------------------------|--------------------|-----------------|--------|----------------------------|-------|-------|-----------------------------|
| Standard Application | Light Application | Heavy Duty Application | D_1 H9 | $L_1+0.2$ | R_1 | 10MPa | 20MPa | 40MPa | d_2 |
| 3-7.9 | 8-18.9 | - | $d_N+4.9$ | 2.2 | 0.4 | 0.3 | 0.20 | 0.15 | 1.78 |
| 8-18.9 | 19-37.9 | - | $d_N+7.3$ | 3.2 | 0.6 | 0.4 | 0.25 | 0.15 | 2.62 |
| 19-37.9 | 38-199.9 | 8-18.9 | $d_N+10.7$ | 4.2 | 1.0 | 0.4 | 0.25 | 0.20 | 3.53 |
| 38-199.9 | 200-255.9 | 19-37.9 | $d_N+15.1$ | 6.3 | 1.3 | 0.5 | 0.30 | 0.20 | 5.33 |
| 200-255.9 | 256-649.9 | 38-199.9 | $d_N+20.5$ | 8.1 | 1.8 | 0.6 | 0.35 | 0.25 | 7.00 |
| 256-649.9 | 650-999.9 | 200-255.9 | $d_N+24.0$ | 8.1 | 1.8 | 0.6 | 0.35 | 0.25 | 7.00 |
| 650-999.9 | ≥ 1000.0 | 256-649.9 | $d_N+27.3$ | 9.5 | 2.5 | 0.7 | 0.50 | 0.30 | 8.40 |
| ≥ 1000.0 | - | 650-999.9 | $d_N+38.0$ | 13.8 | 3.0 | 1.0 | 0.70 | 0.60 | 12.00 |



GSJ

3. Application and properties

Applicable to high and low speed reciprocating motion and high pressure system cylinder rod sealing. Good dimensional stability, not affected by temperature, low friction, strong corrosion resistance, could work in the situation with or without lubrication, easy installation.

Meet the standards of GB/T 15242.1-94 and GB/T 15242.3-94.

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|--------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3 - 1600mm | 0 - 60MPa | -45°C +200°C | 15 m/s | hydraulic oil, flame retardant liquid, water, gas |

6. Installation Dimensions

| Rod Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimensions |
|-------------------|-------------------|---------------------|----------------|-------------------|
| d _N h9 | D ₁ H9 | L ₁ +0.2 | | |
| 4 | 8.9 | 2.2 | GSJ4*8.9*2.2 | 5.28*1.78 |
| 5 | 9.9 | 2.2 | GSJ5*9.9*2.2 | 6.75*1.78 |
| 6 | 10.9 | 2.2 | GSJ6*10.9*2.2 | 7.65*1.78 |
| 8 | 12.9 | 2.2 | GSJ8*12.9*2.2 | 9.25*1.78 |
| 8 | 15.3 | 3.2 | GSJ8*15.3*3.2 | 10.77*2.62 |
| 10 | 14.9 | 2.2 | GSJ10*14.9*2.2 | 11.8*1.78 |
| 10 | 17.3 | 3.2 | GSJ10*17.3*3.2 | 12.37*2.62 |
| 12 | 16.9 | 2.2 | GSJ12*16.9*2.2 | 13.3*1.78 |
| 12 | 19.3 | 3.2 | GSJ12*19.3*3.2 | 13.94*2.62 |
| 14 | 18.9 | 2.2 | GSJ14*18.9*2.2 | 15.6*1.78 |
| 14 | 21.3 | 3.2 | GSJ14*21.3*3.2 | 15.54*2.62 |
| 15 | 19.9 | 2.2 | GSJ15*19.9*2.2 | 16.67*1.78 |
| 15 | 22.3 | 3.2 | GSJ15*22.3*3.2 | 17.12*2.62 |
| 16 | 20.9 | 2.2 | GSJ16*20.9*2.2 | 17.17*1.78 |
| 16 | 23.3 | 3.2 | GSJ16*23.3*3.2 | 18.72*2.62 |
| 18 | 22.9 | 2.2 | GSJ18*22.9*2.2 | 18.77*1.78 |
| 18 | 25.3 | 3.2 | GSJ18*25.3*3.2 | 20.29*2.62 |
| 19 | 29.7 | 4.2 | GSJ19*29.7*4.2 | 23.39*3.53 |
| 20 | 27.3 | 3.2 | GSJ20*27.3*3.2 | 21.89*2.62 |
| 20 | 30.7 | 4.2 | GSJ20*30.7*4.2 | 23.39*3.53 |
| 22 | 29.3 | 3.2 | GSJ22*29.3*3.2 | 23.47*2.62 |



GSJ

| Rod Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimensions |
|-------------------|-------------------|---------------------|-----------------|-------------------|
| d _N h9 | D ₁ H9 | L ₁ +0.2 | | |
| 22 | 32.7 | 4.2 | GSJ22*32.7*4.2 | 26.57*3.53 |
| 25 | 32.3 | 3.2 | GSJ25*32.3*3.2 | 26.64*2.62 |
| 25 | 35.7 | 4.2 | GSJ25*35.7*4.2 | 29.74*3.53 |
| 28 | 38.7 | 4.2 | GSJ28*38.7*4.2 | 31.34*3.53 |
| 30 | 40.7 | 4.2 | GSJ30*40.7*4.2 | 34.52*3.53 |
| 32 | 42.7 | 4.2 | GSJ32*42.7*4.2 | 36.09*3.53 |
| 35 | 45.7 | 4.2 | GSJ35*45.7*4.2 | 37.69*3.53 |
| 36 | 46.7 | 4.2 | GSJ36*46.7*4.2 | 40.87*3.53 |
| 38 | 53.1 | 6.3 | GSJ38*53.1*6.3 | 43.82*5.33 |
| 40 | 50.7 | 4.2 | GSJ40*50.7*4.2 | 44.04*3.53 |
| 40 | 55.1 | 6.3 | GSJ40*55.1*6.3 | 43.82*5.33 |
| 42 | 57.1 | 6.3 | GSJ42*57.1*6.3 | 46.99*5.33 |
| 45 | 55.7 | 4.2 | GSJ45*55.7*4.2 | 47.22*3.53 |
| 45 | 60.1 | 6.3 | GSJ45*60.1*6.3 | 50.17*5.33 |
| 50 | 60.7 | 4.2 | GSJ50*60.7*4.2 | 53.57*3.53 |
| 50 | 65.1 | 6.3 | GSJ50*65.1*6.3 | 56.52*5.33 |
| 55 | 70.1 | 6.3 | GSJ55*70.1*6.3 | 59.69*5.33 |
| 56 | 66.7 | 4.2 | GSJ56*66.7*4.2 | 59.92*3.53 |
| 56 | 71.1 | 6.3 | GSJ56*71.1*6.3 | 59.69*5.33 |
| 56 | 76.5 | 8.1 | GSJ56*76.5*8.1 | 62.87*6.99 |
| 60 | 75.1 | 6.3 | GSJ60*75.1*6.3 | 66.04*5.33 |
| 63 | 73.7 | 4.2 | GSJ63*73.7*4.2 | 66.27*3.53 |
| 63 | 78.1 | 6.3 | GSJ63*78.1*6.3 | 69.22*5.33 |
| 65 | 75.7 | 4.2 | GSJ65*75.7*4.2 | 69.44*3.53 |
| 65 | 80.1 | 6.3 | GSJ65*80.1*6.3 | 69.22*5.33 |
| 70 | 80.7 | 4.2 | GSJ70*80.7*4.2 | 72.62*3.53 |
| 70 | 85.1 | 6.3 | GSJ70*85.1*6.3 | 75.57*5.33 |
| 70 | 90.5 | 8.1 | GSJ70*90.5*8.1 | 78.74*6.99 |
| 75 | 85.7 | 4.2 | GSJ75*85.7*4.2 | 78.97*3.53 |
| 75 | 90.1 | 6.3 | GSJ75*90.1*6.3 | 78.74*5.33 |
| 80 | 90.7 | 4.2 | GSJ80*90.7*4.2 | 82.14*3.53 |
| 80 | 95.1 | 6.3 | GSJ80*95.1*6.3 | 85.09*5.33 |
| 80 | 100.5 | 8.1 | GSJ80*100.5*8.1 | 88.27*6.99 |
| 85 | 95.7 | 4.2 | GSJ85*95.7*4.2 | 88.49*3.53 |
| 85 | 100.1 | 6.3 | GSJ85*100.1*6.3 | 91.44*5.33 |
| 85 | 105.5 | 8.1 | GSJ85*105.5*8.1 | 91.44*6.99 |
| 90 | 100.7 | 4.2 | GSJ90*100.7*4.2 | 94.84*3.53 |
| 90 | 105.1 | 6.3 | GSJ90*105.1*6.3 | 95.5*5.33 |
| 90 | 110.5 | 8.1 | GSJ90*110.5*8.1 | 97.79*6.99 |



G S J

| Rod Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimensions |
|-------------------|-------------------|---------------------|------------------|-------------------|
| d _N h9 | D ₁ H9 | L ₁ +0.2 | | |
| 95 | 105.7 | 4.2 | GSJ95*105.7*4.2 | 98.02*3.53 |
| 95 | 110.1 | 6.3 | GSJ95*110.1*6.3 | 100.97*5.33 |
| 100 | 110.7 | 4.2 | GSJ100*110.7*4.2 | 104.37*3.53 |
| 100 | 115.1 | 6.3 | GSJ100*115.1*6.3 | 104.14*5.33 |
| 100 | 120.5 | 8.1 | GSJ100*120.5*8.1 | 107.32*6.99 |
| 105 | 120.1 | 6.3 | GSJ105*120.1*6.3 | 110.49*5.33 |
| 105 | 125.5 | 8.1 | GSJ105*125.5*8.1 | 113.67*6.99 |
| 110 | 120.7 | 4.2 | GSJ110*120.7*4.2 | 113.89*3.53 |
| 110 | 125.1 | 6.3 | GSJ110*125.1*6.3 | 113.67*5.33 |
| 110 | 130.5 | 8.1 | GSJ110*130.5*8.1 | 116.84*6.99 |
| 115 | 130.1 | 6.3 | GSJ115*130.1*6.3 | 120.02*5.33 |
| 120 | 135.1 | 6.3 | GSJ120*135.1*6.3 | 126.37*5.33 |
| 120 | 140.5 | 8.1 | GSJ120*140.5*8.1 | 126.37*6.99 |
| 125 | 140.1 | 6.3 | GSJ125*140.1*6.3 | 129.54*5.33 |
| 125 | 145.5 | 8.1 | GSJ125*145.5*8.1 | 132.72*6.99 |
| 130 | 145.1 | 6.3 | GSJ130*145.1*6.3 | 135.89*5.33 |
| 130 | 150.5 | 8.1 | GSJ130*150.5*8.1 | 135.89*6.99 |
| 140 | 150.7 | 4.2 | GSJ140*150.7*4.2 | 142.47*3.53 |
| 140 | 155.1 | 6.3 | GSJ140*155.1*6.3 | 145.42*5.33 |
| 140 | 160.5 | 8.1 | GSJ140*160.5*8.1 | 148.59*6.99 |
| 145 | 160.1 | 6.3 | GSJ145*160.1*6.3 | 148.59*5.33 |
| 145 | 165.5 | 8.1 | GSJ145*165.5*8.1 | 151.77*6.99 |
| 150 | 165.1 | 6.3 | GSJ150*165.1*6.3 | 155*5.33 |
| 150 | 170.5 | 8.1 | GSJ150*170.5*8.1 | 158.12*6.99 |
| 160 | 175.1 | 6.3 | GSJ160*175.1*6.3 | 164.47*5.33 |
| 160 | 180.5 | 8.1 | GSJ160*180.5*8.1 | 164.47*6.99 |
| 165 | 180.1 | 6.3 | GSJ165*180.1*6.3 | 170.82*5.33 |
| 170 | 185.1 | 6.3 | GSJ170*185.1*6.3 | 175*5.33 |
| 170 | 190.5 | 8.1 | GSJ170*190.5*8.1 | 177.17*6.99 |
| 180 | 195.1 | 6.3 | GSJ180*195.1*6.3 | 183.32*5.33 |
| 180 | 200.5 | 8.1 | GSJ180*200.5*8.1 | 186.02*6.99 |
| 190 | 205.1 | 6.3 | GSJ190*205.1*6.3 | 196.22*5.33 |
| 200 | 215.1 | 6.3 | GSJ200*215.1*6.3 | 205*5.33 |
| 200 | 220.5 | 8.1 | GSJ200*220.5*8.1 | 206*6.99 |
| 210 | 230.5 | 8.1 | GSJ210*230.5*8.1 | 215.27*6.99 |
| 220 | 240.5 | 8.1 | GSJ220*240.5*8.1 | 227.97*6.99 |
| 230 | 245.1 | 6.3 | GSJ230*245.1*6.3 | 234.32*5.66 |
| 230 | 250.5 | 8.1 | GSJ230*250.5*8.1 | 236*6.99 |
| 240 | 260.5 | 8.1 | GSJ240*260.5*8.1 | 243*6.99 |



GSJ

| Rod Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimensions |
|-------------------|-------------------|---------------------|------------------|-------------------|
| d _N h9 | D ₁ H9 | L ₁ +0.2 | | |
| 250 | 270.5 | 8.1 | GSJ250*270.5*8.1 | 253.37*6.99 |
| 256 | 280 | 8.1 | GSJ256*280*8.1 | 266.07*6.99 |
| 260 | 284 | 8.1 | GSJ260*284*8.1 | 266.07*6.99 |
| 270 | 294 | 8.1 | GSJ270*294*8.1 | 278.77*6.99 |
| 280 | 304 | 8.1 | GSJ280*304*8.1 | 291.47*6.99 |
| 290 | 314 | 8.1 | GSJ290*314*8.1 | 300*6.99 |
| 300 | 324 | 8.1 | GSJ300*324*8.1 | 307*6.99 |
| 320 | 344 | 8.1 | GSJ320*344*8.1 | 329.57*6.99 |
| 330 | 354 | 8.1 | GSJ330*354*8.1 | 355*6.99 |
| 340 | 364 | 8.1 | GSJ340*364*8.1 | 345*6.99 |
| 350 | 374 | 8.1 | GSJ350*374*8.1 | 354.97*6.99 |
| 360 | 384 | 8.1 | GSJ360*384*8.1 | 367.67*6.99 |
| 370 | 394 | 8.1 | GSJ370*394*8.1 | 380.37*6.99 |
| 380 | 404 | 8.1 | GSJ380*404*8.1 | 387*6.99 |
| 390 | 414 | 8.1 | GSJ390*414*8.1 | 400*6.99 |
| 400 | 424 | 8.1 | GSJ400*424*8.1 | 405.26*6.99 |
| 410 | 434 | 8.1 | GSJ410*434*8.1 | 417.96*6.99 |
| 420 | 444 | 8.1 | GSJ420*444*8.1 | 430.66*6.99 |
| 430 | 454 | 8.1 | GSJ430*454*8.1 | 437*6.99 |
| 440 | 464 | 8.1 | GSJ440*464*8.1 | 450*6.99 |
| 450 | 474 | 8.1 | GSJ450*474*8.1 | 456.06*6.99 |
| 460 | 484 | 8.1 | GSJ460*484*8.1 | 468.76*6.99 |
| 480 | 504 | 8.1 | GSJ480*504*8.1 | 487*6.99 |
| 490 | 514 | 8.1 | GSJ490*514*8.1 | 500*6.99 |
| 500 | 524 | 8.1 | GSJ500*524*8.1 | 506.87*6.99 |
| 520 | 544 | 8.1 | GSJ520*544*8.1 | 532.26*6.99 |
| 540 | 564 | 8.1 | GSJ540*564*8.1 | 552.66*6.99 |
| 550 | 574 | 8.1 | GSJ550*574*8.1 | 560*6.99 |
| 580 | 604 | 8.1 | GSJ580*604*8.1 | 582.68*6.99 |
| 600 | 624 | 8.1 | GSJ600*624*8.1 | 608.08*6.99 |
| 620 | 644 | 8.1 | GSJ620*644*8.1 | 633.48*6.99 |
| 630 | 654 | 8.1 | GSJ630*654*8.1 | 640*6.99 |
| 640 | 664 | 8.1 | GSJ640*664*8.1 | 658.88*6.99 |
| 650 | 677.3 | 9.5 | GSJ650*677.3*9.5 | 660*8.4 |
| 660 | 687.3 | 9.5 | GSJ660*687.3*9.5 | 670*8.4 |
| 680 | 707.3 | 9.5 | GSJ680*707.3*9.5 | 690*8.4 |
| 685 | 712.3 | 9.5 | GSJ685*712.3*9.5 | 695*8.4 |
| 700 | 727.3 | 9.5 | GSJ700*727.3*9.5 | 710*8.4 |
| 710 | 737.3 | 9.5 | GSJ710*737.3*9.5 | 720*8.4 |




GSJ

| Rod Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimensions |
|-------------------|-------------------|---------------------|--------------------|-------------------|
| d _N h9 | D ₁ H9 | L ₁ +0.2 | | |
| 730 | 757.3 | 9.5 | GSJ730*757.3*9.5 | 740*8.4 |
| 750 | 777.3 | 9.5 | GSJ750*777.3*9.5 | 760*8.4 |
| 760 | 787.3 | 9.5 | GSJ760*787.3*9.5 | 770*8.4 |
| 780 | 807.3 | 9.5 | GSJ780*807.3*9.5 | 790*8.4 |
| 790 | 817.3 | 9.5 | GSJ790*817.3*9.5 | 800*8.4 |
| 800 | 827.3 | 9.5 | GSJ800*827.3*9.5 | 810*8.4 |
| 810 | 837.3 | 9.5 | GSJ810*837.3*9.5 | 823*8.4 |
| 820 | 847.3 | 9.5 | GSJ820*847.3*9.5 | 830*8.4 |
| 830 | 857.3 | 9.5 | GSJ830*857.3*9.5 | 843*8.4 |
| 850 | 877.3 | 9.5 | GSJ850*877.3*9.5 | 860*8.4 |
| 870 | 897.3 | 9.5 | GSJ870*897.3*9.5 | 883*8.4 |
| 880 | 907.3 | 9.5 | GSJ880*907.3*9.5 | 890*8.4 |
| 890 | 917.3 | 9.5 | GSJ890*917.3*9.5 | 903*8.4 |
| 900 | 927.3 | 9.5 | GSJ900*927.3*9.5 | 910*8.4 |
| 930 | 957.3 | 9.5 | GSJ930*957.3*9.5 | 943*8.4 |
| 950 | 977.3 | 9.5 | GSJ950*977.3*9.5 | 960*8.4 |
| 1000 | 1027.3 | 9.5 | GSJ1000*1027.3*9.5 | 1000*8.4 |
| 1000 | 1038 | 13.8 | GSJ1000*1038*13.8 | 1016*12 |



1. Installation Recommendation



2. Installation Sizes

| Rod Diameter d_N h9 | | | Groove Diameter | Groove Width | Radius | Radial Clearance S max. | | | O-Ring Cross- Section |
|--------------------------|----------------------|------------------------------|--------------------|-----------------|--------|----------------------------|-------|-------|-----------------------------|
| Standard Application | Light Application | Heavy Duty Application | D_1 H9 | $L_1+0.2$ | R_1 | 10MPa | 20MPa | 40MPa | d_2 |
| 3-7.9 | 8-18.9 | - | $d_N+4.9$ | 2.2 | 0.4 | 0.3 | 0.20 | 0.15 | 1.78 |
| 8-18.9 | 19-37.9 | - | $d_N+7.3$ | 3.2 | 0.6 | 0.4 | 0.25 | 0.15 | 2.62 |
| 19-37.9 | 38-199.9 | 8-18.9 | $d_N+10.7$ | 4.2 | 1.0 | 0.4 | 0.25 | 0.20 | 3.53 |
| 38-199.9 | 200-255.9 | 19-37.9 | $d_N+15.1$ | 6.3 | 1.3 | 0.5 | 0.30 | 0.20 | 5.33 |
| 200-225.9 | 256-649.9 | 38-199.9 | $d_N+20.5$ | 8.1 | 1.8 | 0.6 | 0.35 | 0.25 | 7.00 |
| 256-649.9 | 650-999.9 | 200-255.9 | $d_N+24.0$ | 8.1 | 1.8 | 0.6 | 0.35 | 0.25 | 7.00 |
| 650-999.9 | ≥ 1000.0 | 256-649.9 | $d_N+27.3$ | 9.5 | 2.5 | 0.7 | 0.50 | 0.30 | 8.40 |
| ≥ 1000.0 | - | 650-999.9 | $d_N+38.0$ | 13.8 | 3.0 | 1.0 | 0.70 | 0.60 | 12.00 |



G S I

3. Application and properties

Applicable to high and low speed reciprocating motion environment, a wide range of fluids and high temperature condition. Suitable for larger gap of piston rod. Low friction, simple groove, be able to work in the medium with oil spots.

Meet the standard of GB/T 15242.3.

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|--------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3 - 1600mm | 0 - 60MPa | -45°C +200°C | 15 m/s | hydraulic oil, flame retardant liquid, water, gas |

6. Installation Dimensions

| Rod Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimensions |
|-------------------|-------------------|---------------------|----------------|-------------------|
| D _N h9 | D ₁ H9 | L ₁ +0.2 | | |
| 4 | 8.9 | 2.2 | GSI4*8.9*2.2 | 5.6*1.8 |
| 5 | 9.9 | 2.2 | GSI5*9.9*2.2 | 6.7*1.8 |
| 6 | 10.9 | 2.2 | GSI6*10.9*2.2 | 7.65*1.78 |
| 8 | 12.9 | 2.2 | GSI8*12.9*2.2 | 9.5*1.8 |
| 8 | 15.3 | 3.2 | GSI8*15.3*3.2 | 10.77*2.62 |
| 10 | 14.9 | 2.2 | GSI10*14.9*2.2 | 11.8*1.8 |
| 10 | 17.3 | 3.2 | GSI10*17.3*3.2 | 12.37*2.62 |
| 12 | 16.9 | 2.2 | GSI12*16.9*2.2 | 14.0*1.78 |
| 12 | 19.3 | 3.2 | GSI12*19.3*3.2 | 13.94*2.62 |
| 14 | 18.9 | 2.2 | GSI14*18.9*2.2 | 15.6*1.78 |
| 14 | 21.3 | 3.2 | GSI14*21.3*3.2 | 17.12*2.62 |
| 15 | 19.9 | 2.2 | GSI15*19.9*2.2 | 17.17*1.78 |
| 15 | 22.3 | 3.2 | GSI15*22.3*3.2 | 17.12*2.62 |
| 16 | 20.9 | 2.2 | GSI16*20.9*2.2 | 17.17*1.78 |
| 16 | 23.3 | 3.2 | GSI16*23.3*3.2 | 18.72*2.62 |
| 18 | 22.9 | 2.2 | GSI18*22.9*2.2 | 20.35*1.78 |
| 18 | 25.3 | 3.2 | GSI18*25.3*3.2 | 20.29*2.62 |
| 19 | 29.7 | 4.2 | GSI19*29.7*4.2 | 23.39*3.53 |
| 20 | 27.3 | 3.2 | GSI20*27.3*3.2 | 21.89*2.62 |
| 20 | 30.7 | 4.2 | GSI20*30.7*4.2 | 25.0*3.53 |
| 22 | 29.3 | 3.2 | GSI22*29.3*3.2 | 25.07*2.62 |



G S I

| Rod Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimensions |
|-------------------|-------------------|---------------------|----------------|-------------------|
| D _N h9 | D ₁ H9 | L ₁ +0.2 | | |
| 22 | 32.7 | 4.2 | GSI22*32.7*4.2 | 26.57*3.53 |
| 24 | 31.3 | 3.2 | GSI24*31.3*3.2 | 26.64*2.62 |
| 25 | 32.3 | 3.2 | GSI25*32.3*3.2 | 28.24*2.62 |
| 25 | 35.7 | 4.2 | GSI25*35.7*4.2 | 29.74*3.53 |
| 26 | 36.7 | 4.2 | GSI26*36.7*4.2 | 29.74*3.53 |
| 28 | 35.3 | 3.2 | GSI28*35.3*3.2 | 29.82*2.62 |
| 28 | 38.7 | 4.2 | GSI28*38.7*4.2 | 32.92*3.53 |
| 30 | 37.3 | 3.2 | GSI30*37.3*3.2 | 32.99*2.62 |
| 30 | 40.7 | 4.2 | GSI30*40.7*4.2 | 34.52*3.53 |
| 32 | 39.3 | 3.2 | GSI32*39.3*3.2 | 34.59*2.62 |
| 32 | 42.7 | 4.2 | GSI32*42.7*4.2 | 36.09*3.53 |
| 35 | 42.3 | 3.2 | GSI35*42.3*3.2 | 37.77*2.62 |
| 35 | 45.7 | 4.2 | GSI35*45.7*4.2 | 37.69*3.53 |
| 36 | 43.3 | 3.2 | GSI36*43.3*3.2 | 39.34*2.62 |
| 36 | 46.7 | 4.2 | GSI36*46.7*4.2 | 40.87*3.53 |
| 38 | 48.7 | 4.2 | GSI38*48.7*4.2 | 40.87*3.53 |
| 38 | 53.1 | 6.3 | GSI38*53.1*6.3 | 43.82*5.33 |
| 40 | 50.7 | 4.2 | GSI40*50.7*4.2 | 44.04*3.53 |
| 40 | 55.1 | 6.3 | GSI40*55.1*6.3 | 43.82*5.33 |
| 42 | 52.7 | 4.2 | GSI42*52.7*4.2 | 47.22*3.53 |
| 42 | 57.1 | 6.3 | GSI42*57.1*6.3 | 46.99*5.33 |
| 45 | 55.7 | 4.2 | GSI45*55.7*4.2 | 50.39*3.53 |
| 45 | 60.1 | 6.3 | GSI45*60.1*6.3 | 50.17*5.33 |
| 48 | 58.7 | 4.2 | GSI48*58.7*4.2 | 51.5*3.55 |
| 48 | 63.1 | 6.3 | GSI48*63.1*6.3 | 53.34*5.33 |
| 50 | 60.7 | 4.2 | GSI50*60.7*4.2 | 53.57*3.53 |
| 50 | 65.1 | 6.3 | GSI50*65.1*6.3 | 56.52*5.33 |
| 52 | 62.7 | 4.2 | GSI52*62.7*4.2 | 56.74*3.53 |
| 52 | 67.1 | 6.3 | GSI52*67.1*6.3 | 56.52*5.33 |
| 54 | 69.1 | 6.3 | GSI54*69.1*6.3 | 59.69*5.33 |
| 55 | 65.7 | 4.2 | GSI55*65.7*4.2 | 59.92*3.53 |
| 55 | 70.1 | 6.3 | GSI55*70.1*6.3 | 59.69*5.33 |
| 56 | 66.7 | 4.2 | GSI56*66.7*4.2 | 59.92*3.53 |
| 56 | 71.1 | 6.3 | GSI56*71.1*6.3 | 62.87*5.33 |
| 58 | 73.1 | 6.3 | GSI58*73.1*6.3 | 62.87*5.33 |
| 60 | 70.7 | 4.2 | GSI60*70.7*4.2 | 63.09*3.53 |
| 60 | 75.1 | 6.3 | GSI60*75.1*6.3 | 66.04*5.33 |
| 63 | 73.7 | 4.2 | GSI63*73.7*4.2 | 66.27*3.53 |
| 63 | 78.1 | 6.3 | GSI63*78.1*6.3 | 69.22*5.33 |



G S I

| Rod Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimensions |
|-------------------|-------------------|---------------------|------------------|-------------------|
| D _N h9 | D ₁ H9 | L ₁ +0.2 | | |
| 65 | 80.1 | 6.3 | GSI65*80.1*6.3 | 69.22*5.33 |
| 67 | 77.7 | 4.2 | GSI67*77.7*4.2 | 72.62*3.53 |
| 70 | 80.7 | 4.2 | GSI70*80.7*4.2 | 75.79*3.53 |
| 70 | 85.1 | 6.3 | GSI70*85.1*6.3 | 75.57*5.33 |
| 72 | 82.7 | 4.2 | GSI72*82.7*4.2 | 75.79*3.53 |
| 75 | 85.7 | 4.2 | GSI75*85.7*4.2 | 78.97*3.53 |
| 75 | 90.1 | 6.3 | GSI75*90.1*6.3 | 81.92*5.33 |
| 80 | 90.7 | 4.2 | GSI80*90.7*4.2 | 85.32*3.53 |
| 80 | 95.1 | 6.3 | GSI80*95.1*6.3 | 85.09*5.33 |
| 83 | 93.7 | 4.2 | GSI83*93.7*4.2 | 88.49*3.53 |
| 85 | 100.1 | 6.3 | GSI85*100.1*6.3 | 91.44*5.33 |
| 86 | 96.7 | 4.2 | GSI86*96.7*4.2 | 91.67*3.53 |
| 90 | 100.7 | 4.2 | GSI90*100.7*4.2 | 94.84*3.53 |
| 90 | 105.1 | 6.3 | GSI90*105.1*6.3 | 94.62*5.33 |
| 92 | 102.7 | 4.2 | GSI92*102.7*4.2 | 98.02*3.53 |
| 95 | 105.7 | 4.2 | GSI95*105.7*4.2 | 101.19*3.53 |
| 95 | 110.1 | 6.3 | GSI95*110.1*6.3 | 100.97*5.33 |
| 100 | 110.7 | 4.2 | GSI100*110.7*4.2 | 104.37*3.53 |
| 100 | 115.1 | 6.3 | GSI100*115.1*6.3 | 107.32*5.33 |
| 105 | 115.7 | 4.2 | GSI105*115.7*4.2 | 110.72*3.53 |
| 105 | 120.1 | 6.3 | GSI105*120.1*6.3 | 110.49*5.33 |
| 110 | 120.7 | 4.2 | GSI110*120.7*4.2 | 113.89*3.53 |
| 110 | 125.1 | 6.3 | GSI110*125.1*6.3 | 116.84*5.33 |
| 110 | 130.5 | 8.1 | GSI110*130.5*8.1 | 120.02*7.00 |
| 112 | 127.1 | 6.3 | GSI112*127.1*6.3 | 116.84*5.33 |
| 115 | 125.7 | 4.2 | GSI115*125.7*4.2 | 120.24*3.53 |
| 115 | 130.1 | 6.3 | GSI115*130.1*6.3 | 120.02*5.33 |
| 118 | 133.1 | 6.3 | GSI118*133.1*6.3 | 123.19*5.33 |
| 120 | 130.7 | 4.2 | GSI120*130.7*4.2 | 123.42*3.53 |
| 120 | 135.1 | 6.3 | GSI120*135.1*6.3 | 126.37*5.33 |
| 125 | 135.7 | 4.2 | GSI125*135.7*4.2 | 129.77*3.53 |
| 125 | 140.1 | 6.3 | GSI125*140.1*6.3 | 129.54*5.33 |
| 129 | 139.7 | 4.2 | GSI129*139.7*4.2 | 132.97*3.53 |
| 130 | 140.7 | 4.2 | GSI130*140.7*4.2 | 136.12*3.53 |
| 130 | 145.1 | 6.3 | GSI130*145.1*6.3 | 135.89*5.33 |
| 135 | 145.7 | 4.2 | GSI135*145.7*4.2 | 139.29*3.53 |
| 135 | 150.1 | 6.3 | GSI135*150.1*6.3 | 142.24*5.33 |
| 140 | 150.7 | 4.2 | GSI140*150.7*4.2 | 145.64*3.53 |
| 140 | 155.1 | 6.3 | GSI140*155.1*6.3 | 148.82*3.53 |



G S I

| Rod Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimensions |
|-------------------|-------------------|---------------------|------------------|-------------------|
| D _N h9 | D ₁ H9 | L ₁ +0.2 | | |
| 145 | 155.7 | 4.2 | GSI145*155.7*4.2 | 145.42*5.33 |
| 145 | 160.1 | 6.3 | GSI145*160.1*6.3 | 151.77*5.33 |
| 150 | 165.1 | 6.3 | GSI150*165.1*6.3 | 158.12*5.33 |
| 160 | 175.1 | 6.3 | GSI160*175.1*6.3 | 164.47*5.33 |
| 160 | 180.5 | 8.1 | GSI160*180.5*8.1 | 170.82*6.99 |
| 165 | 180.1 | 6.3 | GSI165*180.1*6.3 | 170.82*5.33 |
| 170 | 180.7 | 4.2 | GSI170*180.7*4.2 | 177.39*3.53 |
| 170 | 185.1 | 6.3 | GSI170*185.1*6.3 | 177.17*5.33 |
| 175 | 190.1 | 6.3 | GSI175*190.1*6.3 | 183.52*5.33 |
| 180 | 190.7 | 4.2 | GSI180*190.7*4.2 | 183.74*3.53 |
| 180 | 195.1 | 6.3 | GSI180*195.1*6.3 | 183.52*5.33 |
| 180 | 200.5 | 8.1 | GSI180*200.5*8.1 | 189.87*6.99 |
| 190 | 200.7 | 4.2 | GSI190*200.7*4.2 | 196.44*3.53 |
| 190 | 205.1 | 6.3 | GSI190*205.1*6.3 | 196.22*5.33 |
| 200 | 215.1 | 6.3 | GSI200*215.1*6.3 | 208.92*5.33 |
| 200 | 220.5 | 8.1 | GSI200*220.5*8.1 | 208.92*6.99 |
| 205 | 220.1 | 6.3 | GSI205*220.1*6.3 | 208.92*5.33 |
| 210 | 225.1 | 6.3 | GSI210*225.1*6.3 | 215.27*5.33 |
| 220 | 235.1 | 6.3 | GSI220*235.1*6.3 | 227.97*5.33 |
| 220 | 240.5 | 8.1 | GSI220*240.5*8.1 | 227.97*6.99 |
| 230 | 245.1 | 6.3 | GSI230*245.1*6.3 | 234.32*5.33 |
| 230 | 250.5 | 8.1 | GSI230*250.5*8.1 | 240.67*6.99 |
| 240 | 255.1 | 6.3 | GSI240*255.1*6.3 | 247.02*5.33 |
| 240 | 260.5 | 8.1 | GSI240*260.5*8.1 | 253*37*6.99 |
| 250 | 270.5 | 8.1 | GSI250*270.5*8.1 | 266.07*6.99 |
| 260 | 284 | 8.1 | GSI260*284*8.1 | 266.07*6.99 |
| 270 | 290.5 | 8.1 | GSI270*290.5*8.1 | 278.77*6.99 |
| 270 | 294 | 8.1 | GSI270*294*8.1 | 278.77*6.99 |
| 275 | 299 | 8.1 | GSI275*299*8.1 | 291.47*6.99 |
| 280 | 300.5 | 8.1 | GSI280*300.5*8.1 | 291*47*6.99 |
| 280 | 304 | 8.1 | GSI280*304*8.1 | 291.47*6.99 |
| 290 | 310.5 | 8.1 | GSI290*310.5*8.1 | 304.17*6.99 |
| 290 | 314 | 8.1 | GSI290*314*8.1 | 304.17*6.99 |
| 300 | 324 | 8.1 | GSI300*324*8.1 | 316.87*6.99 |
| 310 | 334 | 8.1 | GSI310*334*8.1 | 316.87*6.99 |
| 320 | 344 | 8.1 | GSI320*344*8.1 | 329.57*6.99 |
| 330 | 354 | 8.1 | GSI330*354*8.1 | 342.27*6.99 |
| 340 | 364 | 8.1 | GSI340*364*8.1 | 354.97*6.99 |
| 350 | 374 | 8.1 | GSI350*374*8.1 | 367.67*6.99 |




G S I

| Rod Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimensions |
|-------------------|-------------------|---------------------|------------------|-------------------|
| D _N h9 | D ₁ H9 | L ₁ +0.2 | | |
| 360 | 384 | 8.1 | GSI360*384*8.1 | 367.67*6.99 |
| 370 | 394 | 8.1 | GSI370*394*8.1 | 380.37*6.99 |
| 380 | 404 | 8.1 | GSI380*404*8.1 | 393.07*6.99 |
| 390 | 414 | 8.1 | GSI390*414*8.1 | 405.26*6.99 |
| 400 | 424 | 8.1 | GSI400*424*8.1 | 417.96*6.99 |
| 410 | 434 | 8.1 | GSI410*434*8.1 | 417.96.6.99 |
| 420 | 444 | 8.1 | GSI420*444*8.1 | 430.66*6.99 |
| 430 | 454 | 8.1 | GSI430*454*8.1 | 443.36*6.99 |
| 440 | 464 | 8.1 | GSI440*464*8.1 | 456.06*6.99 |
| 450 | 474 | 8.1 | GSI450*474*8.1 | 468.76*6.99 |
| 460 | 484 | 8.1 | GSI460*484*8.1 | 481.46*6.99 |
| 470 | 494 | 8.1 | GSI470*494*8.1 | 484.46*6.99 |
| 480 | 504 | 8.1 | GSI480*504*8.1 | 494*16*6.99 |
| 490 | 514 | 8.1 | GSI490*514*8.1 | 506.86*6.99 |
| 500 | 524 | 8.1 | GSI500*524*8.1 | 506.86*6.99 |
| 550 | 574 | 8.1 | GSI550*574*8.1 | 557.66*6.99 |
| 600 | 624 | 8.1 | GSI600*624*8.1 | 608.08*6.99 |
| 650 | 677.3 | 9.5 | GSI650*677.3*9.5 | 663*8.4 |
| 700 | 724 | 8.1 | GSI700*724*8.1 | 712*6.99 |
| 740 | 767.3 | 9.5 | GSI740*767.3*9.5 | 753*8.4 |
| 800 | 827.3 | 9.5 | GSI800*827.3*9.5 | 813*8.4 |
| 850 | 877.3 | 9.5 | GSI850*877.3*9.5 | 863*8.4 |
| 900 | 927.3 | 9.5 | GSI900*927.3*9.5 | 913*8.4 |
| 950 | 977.3 | 9.5 | GSI950*977.3*9.5 | 963*8.4 |



1. Installation Recommendation



2. Application and properties

Applicable to high and low speed reciprocating motion environment, a wide range of fluids and high temperature condition. Suitable for larger gap of piston rod. Low friction, simple groove, be able to work in the medium with oil spots.

3. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|--------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3 - 1600mm | 0 - 60MPa | -30°C +200°C | 15 m/s | hydraulic oil, flame retardant liquid, water, gas |



G S W

5. Installation Dimensions

| Rod Dia. | Outer Dia. | Width | Order No. |
|----------|-------------------|---------------------|----------------|
| d h9 | D ₁ H9 | L ₁ +0.2 | |
| 40 | 50 | 4.2 | GSW40*50*4.2 |
| 45 | 55 | 4.2 | GSW45*55*4.2 |
| 50 | 60 | 4.2 | GSW50*60*4.2 |
| 50 | 65 | 6.8 | GSW50*65*6.8 |
| 53 | 63 | 4.2 | GSW53*63*4.2 |
| 55 | 65 | 4.2 | GSW55*65*4.2 |
| 55 | 70 | 6.8 | GSW55*70*6.8 |
| 60 | 70 | 4.2 | GSW60*70*4.2 |
| 60 | 75 | 6.8 | GSW60*75*6.8 |
| 63 | 73 | 4.2 | GSW63*73*4.2 |
| 65 | 75 | 4.2 | GSW65*75*4.2 |
| 65 | 80 | 6.8 | GSW65*80*6.8 |
| 67 | 77 | 4.2 | GSW67*77*4.2 |
| 70 | 80 | 4.2 | GSW70*80*4.2 |
| 70 | 82 | 6.8 | GSW70*85*6.8 |
| 75 | 85 | 4.2 | GSW75*85*4.2 |
| 75 | 90 | 6.8 | GSW75*90*6.8 |
| 80 | 90 | 4.2 | GSW80*90*4.2 |
| 80 | 75 | 6.8 | GSW80*95*6.8 |
| 85 | 100 | 6.8 | GSW85*100*6.8 |
| 90 | 105 | 6.8 | GSW90*105*6.8 |
| 95 | 110 | 6.8 | GSW95*110*6.8 |
| 100 | 115 | 6.8 | GSW100*115*6.8 |
| 106 | 121 | 6.8 | GSW106*121*6.8 |
| 110 | 125 | 6.8 | GSW110*125*6.8 |
| 115 | 130 | 6.8 | GSW115*130*6.8 |
| 120 | 135 | 6.8 | GSW120*135*6.8 |
| 125 | 140 | 6.8 | GSW125*140*6.8 |
| 130 | 145 | 6.8 | GSW130*145*6.8 |
| 135 | 150 | 6.8 | GSW135*150*6.8 |
| 140 | 155 | 6.8 | GSW140*155*6.8 |
| 145 | 160 | 6.8 | GSW145*160*6.8 |
| 150 | 165 | 6.8 | GSW150*165*6.8 |
| 155 | 170 | 6.8 | GSW155*170*6.8 |
| 160 | 175 | 6.8 | GSW160*175*6.8 |
| 165 | 180 | 6.8 | GSW165*180*6.8 |
| 170 | 185 | 6.8 | GSW170*185*6.8 |
| 175 | 190 | 6.8 | GSW175*190*6.8 |
| 180 | 200 | 8.1 | GSW180*200*8.1 |




GSW

| Rod Dia. | Outer Dia. | Width | Order No. |
|----------|-------------------|---------------------|--|
| d h9 | D ₁ H9 | L ₁ +0.2 | |
| 185 | 205 | 6.8 | GSW185*205*8.1 GSW190*210*8.1 GSW195*215*8.1 |
| 190 | 210 | 6.8 | |
| 195 | 215 | 8.1 | |
| 200 | 220 | 8.1 | GSW200*220*8.1 GSW210*230*8.1 GSW215*235*8.1 |
| 210 | 230 | 8.1 | |
| 215 | 235 | 8.1 | |
| 220 | 240 | 8.1 | GSW220*240*8.1 GSW230*250*8.1 GSW235*255*8.1 |
| 230 | 250 | 8.1 | |
| 235 | 255 | 8.1 | |
| 255 | 275 | 8.1 | GSW255*275*8.1 GSW260*280*8.1 GSW265*285*8.1 |
| 260 | 280 | 8.1 | |
| 265 | 285 | 8.1 | |
| 270 | 290 | 8.1 | GSW270*290*8.1 GSW275*295*8.1 GSW280*300*8.1 |
| 275 | 295 | 8.1 | |
| 280 | 300 | 8.1 | |
| 285 | 310 | 9.5 | GSW285*310*9.5 GSW290*315*9.5 GSW295*320*9.5 |
| 290 | 315 | 9.5 | |
| 295 | 320 | 9.5 | |
| 300 | 325 | 9.5 | GSW300*325*9.5 GSW310*335*9.5 GSW320*345*9.5 |
| 310 | 335 | 9.5 | |
| 320 | 345 | 9.5 | |
| 330 | 355 | 9.5 | GSW330*355*9.5 GSW340*365*9.5 GSW350*375*9.5 |
| 340 | 365 | 9.5 | |
| 350 | 375 | 9.5 | |
| 360 | 385 | 9.5 | GSW360*385*9.5 GSW370*395*9.5 GSW380*405*9.5 |
| 370 | 395 | 9.5 | |
| 380 | 405 | 9.5 | |
| 390 | 415 | 9.5 | GSW390*415*9.5 GSW400*425*9.5 |
| 400 | 425 | 9.5 | |



1. Installation Recommendation



2. Installation Sizes

| Rod Diameter | Outer Diameter | Groove Width | Install Chamfer | Radius | Radial Clearance S max. | | |
|--------------|----------------|--------------|-----------------|----------------|-------------------------|-------|-------|
| d f8 | D H8 | L+0.2 | L ₁ | R ₁ | 10MPa | 20MPa | 40MPa |
| 50-69.9 | d+15.0 | 7.5 | 5.0 | 0.4 | 0.5 | 0.4 | 0.3 |
| 70-149.9 | d+20.0 | 10.1 | 6.0 | 0.4 | 0.7 | 0.5 | 0.4 |
| 200-244.9 | d+25.0 | 12.5 | 8.5 | 0.4 | 0.8 | 0.6 | 0.5 |
| 245-519.9 | d+30.0 | 15.0 | 10.0 | 0.8 | 0.9 | 0.7 | 0.6 |
| 520-769.9 | d+35.0 | 17.5 | 13.0 | 1.2 | 1.0 | 0.8 | 0.7 |
| 770-1500 | d+40.0 | 20.0 | 15.0 | 1.2 | 1.0 | 0.8 | 0.7 |

3. Application and properties

Applied for larger diameter piston rods and heavy-duty hydraulic rod sealing system in hard working conditions. High pressure resistance, excellent resistance to gap extrusion, wear-resisting.

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM



G S J - W

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 50 - 1600mm | 0 - 60MPa | -30°C +100°C | 5 m/s | hydraulic oil, flame retardant liquid, water, gas |

6. Installation Dimensions

| Rod Dia. | Outer Dia. | Groove Width | Order No. |
|----------|------------|--------------|-------------------|
| d f8 | D H8 | L+0.2 | |
| 50 | 65 | 7.5 | GSJ-W50*65*7.5 |
| 60 | 75 | 7.5 | GSJ-W60*75*7.5 |
| 70 | 85 | 7.5 | GSJ-W70*85*7.5 |
| 75 | 95 | 10 | GSJ-W75*95*10 |
| 80 | 100 | 10 | GSJ-W80*100*10 |
| 100 | 120 | 10 | GSJ-W100*120*10 |
| 110 | 130 | 10 | GSJ-W110*130*10 |
| 115 | 135 | 10 | GSJ-W115*135*10 |
| 120 | 140 | 10 | GSJ-W120*140*10 |
| 130 | 150 | 10 | GSJ-W130*150*10 |
| 140 | 160 | 10 | GSJ-W140*160*10 |
| 145 | 165 | 10 | GSJ-W145*165*10 |
| 150 | 170 | 10 | GSJ-W150*170*10 |
| 160 | 180 | 10 | GSJ-W160*180*10 |
| 170 | 190 | 10 | GSJ-W170*190*10 |
| 175 | 195 | 10 | GSJ-W175*195*10 |
| 180 | 200 | 10 | GSJ-W180*200*10 |
| 200 | 220 | 10 | GSJ-W200*220*10 |
| 230 | 255 | 12.5 | GSJ-W230*255*12.5 |
| 240 | 265 | 12.5 | GSJ-W240*265*12.5 |
| 250 | 275 | 12.5 | GSJ-W250*275*12.5 |
| 260 | 285 | 12.5 | GSJ-W260*285*12.5 |
| 265 | 290 | 12.5 | GSJ-W265*290*12.5 |
| 270 | 295 | 12.5 | GSJ-W270*295*12.5 |
| 280 | 305 | 12.5 | GSJ-W280*305*12.5 |
| 290 | 315 | 12.5 | GSJ-W290*315*12.5 |
| 300 | 325 | 12.5 | GSJ-W300*325*12.5 |
| 310 | 340 | 15.0 | GSJ-W310*340*15 |
| 315 | 345 | 15.0 | GSJ-W315*345*15 |
| 320 | 350 | 15.0 | GSJ-W320*350*15 |



| Rod Dia. | Outer Dia. | Groove Width | Order No. |
|----------|------------|--------------|-------------------|
| d f8 | D H8 | L+0.2 | |
| 330 | 360 | 15.0 | GSJ-W330*360*15 |
| 340 | 370 | 15.0 | GSJ-W340*370*15 |
| 350 | 380 | 15.0 | GSJ-W350*380*15 |
| 360 | 390 | 15.0 | GSJ-W360*390*15 |
| 370 | 400 | 15.0 | GSJ-W370*400*15 |
| 380 | 410 | 15.0 | GSJ-W380*410*15 |
| 390 | 420 | 15.0 | GSJ-W390*420*15 |
| 400 | 430 | 15.0 | GSJ-W400*430*15 |
| 410 | 440 | 15.0 | GSJ-W410*440*15 |
| 420 | 450 | 15.0 | GSJ-W420*450*15 |
| 430 | 460 | 15.0 | GSJ-W430*460*15 |
| 440 | 470 | 15.0 | GSJ-W440*470*15 |
| 450 | 480 | 15.0 | GSJ-W450*480*15 |
| 460 | 490 | 15.0 | GSJ-W460*490*15 |
| 470 | 500 | 15.0 | GSJ-W470*500*15 |
| 480 | 510 | 15.0 | GSJ-W480*510*15 |
| 490 | 520 | 15.0 | GSJ-W490*520*15 |
| 500 | 530 | 15.0 | GSJ-W500*530*15 |
| 510 | 540 | 15.0 | GSJ-W510*540*15 |
| 520 | 550 | 15.0 | GSJ-W520*550*15 |
| 530 | 560 | 15.0 | GSJ-W530*560*15 |
| 540 | 575 | 17.5 | GSJ-W540*575*17.5 |
| 545 | 580 | 17.5 | GSJ-W545*580*17.5 |
| 550 | 585 | 17.5 | GSJ-W550*585*17.5 |
| 560 | 595 | 17.5 | GSJ-W560*595*17.5 |
| 570 | 605 | 17.5 | GSJ-W570*605*17.5 |
| 580 | 615 | 17.5 | GSJ-W580*615*17.5 |
| 590 | 625 | 17.5 | GSJ-W590*625*17.5 |
| 600 | 635 | 17.5 | GSJ-W600*635*17.5 |
| 620 | 655 | 17.5 | GSJ-W620*655*17.5 |
| 630 | 665 | 17.5 | GSJ-W630*665*17.5 |
| 640 | 675 | 17.5 | GSJ-W640*675*17.5 |
| 645 | 680 | 17.5 | GSJ-W645*680*17.5 |
| 650 | 685 | 17.5 | GSJ-W650*685*17.5 |
| 660 | 695 | 17.5 | GSJ-W660*695*17.5 |
| 670 | 705 | 17.5 | GSJ-W670*705*17.5 |
| 680 | 715 | 17.5 | GSJ-W680*715*17.5 |
| 690 | 725 | 17.5 | GSJ-W690*725*17.5 |
| 700 | 740 | 20.0 | GSJ-W700*740*20 |




GSJ - W

| Rod Dia. | Outer Dia. | Groove Width | Order No. |
|----------|------------|--------------|-------------------|
| d f8 | D H8 | L+0.2 | |
| 720 | 760 | 20.0 | GSJ-W720*760*20 |
| 730 | 770 | 20.0 | GSJ-W730*770*20 |
| 740 | 780 | 20.0 | GSJ-W740*780*20 |
| 750 | 790 | 20.0 | GSJ-W750*790*20 |
| 760 | 800 | 20.0 | GSJ-W760*800*20 |
| 770 | 810 | 20.0 | GSJ-W770*810*20 |
| 790 | 830 | 20.0 | GSJ-W790*830*20 |
| 800 | 840 | 20.0 | GSJ-W800*840*20 |
| 810 | 850 | 20.0 | GSJ-W810*850*20 |
| 820 | 860 | 20.0 | GSJ-W820*860*20 |
| 830 | 870 | 20.0 | GSJ-W830*870*20 |
| 850 | 890 | 20.0 | GSJ-W850*890*20 |
| 900 | 940 | 20.0 | GSJ-W900*940*20 |
| 950 | 990 | 20.0 | GSJ-W950*990*20 |
| 1000 | 1040 | 20.0 | GSJ-W1000*1040*20 |



1. Installation Recommendation



2. Installation Sizes

| Rod Diameter d e8 | Groove Diameter D H9 | Groove Width L D10 | H |
|-------------------|----------------------|--------------------|----|
| 20-30 | d+8 | 7.5 | 7 |
| 31-35 | d+8 | 7.5 | 7 |
| 36-44 | d+8 | 8.5 | 8 |
| 45-55 | d+10 | 11.0 | 10 |
| 56-119 | d+15 | 13.0 | 12 |
| 120-319 | d+20 | 17.0 | 16 |
| 320-499 | d+30 | 21.0 | 20 |
| >499 | d+40 | 26.5 | 25 |

3. Application and properties

Applicable to hydraulic cylinder piston rod, generally used in conjunction with the guide sleeve. The special-shaped Y-Ring has the sealing function, provides the elasticity to the seal ring, and compensates for the abrasion. Wear-resisting, non stick slip phenomenon. It has a high stability under pressure and harsh conditions.



TDI

4. Standard materials

Sealing ring: filled PTFE

Y-Ring: NBR / PU

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|--|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 20 - 1600mm | 0 - 60MPa | -30°C +100°C | 1 m/s | Petroleum base hydraulic oil, nonflammable hydraulic fluid, water, and others. |

6. Installation Dimensions

| Rod Dia. | Outer Dia. | Groove Width | Order No. |
|----------|------------|--------------|--------------|
| d e8 | D H9 | L D10 | |
| 20 | 28 | 7.5 | TDI20*28*7.5 |
| 22 | 30 | 7.5 | |
| 23 | 31 | 7.5 | |
| 25 | 33 | 7.5 | TDI25*33*7.5 |
| 28 | 36 | 7.5 | |
| 30 | 38 | 7.5 | |
| 32 | 40 | 7.5 | TDI32*40*7.5 |
| 35 | 43 | 7.5 | |
| 36 | 44 | 8.5 | |
| 40 | 48 | 8.5 | TDI40*48*8.5 |
| 42 | 50 | 8.5 | |
| 45 | 55 | 11 | |
| 47 | 57 | 11 | TDI47*57*11 |
| 48 | 58 | 11 | |
| 50 | 60 | 11 | |
| 52 | 62 | 11 | TDI52*62*11 |
| 55 | 65 | 11 | |
| 56 | 71 | 13 | |
| 60 | 75 | 13 | TDI60*75*13 |
| 63 | 78 | 13 | |
| 65 | 80 | 13 | |
| 68 | 78 | 13 | TDI68*78*13 |
| 70 | 85 | 13 | |
| 72 | 87 | 13 | |
| 75 | 90 | 13 | TDI75*90*13 |
| 80 | 95 | 13 | |
| 83 | 98 | 13 | |




TDI

| Rod Dia. | Outer Dia. | Groove Width | Order No. |
|----------|------------|--------------|---|
| d e8 | D H9 | L D10 | |
| 85 | 100 | 13 | TDI85*100*13 TDI87*102*13 TDI90*105*13 |
| 87 | 102 | 13 | |
| 90 | 105 | 13 | |
| 95 | 110 | 13 | TDI95*110*13 TDI96*111*13 TDI100*115*13 |
| 96 | 111 | 13 | |
| 100 | 115 | 13 | |
| 100 | 120 | 15 | TDI100*120*15 TDI105*120*13 TDI110*125*13 |
| 105 | 120 | 13 | |
| 110 | 125 | 13 | |
| 115 | 126 | 16 | TDI115*126*16 TDI115*130*13 TDI120*140*17 |
| 115 | 130 | 13 | |
| 120 | 140 | 17 | |
| 125 | 145 | 17 | TDI125*145*17 TDI130*150*17 TDI135*155*17 |
| 130 | 150 | 17 | |
| 135 | 155 | 17 | |
| 140 | 155 | 18 | TDI140*155*18 TDI140*160*17 TDI150*170*17 |
| 140 | 160 | 17 | |
| 150 | 170 | 17 | |
| 155 | 175 | 17 | TDI155*175*17 TDI160*180*17 TDI165*185*17 |
| 160 | 180 | 17 | |
| 165 | 185 | 17 | |
| 170 | 190 | 17 | TDI170*190*17 TDI175*195*17 TDI180*200*17 |
| 175 | 195 | 17 | |
| 180 | 200 | 17 | |
| 185 | 205 | 17 | TDI185*205*17 TDI190*210*17 TDI200*220*17 |
| 190 | 210 | 17 | |
| 200 | 220 | 17 | |
| 220 | 240 | 17 | TDI220*240*17 TDI225*245*17 TDI230*250*17 |
| 225 | 245 | 17 | |
| 230 | 250 | 17 | |
| 240 | 260 | 17 | TDI240*260*17 TDI250*270*17 TDI260*280*17 |
| 250 | 270 | 17 | |
| 260 | 280 | 17 | |
| 280 | 300 | 17 | TDI280*300*17 TDI300*320*17 TDI350*380*21 |
| 300 | 320 | 17 | |
| 350 | 380 | 21 | |
| 500 | 540 | 26.5 | TDI500*540*26.5 TDI630*670*26.5 TDI1000*1040*26.5 |
| 630 | 670 | 26.5 | |
| 1000 | 1040 | 26.5 | |



1. Installation Recommendation



2. Installation Sizes

| \varnothing - range | e |
|-----------------------|----|
| 20-56 | 6 |
| 60-100 | 7 |
| 105-290 | 10 |
| 300-630 | 15 |
| | |
| | |

| d e8 | D H9 | L D10 | H |
|----------|--------|-------|------|
| 22-39 | d+7.2 | 4.0 | 3.5 |
| 40-79 | d+10.0 | 5.0 | 4.5 |
| 80-100 | d+13.8 | 7.5 | 7.0 |
| >100-250 | d+20.0 | 10.0 | 9.5 |
| >250-600 | d+30.0 | 15.0 | 14.5 |
| >600 | d+40.0 | 20.0 | 19.5 |

3. Application and properties

L-Ring support and guide to ensure a tight sealing environment. Easy installation, wear resistance, anti extrusion, low friction, non stick slip phenomenon.

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

L-Ring: POM / PA



R D I

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 20 - 1600mm | 0 - 45MPa | -30°C +100°C | 1 m/s | hydraulic oil, flame retardant liquid, water, gas |

6. Installation Dimensions

| d e8 | D ₁ H9 | H | L D10 | e | Order No. |
|------|-------------------|-----|-------|----|------------------|
| 22 | 29.2 | 3.5 | 4 | 6 | RDI22*29.2*3.5 |
| 25 | 32.2 | 3.5 | 4 | 6 | RDI25*32.2*3.5 |
| 28 | 35.2 | 3.5 | 4 | 6 | RDI28*35.2*3.5 |
| 30 | 37.2 | 3.5 | 4 | 6 | RDI30*37.2*3.5 |
| 32 | 39.2 | 3.5 | 4 | 6 | RDI32*39.2*3.5 |
| 35 | 42.2 | 3.5 | 4 | 6 | RDI35*42.2*3.5 |
| 36 | 43.2 | 3.5 | 4 | 6 | RDI36*43.2*3.5 |
| 40 | 50 | 4.5 | 5 | 6 | RDI40*50*4.5 |
| 42 | 52 | 4.5 | 5 | 6 | RDI42*52*4.5 |
| 45 | 55 | 4.5 | 5 | 6 | RDI45*55*4.5 |
| 50 | 60 | 4.5 | 5 | 6 | RDI50*60*4.5 |
| 55 | 65 | 4.5 | 5 | 6 | RDI55*65*4.5 |
| 56 | 66 | 4.5 | 5 | 6 | RDI56*66*4.5 |
| 60 | 70 | 4.5 | 5 | 7 | RDI60*70*4.5 |
| 63 | 73 | 4.5 | 7.5 | 7 | RDI63*73*4.5 |
| 65 | 75 | 4.5 | 7.5 | 7 | RDI65*75*4.5 |
| 70 | 80 | 4.5 | 7.5 | 7 | RDI70*80*4.5 |
| 72 | 82 | 4.5 | 7.5 | 7 | RDI72*82*4.5 |
| 75 | 85 | 4.5 | 7.5 | 7 | RDI75*85*4.5 |
| 80 | 93.8 | 7.0 | 7.5 | 7 | RDI80*93.8*7.0 |
| 85 | 98.8 | 7.0 | 7.5 | 7 | RDI85*98.8*7.0 |
| 90 | 103.8 | 7.0 | 7.5 | 7 | RDI90*103.8*7.0 |
| 95 | 108.8 | 7.0 | 7.5 | 7 | RDI95*108.8*7.0 |
| 100 | 113.8 | 7.0 | 7.5 | 7 | RDI100*113.8*7.0 |
| 105 | 125 | 9.5 | 10 | 10 | RDI105*125*9.5 |
| 110 | 130 | 9.5 | 10 | 10 | RDI110*130*9.5 |
| 115 | 135 | 9.5 | 10 | 10 | RDI115*135*9.5 |
| 120 | 140 | 9.5 | 10 | 10 | RDI120*140*9.5 |
| 125 | 145 | 9.5 | 10 | 10 | RDI125*145*9.5 |
| 130 | 150 | 9.5 | 10 | 10 | RDI130*150*9.5 |



R D I

| d e8 | D ₁ H9 | H | L D10 | e | Order No. |
|------|-------------------|------|-------|----|-----------------|
| 140 | 160 | 9.5 | 10 | 10 | RDI140*160*9.5 |
| 150 | 170 | 9.5 | 10 | 10 | RDI150*170*9.5 |
| 160 | 180 | 9.5 | 10 | 10 | RDI160*180*9.5 |
| 165 | 185 | 9.5 | 10 | 10 | RDI165*185*9.5 |
| 170 | 190 | 9.5 | 10 | 10 | RDI170*190*9.5 |
| 180 | 200 | 9.5 | 10 | 10 | RDI180*200*9.5 |
| 190 | 210 | 9.5 | 10 | 10 | RDI190*210*9.5 |
| 200 | 220 | 9.5 | 10 | 10 | RDI200*220*9.5 |
| 220 | 240 | 9.5 | 10 | 10 | RDI220*240*9.5 |
| 225 | 245 | 9.5 | 10 | 10 | RDI225*245*9.5 |
| 230 | 250 | 9.5 | 10 | 10 | RDI230*250*9.5 |
| 240 | 260 | 9.5 | 10 | 10 | RDI240*260*9.5 |
| 250 | 270 | 9.5 | 10 | 10 | RDI250*270*9.5 |
| 260 | 290 | 14.5 | 15 | 10 | RDI260*290*14.5 |
| 280 | 310 | 14.5 | 15 | 15 | RDI280*310*14.5 |
| 290 | 320 | 14.5 | 15 | 15 | RDI290*320*14.5 |
| 300 | 330 | 14.5 | 15 | 15 | RDI300*330*14.5 |
| 320 | 350 | 14.5 | 15 | 15 | RDI320*350*14.5 |
| 350 | 380 | 14.5 | 15 | 15 | RDI350*380*14.5 |
| 360 | 390 | 14.5 | 15 | 15 | RDI360*390*14.5 |
| 380 | 410 | 14.5 | 15 | 15 | RDI380*410*14.5 |
| 400 | 430 | 14.5 | 15 | 15 | RDI400*430*14.5 |
| 415 | 445 | 14.5 | 15 | 15 | RDI415*445*14.5 |
| 420 | 450 | 14.5 | 15 | 15 | RDI420*450*14.5 |
| 425 | 455 | 14.5 | 15 | 15 | RDI425*455*14.5 |
| 450 | 480 | 14.5 | 15 | 15 | RDI450*480*14.5 |
| 480 | 510 | 14.5 | 15 | 15 | RDI480*510*14.5 |
| 500 | 530 | 14.5 | 15 | 15 | RDI500*530*14.5 |
| 550 | 580 | 14.5 | 15 | 15 | RDI550*580*14.5 |
| 560 | 590 | 14.5 | 15 | 15 | RDI560*590*14.5 |
| 600 | 630 | 14.5 | 15 | 15 | RDI600*630*14.5 |
| 630 | 670 | 19.5 | 20 | 15 | RDI630*670*19.5 |
| 650 | 690 | 19.5 | 20 | 15 | RDI650*690*19.5 |
| 680 | 720 | 19.5 | 20 | 15 | RDI680*720*19.5 |
| 700 | 740 | 19.5 | 20 | 15 | RDI700*740*19.5 |
| 720 | 760 | 19.5 | 20 | 15 | RDI720*760*19.5 |
| 750 | 790 | 19.5 | 20 | 15 | RDI750*790*19.5 |
| 800 | 840 | 19.5 | 20 | 15 | RDI800*840*19.5 |
| 850 | 890 | 19.5 | 20 | 15 | RDI850*890*19.5 |




R D I

| d e8 | D ₁ H9 | H | L D10 | e | Order No. |
|------|-------------------|------|-------|----|-------------------|
| 900 | 940 | 19.5 | 20 | 15 | RDI900*940*19.5 |
| 950 | 990 | 19.5 | 20 | 15 | RDI950*990*19.5 |
| 1000 | 1040 | 19.5 | 20 | 15 | RDI1000*1040*19.5 |



1. Installation Recommendation



2. Installation Sizes

| Rod Diameter d e8 | Groove Diameter D H9 | Groove Width L D10 | H |
|-------------------|----------------------|--------------------|----|
| 20-56 | d+10 | 16 | 15 |
| 57-140 | d+13 | 16 | 15 |
| >140 | d+15 | 16 | 15 |

3. Application and properties

Suitable for tandem type internal sealing, and can be used as fluid sealing and dust sealing simultaneously. Excellent sealing effect can be achieved in case of no pressure. Easy installation, wear-resisting, anti extrusion, low friction, non stick slip phenomenon.

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / PU



5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 50 - 1600mm | 0 - 25MPa | -30°C + 100°C | 1 m/s | hydraulic oil, flame retardant liquid, water, gas |

6. Installation Dimensions

| d e8 | D ₁ H9 | H | L D10 | e | Order No. |
|------|-------------------|----|-------|----|---------------|
| 50 | 60 | 15 | 16 | 6 | MDI50*60*15 |
| 55 | 65 | 15 | 16 | 6 | MDI55*65*15 |
| 56 | 66 | 15 | 16 | 6 | MDI56*66*15 |
| 60 | 73 | 15 | 16 | 7 | MDI60*73*15 |
| 63 | 76 | 15 | 16 | 7 | MDI63*76*15 |
| 65 | 78 | 15 | 16 | 7 | MDI65*78*15 |
| 70 | 83 | 15 | 16 | 7 | MDI70*83*15 |
| 72 | 85 | 15 | 16 | 7 | MDI72*85*15 |
| 75 | 88 | 15 | 16 | 7 | MDI75*88*15 |
| 80 | 93 | 15 | 16 | 7 | MDI80*93*15 |
| 85 | 98 | 15 | 16 | 7 | MDI85*98*15 |
| 90 | 103 | 15 | 16 | 7 | MDI90*103*15 |
| 95 | 108 | 15 | 16 | 7 | MDI95*108*15 |
| 100 | 113 | 15 | 16 | 7 | MDI100*113*15 |
| 105 | 118 | 15 | 16 | 10 | MDI105*118*15 |
| 110 | 120 | 15 | 16 | 10 | MDI110*120*15 |
| 110 | 123 | 15 | 16 | 10 | MDI110*123*15 |
| 115 | 128 | 15 | 16 | 10 | MDI115*128*15 |
| 120 | 133 | 15 | 16 | 10 | MDI120*133*15 |
| 125 | 138 | 15 | 16 | 10 | MDI125*138*15 |
| 130 | 143 | 15 | 16 | 10 | MDI130*143*15 |
| 140 | 153 | 15 | 16 | 10 | MDI140*153*15 |
| 150 | 162 | 15 | 16 | 10 | MDI150*162*15 |
| 150 | 165 | 15 | 16 | 10 | MDI150*165*15 |
| 160 | 175 | 15 | 16 | 10 | MDI160*175*15 |
| 165 | 180 | 15 | 16 | 10 | MDI165*180*15 |
| 170 | 185 | 15 | 16 | 10 | MDI170*185*15 |
| 180 | 195 | 15 | 16 | 10 | MDI180*195*15 |
| 185 | 200 | 15 | 16 | 10 | MDI185*200*15 |
| 190 | 205 | 15 | 16 | 10 | MDI190*205*15 |




MDI

| d e8 | D ₁ H9 | H | L D10 | e | Order No. |
|------|-------------------|----|-------|----|---------------|
| 200 | 215 | 15 | 16 | 10 | MDI200*215*15 |
| 220 | 235 | 15 | 16 | 10 | MDI220*235*15 |
| 225 | 240 | 15 | 16 | 10 | MDI225*240*15 |
| 230 | 245 | 15 | 16 | 10 | MDI230*245*15 |
| 240 | 255 | 15 | 16 | 10 | MDI240*255*15 |
| 250 | 265 | 15 | 16 | 10 | MDI250*265*15 |
| 260 | 275 | 15 | 16 | 10 | MDI260*275*15 |
| 280 | 295 | 15 | 16 | 10 | MDI280*295*15 |
| 290 | 305 | 15 | 16 | 10 | MDI290*305*15 |
| 300 | 312 | 15 | 16 | 15 | MDI300*312*15 |
| 300 | 315 | 15 | 16 | 15 | MDI300*315*15 |
| 320 | 335 | 15 | 16 | 15 | MDI320*335*15 |
| 350 | 365 | 15 | 16 | 15 | MDI350*365*15 |
| 360 | 375 | 15 | 16 | 15 | MDI360*375*15 |
| 380 | 395 | 15 | 16 | 15 | MDI380*395*15 |
| 400 | 415 | 15 | 16 | 15 | MDI400*415*15 |
| 450 | 465 | 15 | 16 | 15 | MDI450*465*15 |
| 480 | 495 | 15 | 16 | 15 | MDI480*495*15 |
| 500 | 515 | 15 | 16 | 15 | MDI500*515*15 |
| 550 | 565 | 15 | 16 | 15 | MDI550*565*15 |
| 560 | 575 | 15 | 16 | 15 | MDI560*575*15 |
| 600 | 615 | 15 | 16 | 15 | MDI600*615*15 |
| 650 | 665 | 15 | 16 | 15 | MDI650*665*15 |



1. Installation Recommendation



2. Application and properties

The standard combination seal is suitable for a wide range of pressure work and sliding high speed occasions. Low friction, strong wear resistance.

3. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|---------|--|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 18-1600mm | 0-35MPa | -30°C +200°C | 1.5 m/s | general hydraulic oil, water glycol Hydraulic oil and water emulsion type hydraulic oil. |




5. Installation Dimensions

| Nominal Size of Packing, and Housing dimensions | | | | Order No. |
|---|-------|-----|--------|------------------|
| d | D | H | L +0.2 | |
| 18 | 27 | 4.3 | 4.5 | SPN18*27*4.3 |
| 20 | 29 | 4.3 | 4.5 | SPN20*29*4.3 |
| 22 | 31 | 4.3 | 4.5 | SPN22*31*4.3 |
| 27 | 36 | 4.3 | 4.5 | SPN27*36*4.3 |
| 31.5 | 40.5 | 4.3 | 4.5 | SPN31.5*40.5*4.3 |
| 47 | 60 | 7.3 | 7.5 | SPN47*60*7.3 |
| 53 | 66 | 7.3 | 7.5 | SPN53*66*7.3 |
| 60 | 73 | 7.3 | 7.5 | SPN60*73*7.3 |
| 65 | 78 | 7.3 | 7.5 | SPN65*78*7.3 |
| 70 | 83 | 7.3 | 7.5 | SPN70*83*7.3 |
| 75 | 88 | 7.3 | 7.5 | SPN75*88*7.3 |
| 80 | 93 | 7.3 | 7.5 | SPN80*93*7.3 |
| 90 | 103.4 | 7.3 | 7.5 | SPN90*103.4*7.3 |
| 100 | 113.4 | 7.3 | 7.5 | SPN100*113.4*7.3 |
| 110 | 123.4 | 7.3 | 7.5 | SPN110*123.4*7.3 |
| 120 | 133.4 | 7.3 | 7.5 | SPN120*133.4*7.3 |
| 130 | 143.4 | 7.3 | 7.5 | SPN130*143.4*7.3 |
| 140 | 153.4 | 7.3 | 7.5 | SPN140*153.4*7.3 |



1. Installation Recommendation



2. Application and properties

The standard combination seal is suitable for a wide range of pressure work and sliding high speed occasions. Low friction, strong wear resistance.

3. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|---------|--|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3 - 1600mm | 0 - 35MPa | -30°C +200°C | 1.5 m/s | general hydraulic oil, water glycol Hydraulic oil and water emulsion type hydraulic oil. |

**5. Installation Dimensions**

| Nominal Size of Packing, and Housing dimensions | | | | Order No. |
|---|------|-----|--------|-------------------|
| d | D | H | L +0.2 | |
| 3 | 6 | 2.3 | 2.5 | SPNC3*6*2.5 |
| 4 | 7 | 2.3 | 2.5 | SPNC4*7*2.5 |
| 5 | 8 | 2.3 | 2.5 | SPNC5*8*2.5 |
| 6 | 9 | 2.3 | 2.5 | SPNC6*9*2.5 |
| 7 | 10 | 2.3 | 2.5 | SPNC7*10*2.5 |
| 8 | 11 | 2.3 | 2.5 | SPNC8*11*2.5 |
| 9 | 12 | 2.3 | 2.5 | SPNC9*12*2.5 |
| 10 | 13 | 2.3 | 2.5 | SPNC10*13*2.5 |
| 10 | 14 | 3.0 | 3.2 | SPNC10*14*3.2 |
| 11 | 15 | 3.0 | 3.2 | SPNC11*15*3.2 |
| 11.2 | 15.2 | 3.0 | 3.2 | SPNC11.2*15.2*3.2 |
| 12 | 16 | 3.0 | 3.2 | SPNC12*16*3.2 |
| 12.5 | 16.5 | 3.0 | 3.2 | SPNC12.5*16.5*3.2 |
| 14 | 18 | 3.0 | 3.2 | SPNC14*18*3.2 |
| 15 | 19 | 3.0 | 3.2 | SPNC15*19*3.2 |
| 16 | 20 | 3.0 | 3.2 | SPNC16*20*3.2 |
| 18 | 22 | 3.0 | 3.2 | SPNC18*22*3.2 |
| 20 | 24 | 3.0 | 3.2 | SPNC20*24*3.2 |
| 20 | 24 | 3.0 | 3.2 | SPNC20*24*3.2 |
| 21 | 25 | 3.0 | 3.2 | SPNC21*25*3.2 |
| 22 | 26 | 3.0 | 3.2 | SPNC22*26*3.2 |
| 22 | 28 | 4.4 | 4.7 | SPNC22*28*4.7 |
| 22.4 | 28.4 | 4.4 | 4.7 | SPNC22.4*28.4*4.7 |
| 24 | 30 | 4.4 | 4.7 | SPNC24*30*4.7 |
| 25 | 31 | 4.4 | 4.7 | SPNC25*31*4.7 |
| 25.5 | 31.5 | 4.4 | 4.7 | SPNC25.5*31.5*4.7 |
| 26 | 32 | 4.4 | 4.7 | SPNC26*32*4.7 |
| 28 | 34 | 4.4 | 4.7 | SPNC28*34*4.7 |
| 29 | 35 | 4.4 | 4.7 | SPNC29*35*4.7 |
| 29.5 | 35.5 | 4.4 | 4.7 | SPNC29.5*35.5*4.7 |
| 30 | 36 | 4.4 | 4.7 | SPNC30*36*4.7 |
| 31 | 37 | 4.4 | 4.7 | SPNC31*37*4.7 |
| 31.5 | 37.5 | 4.4 | 4.7 | SPNC31.5*37.5*4.7 |
| 32 | 38 | 4.4 | 4.7 | SPNC32*38*4.7 |
| 34 | 40 | 4.4 | 4.7 | SPNC34*40*4.7 |
| 35 | 41 | 4.4 | 4.7 | SPNC35*41*4.7 |
| 35.5 | 41.5 | 4.4 | 4.7 | SPNC35.5*41.5*4.7 |
| 36 | 42 | 4.4 | 4.7 | SPNC36*42*4.7 |
| 38 | 44 | 4.4 | 4.7 | SPNC38*44*4.7 |



S P N C

| Nominal Size of Packing, and Housing dimensions | | | | Order No. |
|---|-----|-----|--------|-----------------|
| d | D | H | L +0.2 | |
| 39 | 45 | 4.4 | 4.7 | SPNC39*45*4.7 |
| 40 | 46 | 4.4 | 4.7 | SPNC40*46*4.7 |
| 41 | 47 | 4.4 | 4.7 | SPNC41*47*4.7 |
| 42 | 48 | 4.4 | 4.7 | SPNC42*48*4.7 |
| 44 | 50 | 4.4 | 4.7 | SPNC44*50*4.7 |
| 45 | 51 | 4.4 | 4.7 | SPNC45*51*4.7 |
| 46 | 52 | 4.4 | 4.7 | SPNC46*52*4.7 |
| 48 | 54 | 4.4 | 4.7 | SPNC48*54*4.7 |
| 48 | 58 | 7.0 | 7.5 | SPNC48*58*7.5 |
| 49 | 55 | 4.4 | 4.7 | SPNC49*55*4.7 |
| 50 | 56 | 4.4 | 4.7 | SPNC50*56*4.7 |
| 50 | 60 | 7.0 | 7.5 | SPNC50*60*7.5 |
| 52 | 62 | 7.0 | 7.5 | SPNC52*62*7.5 |
| 53 | 63 | 7.0 | 7.5 | SPNC53*63*7.5 |
| 55 | 65 | 7.0 | 7.5 | SPNC55*65*7.5 |
| 56 | 66 | 7.0 | 7.5 | SPNC56*66*7.5 |
| 58 | 68 | 7.0 | 7.5 | SPNC58*68*7.5 |
| 60 | 70 | 7.0 | 7.5 | SPNC60*70*7.5 |
| 62 | 72 | 7.0 | 7.5 | SPNC62*72*7.5 |
| 63 | 73 | 7.0 | 7.5 | SPNC63*73*7.5 |
| 65 | 75 | 7.0 | 7.5 | SPNC65*75*7.5 |
| 67 | 77 | 7.0 | 7.5 | SPNC67*77*7.5 |
| 70 | 80 | 7.0 | 7.5 | SPNC70*80*7.5 |
| 71 | 81 | 7.0 | 7.5 | SPNC71*81*7.5 |
| 75 | 85 | 7.0 | 7.5 | SPNC75*85*7.5 |
| 80 | 90 | 7.0 | 7.5 | SPNC80*90*7.5 |
| 85 | 95 | 7.0 | 7.5 | SPNC85*95*7.5 |
| 90 | 100 | 7.0 | 7.5 | SPNC90*100*7.5 |
| 95 | 105 | 7.0 | 7.5 | SPNC95*105*7.5 |
| 100 | 110 | 7.0 | 7.5 | SPNC100*110*7.5 |
| 105 | 115 | 7.0 | 7.5 | SPNC105*115*7.5 |
| 110 | 120 | 7.0 | 7.5 | SPNC110*120*7.5 |
| 115 | 125 | 7.0 | 7.5 | SPNC115*125*7.5 |
| 120 | 130 | 7.0 | 7.5 | SPNC120*130*7.5 |
| 125 | 135 | 7.0 | 7.5 | SPNC125*135*7.5 |
| 130 | 140 | 7.0 | 7.5 | SPNC130*140*7.5 |
| 132 | 142 | 7.0 | 7.5 | SPNC132*142*7.5 |
| 135 | 145 | 7.0 | 7.5 | SPNC135*145*7.5 |
| 140 | 150 | 7.0 | 7.5 | SPNC140*150*7.5 |




SPNC

| Nominal Size of Packing, and Housing dimensions | | | | Order No. |
|---|-----|------|--------|-----------------|
| d | D | H | L +0.2 | |
| 145 | 155 | 7.0 | 7.5 | SPNC145*155*7.5 |
| 150 | 160 | 7.0 | 7.5 | SPNC150*160*7.5 |
| 150 | 165 | 10.5 | 11 | SPNC150*165*11 |
| 155 | 170 | 10.5 | 11 | SPNC155*170*11 |
| 160 | 175 | 10.5 | 11 | SPNC160*175*11 |
| 165 | 180 | 10.5 | 11 | SPNC165*180*11 |
| 170 | 185 | 10.5 | 11 | SPNC170*185*11 |
| 175 | 190 | 10.5 | 11 | SPNC175*190*11 |
| 180 | 195 | 10.5 | 11 | SPNC180*195*11 |
| 185 | 200 | 10.5 | 11 | SPNC185*200*11 |
| 190 | 205 | 10.5 | 11 | SPNC190*205*11 |
| 195 | 210 | 10.5 | 11 | SPNC195*210*11 |
| 200 | 215 | 10.5 | 11 | SPNC200*215*11 |
| 210 | 225 | 10.5 | 11 | SPNC210*225*11 |
| 220 | 235 | 10.5 | 11 | SPNC220*235*11 |
| 230 | 245 | 10.5 | 11 | SPNC230*245*11 |
| 240 | 255 | 10.5 | 11 | SPNC240*255*11 |
| 260 | 275 | 10.5 | 11 | SPNC260*275*11 |
| 280 | 295 | 10.5 | 11 | SPNC280*295*11 |
| 300 | 315 | 10.5 | 11 | SPNC300*315*11 |
| 320 | 335 | 10.5 | 11 | SPNC320*335*11 |
| 340 | 355 | 10.5 | 11 | SPNC340*355*11 |
| 375 | 390 | 10.5 | 11 | SPNC375*390*11 |



1. Installation Recommendation



2. Application and properties

Applicable to a wide range of pressure work and sliding high speed occasions. Standard combined seal. Low friction, strong wear resistance.

3. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|--------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3 - 1600mm | 0 - 35MPa | -30°C + 200°C | 1.5m/s | general hydraulic oil, water glycol hydraulic oil, oil / water emulsion type hydraulic oil. |

**5. Installation Dimensions**


| Nominal Size of Packing, and Housing dimensions | | | | Order No. |
|---|-----|-----|--------|-----------------|
| d | D | H | L +0.2 | |
| 12 | 18 | 3.0 | 3.2 | SPNO12*18*3.2 |
| 14 | 20 | 3.0 | 3.2 | SPNO14*20*3.2 |
| 16 | 22 | 3.0 | 3.2 | SPNO16*22*3.2 |
| 18 | 24 | 3.0 | 3.2 | SPNO18*24*3.2 |
| 20 | 26 | 3.0 | 3.2 | SPNO20*26*3.2 |
| 22 | 31 | 3.8 | 4 | SPNO22*31*4 |
| 25 | 34 | 3.8 | 4 | SPNO25*34*4 |
| 28 | 37 | 3.8 | 4 | SPNO28*37*4 |
| 30 | 39 | 3.8 | 4 | SPNO30*39*4 |
| 32 | 41 | 3.8 | 4 | SPNO32*41*4 |
| 36 | 45 | 3.8 | 4 | SPNO36*45*4 |
| 40 | 49 | 3.8 | 4 | SPNO40*49*4 |
| 45 | 54 | 3.8 | 4 | SPNO45*54*4 |
| 50 | 65 | 6.3 | 6.5 | SPNO50*65*6.5 |
| 56 | 71 | 6.3 | 6.5 | SPNO56*71*6.5 |
| 60 | 75 | 6.3 | 6.5 | SPNO60*75*6.5 |
| 63 | 78 | 6.3 | 6.5 | SPNO63*78*6.5 |
| 70 | 85 | 6.3 | 6.5 | SPNO70*85*6.5 |
| 75 | 90 | 6.3 | 6.5 | SPNO75*90*6.5 |
| 80 | 95 | 6.3 | 6.5 | SPNO80*95*6.5 |
| 85 | 100 | 6.3 | 6.5 | SPNO85*100*6.5 |
| 90 | 105 | 6.3 | 6.5 | SPNO90*105*6.5 |
| 95 | 110 | 6.3 | 6.5 | SPNO95*110*6.5 |
| 100 | 115 | 6.3 | 6.5 | SPNO100*115*6.5 |
| 105 | 120 | 6.3 | 6.5 | SPNO105*120*6.5 |
| 110 | 125 | 6.3 | 6.5 | SPNO110*125*6.5 |
| 115 | 130 | 6.3 | 6.5 | SPNO115*130*6.5 |
| 120 | 135 | 6.3 | 6.5 | SPNO120*135*6.5 |
| 125 | 140 | 6.3 | 6.5 | SPNO125*140*6.5 |
| 130 | 145 | 6.3 | 6.5 | SPNO130*145*6.5 |
| 135 | 150 | 6.3 | 6.5 | SPNO135*150*6.5 |
| 140 | 155 | 6.3 | 6.5 | SPNO140*155*6.5 |
| 145 | 160 | 6.3 | 6.5 | SPNO145*160*6.5 |
| 150 | 170 | 9.8 | 10 | SPNO150*170*10 |
| 160 | 180 | 9.8 | 10 | SPNO160*180*10 |
| 170 | 190 | 9.8 | 10 | SPNO170*190*10 |



| Nominal Size of Packing, and Housing dimensions | | | | Order No. |
|---|-----|-----|--------|----------------|
| d | D | H | L +0.2 | |
| 180 | 200 | 9.8 | 10 | SPNO180*200*10 |
| 190 | 210 | 9.8 | 10 | SPNO190*210*10 |
| 200 | 220 | 9.8 | 10 | SPNO200*220*10 |
| 210 | 230 | 9.8 | 10 | SPNO210*230*10 |
| 220 | 240 | 9.8 | 10 | SPNO220*240*10 |
| 224 | 244 | 9.8 | 10 | SPNO224*244*10 |
| 230 | 250 | 9.8 | 10 | SPNO230*250*10 |
| 240 | 260 | 9.8 | 10 | SPNO240*260*10 |
| 250 | 270 | 9.8 | 10 | SPNO250*270*10 |
| 260 | 280 | 9.8 | 10 | SPNO260*280*10 |
| 270 | 290 | 9.8 | 10 | SPNO270*290*10 |
| 280 | 300 | 9.8 | 10 | SPNO280*300*10 |
| 290 | 310 | 9.8 | 10 | SPNO290*310*10 |
| 300 | 320 | 9.8 | 10 | SPNO300*320*10 |
| 310 | 330 | 9.8 | 10 | SPNO310*330*10 |
| 320 | 340 | 9.8 | 10 | SPNO320*340*10 |
| 330 | 350 | 9.8 | 10 | SPNO330*350*10 |
| 340 | 360 | 9.8 | 10 | SPNO340*360*10 |
| 350 | 370 | 9.8 | 10 | SPNO350*370*10 |
| 360 | 380 | 9.8 | 10 | SPNO360*380*10 |
| 370 | 390 | 9.8 | 10 | SPNO370*390*10 |
| 380 | 400 | 9.8 | 10 | SPNO380*400*10 |



1. Installation Recommendation



2. Installation Sizes

| Bore Diameter D_N H9 | | | Groove Diameter | Groove Width | Radius | Radial Clearance S max. | | | O-Ring Cross- Section |
|---------------------------|----------------------|------------------------------|--------------------|-----------------|--------|----------------------------|-------|-------|-----------------------------|
| Standard Application | Light Application | Heavy Duty Application | d_1 h9 | $L_1+0.2$ | R_1 | 10MPa | 20MPa | 40MPa | d_2 |
| 8-14.9 | 15-39.9 | - | D_N -4.9 | 2.2 | 0.4 | 0.3 | 0.20 | 0.15 | 1.78 |
| 15-39.9 | 40-79.9 | - | D_N -7.5 | 3.2 | 0.6 | 0.4 | 0.25 | 0.15 | 2.62 |
| 40-79.9 | 80-132.9 | 15-39.9 | D_N -11.0 | 4.2 | 1.0 | 0.4 | 0.25 | 0.20 | 3.53 |
| 80-132.9 | 133-329.9 | 40-79.9 | D_N -15.5 | 6.3 | 1.3 | 0.5 | 0.30 | 0.20 | 5.33 |
| 133-329.9 | 330-699.9 | 80-132.9 | D_N -21.0 | 8.1 | 1.8 | 0.6 | 0.35 | 0.25 | 7.00 |
| 330-669.9 | 670-99.9 | 133-329.9 | D_N -24.5 | 8.1 | 1.8 | 0.6 | 0.35 | 0.25 | 7.00 |
| 670-999.9 | \geq 1000 | 330-669.9 | D_N -28.0 | 9.5 | 2.5 | 0.7 | 0.50 | 0.30 | 8.40 |
| \geq 1000 | \geq 1000 | \geq 1000 | D_N -38.0 | 13.8 | 3.0 | 1.0 | 0.70 | 0.60 | 12.00 |



GSF

3. Application and properties

Standard double acting seal. Suitable for reciprocating motion, allowing larger extrusion clearances, has wide application. Dynamic and static sealing property are excellent, be able to work in dusty condition. Low friction, simple groove, strong adaptability to work conditions.

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|--------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 8 - 1600mm | 0 - 60MPa | -45°C +200°C | 15 m/s | hydraulic oil, flame retardant liquid, water and others |

6. Installation Dimensions

| Bore Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimensions |
|-------------------|-------------------|---------------------|----------------|-------------------|
| D _N H9 | d ₁ h9 | L ₁ +0.2 | | |
| 8 | 3.1 | 2.2 | GSF8*3.1*2.2 | 2.90*1.78 |
| 10 | 5.1 | 2.2 | GSF10*5.1*2.2 | 4.80*1.8 |
| 12 | 7.1 | 2.2 | GSF12*7.1*2.2 | 6.70*1.8 |
| 14 | 9.1 | 2.2 | GSF14*9.1*2.2 | 8.75*1.8 |
| 15 | 10.1 | 2.2 | GSF15*10.1*2.2 | 7.59*2.62 |
| 15 | 7.5 | 3.2 | GSF15*7.5*3.2 | 8.75*1.8 |
| 16 | 11.1 | 2.2 | GSF16*11.1*2.2 | 10.82*1.78 |
| 16 | 8.5 | 3.2 | GSF16*8.5*3.2 | 7.59*2.62 |
| 18 | 13.1 | 2.2 | GSF18*13.1*2.2 | 12.42*1.78 |
| 18 | 10.5 | 3.2 | GSF18*10.5*3.2 | 9.19*2.62 |
| 20 | 15.1 | 2.2 | GSF20*15.1*2.2 | 14.00*1.78 |
| 20 | 12.5 | 3.2 | GSF20*12.5*3.2 | 12.37*2.62 |
| 24 | 19.1 | 2.2 | GSF24*19.1*2.2 | 18.77*1.78 |
| 24 | 16.5 | 3.2 | GSF24*16.5*3.2 | 15.54*2.62 |
| 25 | 17.5 | 3.2 | GSF25*17.5*3.2 | 17.12*2.62 |
| 25 | 14 | 4.2 | GSF25*14*4.2 | 13.87*3.53 |
| 28 | 20.5 | 3.2 | GSF28*20.5*3.2 | 20.29*2.62 |
| 28 | 17 | 4.2 | GSF28*17*4.2 | 15.47*3.53 |
| 30 | 22.5 | 3.2 | GSF30*22.5*3.2 | 21.89*2.62 |
| 30 | 19 | 4.2 | GSF30*19*4.2 | 26.70*1.78 |
| 32 | 24.5 | 3.2 | GSF32*24.5*3.2 | 23.47*2.62 |



GSF

| Bore Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimensions |
|-------------------|-------------------|---------------------|----------------|-------------------|
| D _N H9 | d ₁ h9 | L ₁ +0.2 | | |
| 32 | 21 | 4.2 | GSF32*21*4.2 | 20.22*3.53 |
| 35 | 27.5 | 3.2 | GSF35*27.5*3.2 | 26.64*2.62 |
| 35 | 24 | 4.2 | GSF35*24*4.2 | 23.40*3.53 |
| 36 | 28.5 | 3.2 | GSF36*28.5*3.2 | 28.24*2.62 |
| 36 | 25 | 4.2 | GSF36*25*4.2 | 23.39*3.53 |
| 38 | 30.5 | 3.2 | GSF38*30.5*3.2 | 29.82*2.62 |
| 38 | 27 | 4.2 | GSF38*27*4.2 | 25.86*3.53 |
| 40 | 32.5 | 3.2 | GSF40*32.5*3.2 | 31.42*2.62 |
| 40 | 29 | 4.2 | GSF40*29*4.2 | 28.17*3.53 |
| 45 | 37.5 | 3.2 | GSF45*37.5*3.2 | 36.5*2.62 |
| 45 | 34 | 4.2 | GSF45*34*4.2 | 32.92*3.53 |
| 48 | 40.5 | 3.2 | GSF48*40.5*3.2 | 36.09*3.53 |
| 48 | 37 | 4.2 | GSF48*37*4.2 | 36.09*3.53 |
| 50 | 39 | 4.2 | GSF50*39*4.2 | 37.70*3.53 |
| 50 | 34.5 | 6.3 | GSF50*34.5*6.3 | 32.69*5.33 |
| 52 | 41 | 4.2 | GSF52*41*4.2 | 40.87*3.53 |
| 52 | 36.5 | 6.3 | GSF52*36.5*6.3 | 35*5.33 |
| 55 | 44 | 4.2 | GSF55*44*4.2 | 44.04*3.53 |
| 55 | 39.5 | 6.3 | GSF55*39.5*6.3 | 38*5.33 |
| 56 | 45 | 4.2 | GSF56*45*4.2 | 44.04*3.53 |
| 56 | 40.5 | 6.3 | GSF56*40.5*6.3 | 39*5.33 |
| 60 | 49 | 4.2 | GSF60*49*4.2 | 47.22*3.53 |
| 60 | 44.5 | 6.3 | GSF60*44.5*6.3 | 42.5*5.33 |
| 63 | 52 | 4.2 | GSF63*52*4.2 | 50.39*3.53 |
| 63 | 47.5 | 6.3 | GSF63*47.5*6.3 | 46*5.33 |
| 64 | 53 | 4.2 | GSF64*53*4.2 | 51.5*3.53 |
| 64 | 48.5 | 6.3 | GSF64*48.5*6.3 | 46.99*5.33 |
| 65 | 54 | 4.2 | GSF65*54*4.2 | 53.57*3.53 |
| 65 | 49.5 | 6.3 | GSF65*49.5*6.3 | 48*5.33 |
| 70 | 59 | 4.2 | GSF70*59*4.2 | 56.74*3.53 |
| 70 | 54.5 | 6.3 | GSF70*54.5*6.3 | 53.34*5.33 |
| 75 | 64 | 4.2 | GSF75*64*4.2 | 63.09*3.53 |
| 75 | 59.5 | 6.3 | GSF75*59.5*6.3 | 56.52*5.33 |
| 80 | 69 | 4.2 | GSF80*69*4.2 | 66.27*3.53 |
| 80 | 64.5 | 6.3 | GSF80*64.5*6.3 | 62.87*5.33 |
| 85 | 74 | 4.2 | GSF85*74*4.2 | 72.62*3.53 |
| 85 | 69.5 | 6.3 | GSF85*69.5*6.3 | 69.22*5.33 |
| 90 | 79 | 4.2 | GSF90*79*4.2 | 78.97*3.53 |
| 90 | 74.5 | 6.3 | GSF90*74.5*6.3 | 72.39*5.33 |





G S F

| Bore Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimensions |
|-------------------|-------------------|---------------------|------------------|-------------------|
| D _N H9 | d ₁ h9 | L ₁ +0.2 | | |
| 95 | 84 | 4.2 | GSF95*84*4.2 | 82.14*3.53 |
| 95 | 79.5 | 6.3 | GSF95*79.5*6.3 | 78.74*5.33 |
| 100 | 89 | 4.2 | GSF100*89*4.2 | 88.49*3.53 |
| 100 | 84.5 | 6.3 | GSF100*84.5*6.3 | 81.92*5.33 |
| 105 | 94 | 4.2 | GSF105*94*4.2 | 91.67*3.53 |
| 105 | 89.5 | 6.3 | GSF105*89.5*6.3 | 88.27*5.33 |
| 110 | 99 | 4.2 | GSF110*99*4.2 | 98.02*3.53 |
| 110 | 94.5 | 6.3 | GSF110*94.5*6.3 | 91.44*5.33 |
| 115 | 99.5 | 6.3 | GSF115*99.5*6.3 | 97.79*5.33 |
| 120 | 104.5 | 6.3 | GSF120*104.5*6.3 | 100.97*5.33 |
| 125 | 109.5 | 6.3 | GSF125*109.5*6.3 | 107.32*5.33 |
| 125 | 104 | 8.1 | GSF125*104*8.1 | 103*7.0 |
| 130 | 114.5 | 6.3 | GSF130*114.5*6.3 | 113.67*5.33 |
| 130 | 109 | 8.1 | GSF130*109*8.1 | 108*7.0 |
| 135 | 119.5 | 6.3 | GSF135*119.5*6.3 | 118*5.33 |
| 135 | 114 | 8.1 | GSF135*114*8.1 | 113.67*7.0 |
| 140 | 124.5 | 6.3 | GSF140*124.5*6.3 | 123.19*5.33 |
| 140 | 119 | 8.1 | GSF140*119*8.1 | 116.84*7.0 |
| 145 | 124 | 8.1 | GSF145*124*8.1 | 123.19*7.0 |
| 150 | 129 | 8.1 | GSF150*129*8.1 | 126.37*7.0 |
| 155 | 134 | 8.1 | GSF155*134*8.1 | 132.72*7.0 |
| 160 | 139 | 8.1 | GSF160*139*8.1 | 135.89*7.0 |
| 165 | 144 | 8.1 | GSF165*144*8.1 | 142.24*7.0 |
| 170 | 149 | 8.1 | GSF170*149*8.1 | 145.42*7.0 |
| 175 | 154 | 8.1 | GSF175*154*8.1 | 151.77*7.0 |
| 180 | 159 | 8.1 | GSF180*159*8.1 | 158.12*7.0 |
| 190 | 169 | 8.1 | GSF190*169*8.1 | 164.47*7.0 |
| 200 | 179 | 8.1 | GSF200*179*8.1 | 177.17*7.0 |
| 210 | 189 | 8.1 | GSF210*189*8.1 | 183.52*7.0 |
| 220 | 199 | 8.1 | GSF220*199*8.1 | 196.22*7.0 |
| 230 | 209 | 8.1 | GSF230*209*8.1 | 208.9*7.0 |
| 240 | 219 | 8.1 | GSF240*219*8.1 | 215.27*7.0 |
| 250 | 229 | 8.1 | GSF250*229*8.1 | 227.97*7.0 |
| 260 | 239 | 8.1 | GSF260*239*8.1 | 240.67*7.0 |
| 270 | 249 | 8.1 | GSF270*249*8.1 | 240.67*7.0 |
| 275 | 254 | 8.1 | GSF275*254*8.1 | 253.37*7.0 |
| 280 | 259 | 8.1 | GSF280*259*8.1 | 253.37*7.0 |
| 290 | 269 | 8.1 | GSF290*269*8.1 | 266.07*7.0 |
| 300 | 279 | 8.1 | GSF300*279*8.1 | 278.77*7.0 |



GSF

| Bore Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimensions |
|-------------------|-------------------|---------------------|------------------|-------------------|
| D _N H9 | d ₁ h9 | L ₁ +0.2 | | |
| 310 | 289 | 8.1 | GSF310*289*8.1 | 278.77*7.0 |
| 320 | 299 | 8.1 | GSF320*299*8.1 | 291.47*7.0 |
| 330 | 305.5 | 8.1 | GSF330*305.5*8.1 | 304.17*7.0 |
| 340 | 315.5 | 8.1 | GSF340*315.5*8.1 | 316.87*7.0 |
| 350 | 325.5 | 8.1 | GSF350*325.5*8.1 | 316.87*7.0 |
| 360 | 335.5 | 8.1 | GSF360*335.5*8.1 | 329.57*7.0 |
| 370 | 345.5 | 8.1 | GSF370*345.5*8.1 | 342.27*7.0 |
| 380 | 355.5 | 8.1 | GSF380*355.5*8.1 | 354.97*7.0 |
| 390 | 365.5 | 8.1 | GSF390*365.5*8.1 | 365*7.0 |
| 400 | 375.5 | 8.1 | GSF400*375.5*8.1 | 367.67*7.0 |
| 410 | 385.5 | 8.1 | GSF410*385.5*8.1 | 387*7.0 |
| 420 | 395.5 | 8.1 | GSF420*395.5*8.1 | 393.07*7.0 |
| 430 | 405.5 | 8.1 | GSF430*405.5*8.1 | 405.26*7.0 |
| 440 | 415.5 | 8.1 | GSF440*415.5*8.1 | 405.26*7.0 |
| 450 | 425.5 | 8.1 | GSF450*425.5*8.1 | 417.96*7.0 |
| 460 | 435.5 | 8.1 | GSF460*435.5*8.1 | 430.66*7.0 |
| 470 | 445.5 | 8.1 | GSF470*445.5*8.1 | 443.36*7.0 |
| 480 | 455.5 | 8.1 | GSF480*455.5*8.1 | 456.06*7.0 |
| 490 | 465.5 | 8.1 | GSF490*465.5*8.1 | 462*7.0 |
| 500 | 475.5 | 8.1 | GSF500*475.5*8.1 | 468.76*7.0 |
| 510 | 485.5 | 8.1 | GSF510*485.5*8.1 | 480*7.0 |
| 520 | 495.5 | 8.1 | GSF520*495.5*8.1 | 490*7.0 |
| 530 | 505.5 | 8.1 | GSF530*505.5*8.1 | 498*7.0 |
| 540 | 515.5 | 8.1 | GSF540*515.5*8.1 | 505*7.0 |
| 550 | 525.5 | 8.1 | GSF550*525.5*8.1 | 515*7.0 |
| 560 | 535.5 | 8.1 | GSF560*535.5*8.1 | 523*7.0 |
| 570 | 545.5 | 8.1 | GSF570*545.5*8.1 | 533*7.0 |
| 580 | 555.5 | 8.1 | GSF580*555.5*8.1 | 542*7.0 |
| 600 | 575.5 | 8.1 | GSF600*575.5*8.1 | 557.66*7.0 |
| 610 | 585.5 | 8.1 | GSF610*585.5*8.1 | 567*7.0 |
| 620 | 595.5 | 8.1 | GSF620*595.5*8.1 | 576*7.0 |
| 630 | 605.5 | 8.1 | GSF630*605.5*8.1 | 586*7.0 |
| 640 | 615.5 | 8.1 | GSF640*615.5*8.1 | 608.08*7.0 |
| 650 | 625.5 | 8.1 | GSF650*625.5*8.1 | 618*7.0 |
| 660 | 635.5 | 8.1 | GSF660*635.5*8.1 | 633.48*7.0 |
| 670 | 642 | 9.5 | GSF670*642*9.5 | 630*8.4 |
| 680 | 652 | 9.5 | GSF680*652*9.5 | 650*8.4 |
| 700 | 672 | 9.5 | GSF700*672*9.5 | 670*8.4 |
| 750 | 722 | 9.5 | GSF750*722*9.5 | 720*8.4 |




GSF

| Bore Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimensions |
|-------------------|-------------------|---------------------|------------------|-------------------|
| D _N H9 | d ₁ h9 | L ₁ +0.2 | | |
| 780 | 752 | 9.5 | GSF780*752*9.5 | 750*8.4 |
| 800 | 772 | 9.5 | GSF800*772*9.5 | 770*8.4 |
| 850 | 822 | 9.5 | GSF850*822*9.5 | 820*8.4 |
| 900 | 872 | 9.5 | GSF900*872*9.5 | 870*8.4 |
| 950 | 922 | 9.5 | GSF950*922*9.5 | 920*8.4 |
| 1000 | 962 | 13.8 | GSF1000*962*13.8 | 960*12.0 |



G S D

1. Installation Recommendation



2. Installation Sizes

| Bore Diameter D _N H9 | | | Groove Diameter | Groove Width | Radius | Radial Clearance S max. | | | O-Ring Cross- Section |
|------------------------------------|----------------------|------------------------------|----------------------|---------------------|----------------|----------------------------|-------|-------|-----------------------------|
| Standard Application | Light Application | Heavy Duty Application | d ₁ h9 | L ₁ +0.2 | R ₁ | 10MPa | 20MPa | 40MPa | d ₂ |
| 8-16.9 | 17-26.9 | — | D _N -4.9 | 2.2 | 0.4 | 0.30 | 0.20 | 0.15 | 1.78 |
| 17-26.9 | 27-59.9 | — | D _N -7.3 | 3.2 | 0.6 | 0.40 | 0.25 | 0.15 | 2.62 |
| 27-59.9 | 60-199.9 | 17-26.9 | D _N -10.7 | 4.2 | 1.0 | 0.50 | 0.30 | 0.20 | 3.53 |
| 60-199.9 | 200-255.9 | 27-59.9 | D _N -15.1 | 6.3 | 1.3 | 0.70 | 0.40 | 0.25 | 5.33 |
| 200-255.9 | 256-669.9 | 60-199.9 | D _N -20.5 | 8.1 | 1.8 | 0.80 | 0.60 | 0.35 | 7.00 |
| 256-669.9 | 670-999.9 | 200-669.9 | D _N -24.0 | 8.1 | 1.8 | 0.90 | 0.70 | 0.40 | 7.00 |
| 670-999.9 | — | 256-669.9 | D _N -28.0 | 9.5 | 2.5 | 1.00 | 0.80 | 0.60 | 8.40 |
| — | 1000-2000 | — | D _N -28.0 | 9.5 | 2.5 | 1.00 | 0.80 | 0.60 | 8.40 |
| — | — | 670-999.9 | D _N -38.0 | 13.8 | 3.0 | 1.20 | 0.90 | 0.60 | 12.00 |
| 1000-2700 | — | — | D _N -38.0 | 13.8 | 3.0 | 1.20 | 0.90 | 0.60 | 12.00 |



G S D

3. Application and properties

Standard single acting sealing. Suitable for reciprocating environment, allowing larger extrusion clearances, has wide application. Dynamic and static sealing property are good, be able to work in dusty condition. Low friction, simple groove, strong adaptability to work conditions.

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|--------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 8 - 1600mm | 0 - 60MPa | -45°C +200°C | 15 m/s | hydraulic oil, flame retardant liquid, water and others |

6. Installation Dimensions

| Bore Dia. | Groove Dia. | Width | Order No. | O-Ring Dimension |
|-----------|-------------------|---------------------|----------------|------------------|
| D H9 | d ₁ h9 | L ₁ +0.2 | | |
| 9 | 4.1 | 2.2 | GSD9*4.1*2.2 | 3.68*1.78 |
| 10 | 5.1 | 2.2 | GSD10*5.1*2.2 | 4.80*1.8 |
| 12 | 7.1 | 2.2 | GSD12*7.1*2.2 | 6.70*1.8 |
| 15 | 10.1 | 2.2 | GSD15*10.1*2.2 | 9.25*1.78 |
| 18 | 10.7 | 3.2 | GSD18*10.7*3.2 | 9.19*2.62 |
| 20 | 15.1 | 2.2 | GSD20*15.1*2.2 | 14.0*1.78 |
| 20 | 12.7 | 3.2 | GSD20*12.7*3.2 | 12.37*2.62 |
| 22 | 14.7 | 3.2 | GSD22*14.7*3.2 | 13.94*2.62 |
| 25 | 17.7 | 3.2 | GSD25*17.7*3.2 | 17.12*2.62 |
| 27 | 16.3 | 4.2 | GSD27*16.3*4.2 | 15.47*3.53 |
| 28 | 17.3 | 4.2 | GSD28*17.3*4.2 | 16.4*3.53 |
| 30 | 19.3 | 4.2 | GSD30*19.3*4.2 | 18.66*3.53 |
| 32 | 24.7 | 3.2 | GSD32*24.7*3.2 | 23.47*2.62 |
| 32 | 21.3 | 4.2 | GSD32*21.3*4.2 | 20.22*3.53 |
| 35 | 24.3 | 4.2 | GSD35*24.3*4.2 | 23.40*3.53 |
| 36 | 25.3 | 4.2 | GSD36*25.3*4.2 | 24*3.53 |
| 38 | 27.3 | 4.2 | GSD38*27.3*4.2 | 26*3.53 |
| 40 | 32.7 | 3.2 | GSD40*32.7*3.2 | 31.42*2.62 |
| 40 | 29.9 | 4.2 | GSD40*29.3*4.2 | 28.17*3.53 |
| 45 | 34.3 | 4.2 | GSD45*34.3*4.2 | 32.92*3.53 |
| 48 | 37.3 | 4.2 | GSD48*37.3*4.2 | 36.09*3.53 |



G S D

| Bore Dia. | Groove Dia. | Width | Order No. | O-Ring Dimension |
|-----------|-------------------|---------------------|------------------|------------------|
| D H9 | d ₁ h9 | L ₁ +0.2 | | |
| 50 | 39.3 | 4.2 | GSD50*39.3*4.2 | 37.70*3.53 |
| 50 | 34.9 | 6.3 | GSD50*34.9*6.3 | 32.69*5.33 |
| 52 | 41.3 | 4.2 | GSD52*41.3*4.2 | 40.87*3.53 |
| 55 | 44.3 | 4.2 | GSD55*44.3*4.2 | 44.04*3.53 |
| 60 | 44.9 | 6.3 | GSD60*44.9*6.3 | 43.82*5.33 |
| 63 | 52.3 | 4.2 | GSD63*52.3*4.2 | 50.39*3.53 |
| 63 | 47.9 | 6.3 | GSD63*47.9*6.3 | 46.99*5.33 |
| 64 | 48.9 | 6.3 | GSD64*48.9*6.3 | 46.99*5.33 |
| 65 | 49.9 | 6.3 | GSD65*49.9*6.3 | 46.99*5.33 |
| 70 | 59.3 | 4.2 | GSD70*59.3*4.2 | 56.74*3.53 |
| 70 | 54.9 | 6.3 | GSD70*54.9*6.3 | 53.34*5.33 |
| 75 | 59.9 | 6.3 | GSD75*59.9*6.3 | 56.52*5.33 |
| 80 | 64.9 | 6.3 | GSD80*64.9*6.3 | 62.87*5.33 |
| 80 | 59.5 | 8.1 | GSD80*59.5*8.1 | 58*7.0 |
| 85 | 69.9 | 6.3 | GSD85*69.9*6.3 | 69.22*5.33 |
| 90 | 74.9 | 6.3 | GSD90*74.9*6.3 | 72.39*5.33 |
| 90 | 69.5 | 8.1 | GSD90*69.5*8.1 | 68*7.0 |
| 95 | 79.9 | 6.3 | GSD95*79.9*6.3 | 78.74*5.33 |
| 95 | 74.5 | 8.1 | GSD95*74.5*8.1 | 73*7.0 |
| 100 | 84.9 | 6.3 | GSD100*84.9*6.3 | 81.92*5.33 |
| 100 | 79.5 | 8.1 | GSD100*79.5*8.1 | 78*7.0 |
| 110 | 94.9 | 6.3 | GSD110*94.9*6.3 | 91.44*5.33 |
| 120 | 104.9 | 6.3 | GSD120*104.9*6.3 | 104.14*5.33 |
| 125 | 104.5 | 6.3 | GSD125*109.9*6.3 | 107.32*5.33 |
| 125 | 104.9 | 8.1 | GSD125*104.5*8.1 | 103*7.0 |
| 130 | 114.9 | 6.3 | GSD130*114.9*6.3 | 113.67*5.33 |
| 135 | 119.9 | 6.3 | GSD135*119.9*6.3 | 113.67*7.0 |
| 140 | 124.9 | 6.3 | GSD140*124.9*6.3 | 116.84*7.0 |
| 145 | 129.9 | 6.3 | GSD145*129.9*6.3 | 123.19*7.0 |
| 150 | 134.9 | 6.3 | GSD150*134.9*6.3 | 126.37*7.0 |
| 155 | 139.9 | 6.3 | GSD155*139.9*6.3 | 135.89*5.33 |
| 160 | 144.9 | 6.3 | GSD160*144.9*6.3 | 142.24*5.33 |
| 160 | 139.5 | 8.1 | GSD160*139.5*8.1 | 135.89*7.0 |
| 165 | 149.9 | 6.3 | GSD165*149.9*6.3 | 148.49*5.33 |
| 170 | 154.9 | 6.3 | GSD170*154.9*6.3 | 145.42*7.0 |
| 175 | 159.9 | 6.3 | GSD175*159.9*6.3 | 158.12*5.33 |
| 180 | 164.9 | 6.3 | GSD180*164.9*6.3 | 164.47*5.33 |
| 180 | 159.9 | 8.1 | GSD180*159.5*8.1 | 158.12*7.0 |
| 190 | 174.9 | 6.3 | GSD190*174.9*6.3 | 170.82*5.33 |



G S D

| Bore Dia. | Groove Dia. | Width | Order No. | O-Ring Dimension |
|-----------|-------------------|---------------------|------------------|------------------|
| D H9 | d ₁ h9 | L ₁ +0.2 | | |
| 190 | 169.5 | 8.1 | GSD190*169.5*8.1 | 164.47*7.0 |
| 200 | 184.9 | 6.3 | GSD200*184.9*6.3 | 183.52*5.33 |
| 200 | 179.5 | 8.1 | GSD200*179.5*8.1 | 177.17*7.0 |
| 210 | 189.5 | 8.1 | GSD210*189.5*8.1 | 183.52*7.0 |
| 220 | 204.9 | 6.3 | GSD220*204.9*6.3 | 202.57*5.33 |
| 220 | 199.5 | 8.1 | GSD220*199.5*8.1 | 196.22*7.0 |
| 230 | 209.5 | 8.1 | GSD230*209.5*8.1 | 208.92*7.0 |
| 240 | 219.5 | 8.1 | GSD240*219.5*8.1 | 215.27*7.0 |
| 250 | 229.5 | 8.1 | GSD250*229.5*8.1 | 227.97*7.0 |
| 250 | 226.0 | 8.1 | GSD250*226*8.1 | 227.97*7.0 |
| 256 | 232.0 | 8.1 | GSD256*232*8.1 | 227.97*7.0 |
| 260 | 236.0 | 8.1 | GSD260*236*8.1 | 227.97*7.0 |
| 270 | 246.0 | 8.1 | GSD270*246*8.1 | 240.67*7.0 |
| 280 | 256.0 | 8.1 | GSD280*256*8.1 | 253.37*7.0 |
| 290 | 266.0 | 8.1 | GSD290*266*8.1 | 263*7.0 |
| 300 | 276.0 | 8.1 | GSD300*276*8.1 | 266.07*7.0 |
| 310 | 286.0 | 8.1 | GSD310*286*8.1 | 278.77*7.0 |
| 320 | 299.0 | 8.1 | GSD320*299.5*8.1 | 291.47*7.0 |
| 320 | 296.0 | 8.1 | GSD320*296*8.1 | 291.47*7.0 |
| 330 | 306.0 | 8.1 | GSD330*306*8.1 | 304.17*7.0 |
| 340 | 316.0 | 8.1 | GSD340*316*8.1 | 316.87*7.0 |
| 350 | 326.0 | 8.1 | GSD350*326*8.1 | 316.87*7.0 |
| 360 | 336.0 | 8.1 | GSD360*336*8.1 | 329.57*7.0 |
| 370 | 346.0 | 8.1 | GSD370*346*8.1 | 342.27*7.0 |
| 380 | 356.0 | 8.1 | GSD380*356*8.1 | 354.97*7.0 |
| 390 | 366.0 | 8.1 | GSD390*366*8.1 | 365*7.0 |
| 400 | 376.0 | 8.1 | GSD400*376*8.1 | 367.67*7.0 |
| 410 | 386.0 | 8.1 | GSD410*386*8.1 | 385*7.0 |
| 420 | 396.0 | 8.1 | GSD420*396*8.1 | 393.07*7.0 |
| 430 | 406.0 | 8.1 | GSD430*406*8.1 | 405.25*7.0 |
| 440 | 416.0 | 8.1 | GSD440*416*8.1 | 405.25*7.0 |
| 450 | 426.0 | 8.1 | GSD450*426*8.1 | 417.95*7.0 |
| 460 | 436.0 | 8.1 | GSD460*436*8.1 | 430*7.0 |
| 470 | 446.0 | 8.1 | GSD470*446*8.1 | 445*7.0 |
| 480 | 456.0 | 8.1 | GSD480*456*8.1 | 456.06*7.0 |
| 490 | 466.0 | 8.1 | GSD490*466*8.1 | 465*7.0 |
| 500 | 476.0 | 8.1 | GSD500*476*8.1 | 468.76*7.0 |
| 510 | 486.0 | 8.1 | GSD510*486*8.1 | 478*7.0 |
| 520 | 496.0 | 8.1 | GSD520*496*8.1 | 494.15*7.0 |




G S D

| Bore Dia. | Groove Dia. | Width | Order No. | O-Ring Dimension |
|-----------|-------------------|---------------------|-------------------|------------------|
| D H9 | d ₁ h9 | L ₁ +0.2 | | |
| 530 | 506.0 | 8.1 | GSD530*506*8.1 | 500*7.0 |
| 540 | 516.0 | 8.1 | GSD540*516*8.1 | 506.85*7.0 |
| 550 | 526.0 | 8.1 | GSD550*526*8.1 | 516*7.0 |
| 560 | 536.0 | 8.1 | GSD560*536*8.1 | 526*7.0 |
| 570 | 546.0 | 8.1 | GSD570*546*8.1 | 535*7.0 |
| 580 | 556.0 | 8.1 | GSD580*556*8.1 | 545*7.0 |
| 590 | 566.0 | 8.1 | GSD590*566*8.1 | 554*7.0 |
| 600 | 576.0 | 8.1 | GSD600*576*8.1 | 557.65*7.0 |
| 610 | 586.0 | 8.1 | GSD610*586*8.1 | 568*7.0 |
| 620 | 596.0 | 8.1 | GSD620*596*8.1 | 578*7.0 |
| 630 | 606.0 | 8.1 | GSD630*606*8.1 | 590*7.0 |
| 640 | 616.0 | 8.1 | GSD640*616*8.1 | 600*7.0 |
| 650 | 626.0 | 8.1 | GSD650*626*8.1 | 608.08*7.0 |
| 660 | 636.0 | 8.1 | GSD660*636*8.1 | 618*7.0 |
| 670 | 642.7 | 9.5 | GSD670*642.7*9.5 | 640*8.4 |
| 680 | 652.7 | 9.5 | GSD680*652.7*9.5 | 650*8.4 |
| 690 | 662.7 | 9.5 | GSD690*662.7*9.5 | 660*8.4 |
| 700 | 672.7 | 9.5 | GSD700*672.7*9.5 | 670*8.4 |
| 710 | 682.7 | 9.5 | GSD710*682.7*9.5 | 680*8.4 |
| 720 | 692.7 | 9.5 | GSD720*692.7*9.5 | 690*8.4 |
| 730 | 702.7 | 9.5 | GSD730*702.7*9.5 | 700*8.4 |
| 740 | 712.7 | 9.5 | GSD740*712.7*9.5 | 710*8.4 |
| 750 | 722.7 | 9.5 | GSD750*722.7*9.5 | 720*8.4 |
| 760 | 732.7 | 9.5 | GSD760*732.7*9.5 | 730*8.4 |
| 770 | 742.7 | 9.5 | GSD770*742.7*9.5 | 740*8.4 |
| 780 | 752.7 | 9.5 | GSD780*752.7*9.5 | 750*8.4 |
| 790 | 762.7 | 9.5 | GSD790*762.7*9.5 | 760*8.4 |
| 800 | 772.7 | 9.5 | GSD800*772.7*9.5 | 770*8.4 |
| 900 | 872.7 | 9.5 | GSD900*872.7*9.5 | 870*8.4 |
| 920 | 892.7 | 9.5 | GSD920*892.7*9.5 | 890*8.4 |
| 1000 | 972.7 | 9.5 | GSD1000*972.7*9.5 | 970*8.4 |



1. Installation Recommendation



2. Application and properties

Standard double acting sealing, a wide range of applications. Friction resistance is very low, no crawling phenomenon, strong wear resistance, and saving installation space.

3. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|---------|--|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 30 - 1600mm | 0 - 35MPa | -30°C +200°C | 1.5 m/s | hydraulic oil, flame retardant liquid, water and others. |

**5. Installation Dimensions**


| Nominal Size of Packing, and Housing dimensions | | | L +0.2 | Order No. |
|---|------|------|--------|----------------|
| D | d | H | | |
| 30 | 20.5 | 4.3 | 4.5 | SPG30*20.5*4.5 |
| 31.5 | 22 | 4.3 | 4.5 | SPG31.5*22*4.5 |
| 32 | 22.5 | 4.3 | 4.5 | SPG32*22.5*4.5 |
| 35 | 25.5 | 4.3 | 4.5 | SPG35*25.5*4.5 |
| 35.5 | 26 | 4.3 | 4.5 | SPG35.5*26*4.5 |
| 40 | 30 | 4.3 | 4.5 | SPG40*30*4.5 |
| 45 | 35 | 4.3 | 4.5 | SPG45*35*4.5 |
| 50 | 40 | 4.3 | 4.5 | SPG50*40*4.5 |
| 55 | 45 | 4.3 | 4.5 | SPG55*45*4.5 |
| 56 | 46 | 4.3 | 4.5 | SPG56*46*4.5 |
| 60 | 50 | 4.3 | 4.5 | SPG60*50*4.5 |
| 63 | 48 | 7.3 | 7.5 | SPG63*48*7.5 |
| 65 | 50 | 7.3 | 7.5 | SPG65*50*7.5 |
| 69 | 54 | 7.3 | 7.5 | SPG69*54*7.5 |
| 70 | 55 | 7.3 | 7.5 | SPG70*55*7.5 |
| 71 | 56 | 7.3 | 7.5 | SPG71*56*7.5 |
| 75 | 60 | 7.3 | 7.5 | SPG75*60*7.5 |
| 80 | 65 | 7.3 | 7.5 | SPG80*65*7.5 |
| 85 | 70 | 7.3 | 7.5 | SPG85*70*7.5 |
| 90 | 75 | 7.3 | 7.5 | SPG90*75*7.5 |
| 95 | 80 | 7.3 | 7.5 | SPG95*80*7.5 |
| 100 | 85 | 7.3 | 7.5 | SPG100*85*7.5 |
| 105 | 90 | 7.3 | 7.5 | SPG105*90*7.5 |
| 108 | 92 | 7.3 | 7.5 | SPG108*92*7.5 |
| 110 | 94 | 7.3 | 7.5 | SPG110*94*7.5 |
| 112 | 96 | 7.3 | 7.5 | SPG112*96*7.5 |
| 120 | 104 | 7.3 | 7.5 | SPG120*104*7.5 |
| 125 | 109 | 7.3 | 7.5 | SPG125*109*7.5 |
| 130 | 114 | 7.3 | 7.5 | SPG130*114*7.5 |
| 135 | 119 | 7.3 | 7.5 | SPG135*119*7.5 |
| 140 | 124 | 7.3 | 7.5 | SPG140*124*7.5 |
| 145 | 129 | 7.3 | 7.5 | SPG145*129*7.5 |
| 150 | 134 | 7.3 | 7.5 | SPG150*134*7.5 |
| 155 | 139 | 7.3 | 7.5 | SPG155*139*7.5 |
| 160 | 144 | 7.3 | 7.5 | SPG160*144*7.5 |
| 170 | 148 | 10.8 | 11 | SPG170*148*11 |



| Nominal Size of Packing, and Housing dimensions | | | L +0.2 | Order No. |
|---|-----|------|--------|-----------------|
| D | d | H | | |
| 180 | 158 | 10.8 | 11 | SPG180*158*11 |
| 190 | 168 | 10.8 | 11 | SPG190*168*11 |
| 200 | 178 | 10.8 | 11 | SPG200*178*11 |
| 210 | 188 | 10.8 | 11 | SPG210*188*11 |
| 215 | 193 | 10.8 | 11 | SPG215*193*11 |
| 220 | 198 | 10.8 | 11 | SPG220*198*11 |
| 230 | 208 | 10.8 | 11 | SPG230*208*11 |
| 240 | 218 | 10.8 | 11 | SPG240*218*11 |
| 250 | 228 | 10.8 | 11 | SPG250*228*11 |
| 260 | 236 | 11.7 | 12 | SPG260*236*12 |
| 270 | 246 | 11.7 | 12 | SPG270*246*12 |
| 280 | 256 | 11.7 | 12 | SPG280*256*12 |
| 290 | 266 | 11.7 | 12 | SPG290*266*12 |
| 300 | 276 | 11.7 | 12 | SPG300*276*12 |
| 310 | 286 | 11.7 | 12 | SPG310*286*12 |
| 320 | 296 | 11.7 | 12 | SPG320*296*12 |
| 330 | 308 | 9.75 | 10 | SPG330*308*10 |
| 360 | 336 | 11.7 | 12 | SPG360*336*12 |
| 400 | 376 | 11.7 | 12 | SPG400*376*12 |
| 485 | 455 | 14.8 | 15 | SPG485*455*15 |
| 500 | 470 | 14.8 | 15 | SPG500*470*15 |
| 550 | 515 | 17.2 | 17.5 | SPG550*515*17.5 |
| 600 | 570 | 14.8 | 15 | SPG600*570*15 |
| 650 | 620 | 14.8 | 15 | SPG650*620*15 |
| 720 | 690 | 14.8 | 15 | SPG720*690*15 |
| 800 | 785 | 12.7 | 13 | SPG800*785*13 |
| 900 | 870 | 24.5 | 25 | SPG900*870*25 |
| 930 | 890 | 19 | 20 | SPG930*890*20 |
| 950 | 925 | 17.7 | 18 | SPG950*925*18 |
| 1000 | 960 | 19.7 | 20 | SPG1000*960*20 |



1. Installation Recommendation



2. Application and properties

Suitable for light and medium hydraulic systems, also be used for pneumatic equipment. Low friction, no crawling phenomenon.

3. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|---------|--|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 6 - 1600mm | 0 - 35MPa | -30°C +200°C | 1.5 m/s | hydraulic oil, flame retardant liquid, water and others. |



S P G C

5. Installation Dimensions

| Nominal Size of Packing, and Housing dimensions | | | L +0.2 | Order No. |
|---|------|-----|--------|-------------------|
| D | d | H | | |
| 28 | 22 | 4.4 | 4.7 | SPGC28*22*4.7 |
| 28.4 | 22.4 | 4.4 | 4.7 | SPGC28.4*22.4*4.7 |
| 30 | 24 | 4.4 | 4.7 | SPGC30*24*4.7 |
| 31 | 25 | 4.4 | 4.7 | SPGC31*25*4.7 |
| 31.5 | 25.5 | 4.4 | 4.7 | SPGC31.5*25.5*4.7 |
| 34 | 28 | 4.4 | 4.7 | SPGC34*28*4.7 |
| 35 | 29 | 4.4 | 4.7 | SPGC35*29*4.7 |
| 35.5 | 29.5 | 4.4 | 4.7 | SPGC35.5*29.5*4.7 |
| 36 | 30 | 4.4 | 4.7 | SPGC36*30*4.7 |
| 37 | 31 | 4.4 | 4.7 | SPGC37*31*4.7 |
| 37.5 | 31.5 | 4.4 | 4.7 | SPGC37.5*31.5*4.7 |
| 38 | 32 | 4.4 | 4.7 | SPGC38*32*4.7 |
| 40 | 34 | 4.4 | 4.7 | SPGC40*34*4.7 |
| 41 | 35 | 4.4 | 4.7 | SPGC41*35*4.7 |
| 41.5 | 35.5 | 4.4 | 4.7 | SPGC41.5*35.5*4.7 |
| 42 | 36 | 4.4 | 4.7 | SPGC42*36*4.7 |
| 44 | 38 | 4.4 | 4.7 | SPGC44*38*4.7 |
| 45 | 39 | 4.4 | 4.7 | SPGC45*39*4.7 |
| 46 | 40 | 4.4 | 4.7 | SPGC46*40*4.7 |
| 47 | 41 | 4.4 | 4.7 | SPGC47*41*4.7 |
| 48 | 42 | 4.4 | 4.7 | SPGC48*42*4.7 |
| 50 | 44 | 4.4 | 4.7 | SPGC50*44*4.7 |
| 51 | 45 | 4.4 | 4.7 | SPGC51*45*4.7 |
| 52 | 46 | 4.4 | 4.7 | SPGC52*46*4.7 |
| 54 | 48 | 4.4 | 4.7 | SPGC54*48*4.7 |
| 55 | 49 | 4.4 | 4.7 | SPGC55*49*4.7 |
| 56 | 50 | 4.4 | 4.7 | SPGC56*50*4.7 |
| 58 | 48 | 4.4 | 4.7 | SPGC58*48*4.7 |
| 60 | 50 | 4.4 | 4.7 | SPGC60*50*4.7 |
| 62 | 52 | 4.4 | 4.7 | SPGC62*52*4.7 |
| 63 | 53 | 4.4 | 4.7 | SPGC63*53*4.7 |
| 65 | 55 | 4.4 | 4.7 | SPGC65*55*4.7 |
| 66 | 56 | 4.4 | 4.7 | SPGC66*56*4.7 |
| 68 | 58 | 7.0 | 7.5 | SPGC68*58*7.5 |
| 70 | 60 | 7.0 | 7.5 | SPGC70*60*7.5 |
| 72 | 62 | 7.0 | 7.5 | SPGC72*62*7.5 |



SPGC

| Nominal Size of Packing, and Housing dimensions | | | L +0.2 | Order No. |
|---|-----|------|--------|-----------------|
| D | d | H | | |
| 73 | 63 | 7.0 | 7.5 | SPGC73*63*7.5 |
| 75 | 65 | 7.0 | 7.5 | SPGC75*65*7.5 |
| 77 | 67 | 7.0 | 7.5 | SPGC77*67*7.5 |
| 80 | 70 | 7.0 | 7.5 | SPGC80*70*7.5 |
| 81 | 71 | 7.0 | 7.5 | SPGC81*71*7.5 |
| 85 | 75 | 7.0 | 7.5 | SPGC85*75*7.5 |
| 90 | 80 | 7.0 | 7.5 | SPGC90*80*7.5 |
| 95 | 85 | 7.0 | 7.5 | SPGC95*85*7.5 |
| 100 | 90 | 7.0 | 7.5 | SPGC100*90*7.5 |
| 105 | 95 | 7.0 | 7.5 | SPGC105*95*7.5 |
| 110 | 100 | 7.0 | 7.5 | SPGC110*100*7.5 |
| 112 | 102 | 7.0 | 7.5 | SPGC112*102*7.5 |
| 115 | 105 | 7.0 | 7.5 | SPGC115*105*7.5 |
| 120 | 110 | 7.0 | 7.5 | SPGC120*110*7.5 |
| 122 | 112 | 7.0 | 7.5 | SPGC122*112*7.5 |
| 125 | 115 | 7.0 | 7.5 | SPGC125*115*7.5 |
| 130 | 120 | 7.0 | 7.5 | SPGC130*120*7.5 |
| 135 | 125 | 7.0 | 7.5 | SPGC135*125*7.5 |
| 140 | 130 | 7.0 | 7.5 | SPGC140*130*7.5 |
| 142 | 132 | 7.0 | 7.5 | SPGC142*132*7.5 |
| 145 | 135 | 7.0 | 7.5 | SPGC145*135*7.5 |
| 150 | 140 | 7.0 | 7.5 | SPGC150*140*7.5 |
| 155 | 145 | 7.0 | 7.5 | SPGC155*145*7.5 |
| 160 | 150 | 7.0 | 7.5 | SPGC160*150*7.5 |
| 165 | 150 | 10.5 | 11 | SPGC165*150*11 |
| 170 | 155 | 10.5 | 11 | SPGC170*155*11 |
| 175 | 160 | 10.5 | 11 | SPGC175*160*11 |
| 180 | 165 | 10.5 | 11 | SPGC180*165*11 |
| 185 | 170 | 10.5 | 11 | SPGC185*170*11 |
| 190 | 175 | 10.5 | 11 | SPGC190*175*11 |
| 195 | 180 | 10.5 | 11 | SPGC195*180*11 |
| 200 | 185 | 10.5 | 11 | SPGC200*185*11 |
| 205 | 190 | 10.5 | 11 | SPGC205*190*11 |
| 210 | 195 | 10.5 | 11 | SPGC210*195*11 |
| 215 | 200 | 10.5 | 11 | SPGC215*200*11 |
| 220 | 205 | 10.5 | 11 | SPGC220*205*11 |
| 224 | 209 | 10.5 | 11 | SPGC224*209*11 |
| 225 | 210 | 10.5 | 11 | SPGC225*210*11 |
| 230 | 215 | 10.5 | 11 | SPGC230*215*11 |




SPGC

| Nominal Size of Packing, and Housing dimensions | | | L +0.2 | Order No. |
|---|-----|------|--------|----------------|
| D | d | H | | |
| 235 | 220 | 10.5 | 11 | SPGC235*220*11 |
| 240 | 225 | 10.5 | 11 | SPGC240*225*11 |
| 245 | 230 | 10.5 | 11 | SPGC245*230*11 |
| 250 | 235 | 10.5 | 11 | SPGC250*235*11 |
| 255 | 240 | 10.5 | 11 | SPGC255*240*11 |
| 260 | 245 | 10.5 | 11 | SPGC260*245*11 |
| 265 | 250 | 10.5 | 11 | SPGC265*250*11 |
| 270 | 255 | 10.5 | 11 | SPGC270*255*11 |
| 275 | 260 | 10.5 | 11 | SPGC275*260*11 |



1. Installation Recommendation



2. Application and properties

Standard double acting sealing, a wide range of applications. Friction resistance is very low, no crawling phenomenon, strong wear resistance, and saving installation space.

3. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|---------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 20 - 1600mm | 0—35MPa | -30°C +200°C | 1.5 m/s | hydraulic oil, flame retardant liquid, water and others |



SPGO

5. Installation Dimensions


| Bore Dia. | Groove Width | Order No. | O-Ring Dimension |
|-----------|--------------|-------------|------------------|
| D H9 | L1+0.2 | | |
| 60 | 6 | SPGO60*6 | 43.5*5.3 |
| 65 | 6 | SPGO65*6 | 48*5.3 |
| 70 | 6 | SPGO70*6 | 53*5.3 |
| 75 | 6 | SPGO75*6 | 58*5.3 |
| 80 | 6 | SPGO80*6 | 63*5.3 |
| 85 | 6 | SPGO85*6 | 67*5.3 |
| 90 | 6 | SPGO90*6 | 73*5.3 |
| 95 | 6 | SPGO95*6 | 77.5*5.3 |
| 100 | 6 | SPGO100*6 | 83*5.3 |
| 105 | 6 | SPGO105*6 | 87.5*5.3 |
| 110 | 6 | SPGO110*6 | 92.5*5.3 |
| 115 | 6 | SPGO115*6 | 97.5*5.3 |
| 120 | 6 | SPGO120*6 | 103*5.3 |
| 125 | 6 | SPGO125*6 | 108*5.3 |
| 130 | 6 | SPGO130*6 | 112*5.3 |
| 135 | 6 | SPGO135*6 | 118*5.3 |
| 140 | 6 | SPGO140*6 | 123.19*5.3 |
| 145 | 6 | SPGO145*6 | 128*5.3 |
| 150 | 6 | SPGO150*6 | 132.72*5.3 |
| 155 | 6 | SPGO155*6 | 138*5.3 |
| 160 | 6 | SPGO160*6 | 142.24*5.3 |
| 165 | 6 | SPGO165*6 | 148.5*5.3 |
| 170 | 6 | SPGO170*6 | 151.77*5.3 |
| 175 | 6 | SPGO175*6 | 158*5.3 |
| 180 | 6 | SPGO180*6 | 164.47*5.3 |
| 185 | 6 | SPGO185*6 | 167*5.3 |
| 190 | 6 | SPGO190*6 | 173*5.3 |
| 195 | 6 | SPGO195*6 | 177.17*5.3 |
| 80 | 7.9 | SPGO80*7.9 | 56*7 |
| 85 | 7.9 | SPGO85*7.9 | 61*7 |
| 90 | 7.9 | SPGO90*7.9 | 66*7 |
| 95 | 7.9 | SPGO95*7.9 | 71*7 |
| 100 | 7.9 | SPGO100*7.9 | 77.5*7 |
| 105 | 7.9 | SPGO105*7.9 | 82*7 |
| 110 | 7.9 | SPGO110*7.9 | 86*7 |
| 115 | 7.9 | SPGO115*7.9 | 92*7 |



SPGO

| Bore Dia. | Groove Width | Order No. | O-Ring Dimension |
|-----------|--------------|---|------------------|
| D H9 | L1+0.2 | | |
| 120 | 7.9 | SPGO120*7.9 SPGO125*7.9 SPGO130*7.9 | 97*7 |
| 125 | 7.9 | | 103*7 |
| 130 | 7.9 | | 107*7 |
| 135 | 7.9 | SPGO135*7.9 SPGO140*7.9 SPGO145*7.9 | 112*7 |
| 140 | 7.9 | | 117*7 |
| 145 | 7.9 | | 122*7 |
| 150 | 7.9 | SPGO150*7.9 SPGO155*7.9 SPGO160*7.9 | 126.37*7 |
| 155 | 7.9 | | 132*7 |
| 160 | 7.9 | | 136*7 |
| 165 | 7.9 | SPGO165*7.9 SPGO170*7.9 SPGO175*7.9 | 142.24*7 |
| 170 | 7.9 | | 145.42*7 |
| 175 | 7.9 | | 152*7 |
| 180 | 7.9 | SPGO180*7.9 SPGO185*7.9 SPGO190*7.9 | 157.5*7 |
| 185 | 7.9 | | 160*7 |
| 190 | 7.9 | | 165*7 |
| 195 | 7.9 | SPGO195*7.9 SPGO200*7.9 SPGO210*7.9 | 170*7 |
| 200 | 7.9 | | 177.17*7 |
| 210 | 7.9 | | 185*7 |
| 220 | 7.9 | SPGO220*7.9 SPGO230*7.9 SPGO240*7.9 | 197*7 |
| 230 | 7.9 | | 207.5*7 |
| 240 | 7.9 | | 218*7 |
| 250 | 7.9 | SPGO250*7.9 SPGO260*7.9 SPGO270*7.9 | 227*7 |
| 260 | 7.9 | | 237*7 |
| 270 | 7.9 | | 250*7 |
| 280 | 7.9 | SPGO280*7.9 SPGO290*7.9 SPGO300*7.9 | 258*7 |
| 290 | 7.9 | | 265*7 |
| 300 | 7.9 | | 280*7 |
| 120 | 9.5 | SPGO120*9.5 SPGO125*9.5 SPGO130*9.5 | 107*8.6 |
| 125 | 9.5 | | 112*8.6 |
| 130 | 9.5 | | 117*8.6 |
| 135 | 9.5 | SPGO135*9.5 SPGO140*9.5 SPGO145*9.5 | 122*8.6 |
| 140 | 9.5 | | 127*8.6 |
| 145 | 9.5 | | 132*8.6 |
| 150 | 9.5 | SPGO150*9.5 SPGO160*9.5 | 137*8.6 |
| 160 | 9.5 | | 147*8.6 |

1. Installation Recommendation



2. Application and properties

Standard double acting sealing, a wide range of applications. Friction resistance is very low, no crawling phenomenon, strong wear resistance, and saving installation space.

3. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|---------|--|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 20 - 1600mm | 0 - 35MPa | -30°C +200°C | 1.5 m/s | hydraulic oil, flame retardant liquid, water and others. |



D P O

5. Installation Dimensions

| Nominal Size of Packing, and Housing dimensions | | | L +0.2 | Order No. |
|---|------|-----|--------|----------------|
| D | d | H | | |
| 20 | 14 | 3 | 3.2 | DPO20*14*3.2 |
| 25 | 19 | 3 | 3.2 | DPO25*19*3.2 |
| 30 | 21.5 | 3.8 | 4 | DPO30*21.5*4 |
| 31.5 | 23 | 3.8 | 4 | DPO31.5*23*4 |
| 32 | 23.5 | 3.8 | 4 | DPO32*23.5*4 |
| 35 | 26.5 | 3.8 | 4 | DPO35*26.5*4 |
| 35.5 | 27 | 3.8 | 4 | DPO35.5*27*4 |
| 40 | 31.5 | 3.8 | 4 | DPO40*31.5*4 |
| 45 | 36.5 | 3.8 | 4 | DPO45*36.5*4 |
| 50 | 41.5 | 3.8 | 4 | DPO50*41.5*4 |
| 53 | 44.5 | 3.8 | 4 | DPO53*44.5*4 |
| 55 | 46.5 | 3.8 | 4 | DPO55*46.5*4 |
| 56 | 47.5 | 3.8 | 4 | DPO56*47.5*4 |
| 60 | 51.5 | 3.8 | 4 | DPO60*51.5*4 |
| 63 | 49 | 6.3 | 6.5 | DPO63*49*6.5 |
| 65 | 51 | 6.3 | 6.5 | DPO65*51*6.5 |
| 70 | 56 | 6.3 | 6.5 | DPO70*56*6.5 |
| 71 | 57 | 6.3 | 6.5 | DPO71*57*6.5 |
| 75 | 61 | 6.3 | 6.5 | DPO75*61*6.5 |
| 80 | 66 | 6.3 | 6.5 | DPO80*66*6.5 |
| 85 | 71 | 6.3 | 6.5 | DPO85*71*6.5 |
| 90 | 76 | 6.3 | 6.5 | DPO90*76*6.5 |
| 95 | 81 | 6.3 | 6.5 | DPO95*81*6.5 |
| 100 | 86 | 6.3 | 6.5 | DPO100*86*6.5 |
| 105 | 91 | 6.3 | 6.5 | DPO105*91*6.5 |
| 110 | 96 | 6.3 | 6.5 | DPO110*96*6.5 |
| 112 | 98 | 6.3 | 6.5 | DPO112*98*6.5 |
| 115 | 101 | 6.3 | 6.5 | DPO115*101*6.5 |
| 120 | 106 | 6.3 | 6.5 | DPO120*106*6.5 |
| 125 | 111 | 6.3 | 6.5 | DPO125*111*6.5 |
| 130 | 116 | 6.3 | 6.5 | DPO130*116*6.5 |
| 135 | 121 | 6.3 | 6.5 | DPO135*121*6.5 |
| 140 | 126 | 6.3 | 6.5 | DPO140*126*6.5 |
| 150 | 136 | 6.3 | 6.5 | DPO150*136*6.5 |
| 160 | 146 | 6.3 | 6.5 | DPO160*146*6.5 |
| 170 | 150 | 9.8 | 10.0 | DPO170*150*10 |
| 180 | 160 | 9.8 | 10.0 | DPO180*160*10 |
| 190 | 170 | 9.8 | 10.0 | DPO190*170*10 |
| 200 | 180 | 9.8 | 10.0 | DPO200*180*10 |




D P O

| Nominal Size of Packing, and Housing dimensions | | | L +0.2 | Order No. |
|---|-----|-----|--------|---------------|
| D | d | H | | |
| 210 | 190 | 9.8 | 10.0 | DPO210*190*10 |
| 220 | 200 | 9.8 | 10.0 | DPO220*200*10 |
| 224 | 204 | 9.8 | 10.0 | DPO224*204*10 |
| 230 | 210 | 9.8 | 10.0 | DPO230*210*10 |
| 240 | 220 | 9.8 | 10.0 | DPO240*220*10 |
| 250 | 230 | 9.8 | 10.0 | DPO250*230*10 |
| 260 | 240 | 9.8 | 10.0 | DPO260*240*10 |
| 270 | 250 | 9.8 | 10.0 | DPO270*250*10 |
| 280 | 260 | 9.8 | 10.0 | DPO280*260*10 |
| 290 | 270 | 9.8 | 10.0 | DPO290*270*10 |
| 300 | 280 | 9.8 | 10.0 | DPO300*280*10 |
| 310 | 290 | 9.8 | 10.0 | DPO310*290*10 |
| 320 | 300 | 9.8 | 10.0 | DPO320*300*10 |
| 340 | 320 | 9.8 | 10.0 | DPO340*320*10 |
| 350 | 330 | 9.8 | 10.0 | DPO350*330*10 |
| 360 | 340 | 9.8 | 10.0 | DPO360*340*10 |
| 375 | 355 | 9.8 | 10.0 | DPO375*355*10 |
| 380 | 360 | 9.8 | 10.0 | DPO380*360*10 |
| 400 | 380 | 9.8 | 10.0 | DPO400*380*10 |



D A Q

1. Installation Recommendation



2. Installation Sizes

| Bore Diameter D_N H9 | | Groove Diameter | Groove Width | Radius | Radial Clearance S max. | | | O-Ring Cross Section | X-Ring Seal Cross Section |
|---------------------------|----------------------|--------------------|-----------------|--------|----------------------------|-------|-------|----------------------------|------------------------------------|
| Standard Application | Light Application | d_1 h9 | $L_1+0.2$ | R_1 | 10MPa | 20MPa | 30MPa | d_2 | W |
| 15 - 39.9 | 40 - 79.9 | D_N - 11.0 | 4.2 | 1.0 | 0.25 | 0.15 | 0.10 | 3.53 | 1.78 |
| 40 - 79.9 | 80 - 132.9 | D_N - 15.5 | 6.3 | 1.3 | 0.3 | 0.20 | 0.15 | 5.33 | 1.78 |
| 80 - 132.9 | 133 - 252.9 | D_N - 21.0 | 8.1 | 1.8 | 0.3 | 0.20 | 0.15 | 7.00 | 2.62 |
| 133 - 252.9 | - | D_N - 24.5 | 8.1 | 1.8 | 0.3 | 0.20 | 0.15 | 7.00 | 2.62 |
| 253 - 462.9 | - | D_N - 28.0 | 9.5 | 2.5 | 0.45 | 0.30 | 0.25 | 8.40 | 3.53 |
| 463 - 700 | - | D_N - 35.0 | 11.5 | 3.0 | 0.55 | 0.40 | 0.35 | 10.00 | 5.33 |



D A Q

3. Application and properties

Apply to the working condition of fast speed, high pressure, and the necessary pressure keeping. Recommended for double-acting pistons as piston-type energy storage, supporting cylinder and positional cylinder. Double safety with low friction and high elasticity, good dynamic and static sealing performance, larger extrusion clearances can be allowed, at the same time with the function of holding pressure, less leakage in the hydraulic cylinder. Simple groove, small installation space, excellent sliding performance, no crawling phenomenon.

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

X-Ring: NBR / FKM

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 16 - 1600mm | 0–40MPa | -30°C +200°C | 2 m/s | hydraulic oil, flame retardant liquid, water and others |

6. Installation Dimensions

| Bore Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimension |
|-----------|-------------------|---------------------|----------------|------------------|
| d h9 | D ₁ H9 | L ₁ +0.2 | | |
| 16 | 5 | 4.2 | DAQ16*5*4.2 | 4.34*3.53 |
| 18 | 7 | 4.2 | DAQ18*7*4.2 | 6.42*3.53 |
| 20 | 9 | 4.2 | DAQ20*9*4.2 | 8.42*3.53 |
| 22 | 11 | 4.2 | DAQ22*11*4.2 | 10.69*3.53 |
| 25 | 14 | 4.2 | DAQ25*14*4.2 | 13.87*3.53 |
| 28 | 17 | 4.2 | DAQ28*17*4.2 | 15.47*3.53 |
| 30 | 19 | 4.2 | DAQ30*19*4.2 | 18.66*3.53 |
| 32 | 21 | 4.2 | DAQ32*21*4.2 | 20.22*3.53 |
| 35 | 24 | 4.2 | DAQ35*24*4.2 | 23.40*3.53 |
| 40 | 29 | 4.2 | DAQ40*29*4.2 | 28.17*3.53 |
| 42 | 31 | 4.2 | DAQ42*31*4.2 | 29.75*3.53 |
| 45 | 34 | 4.2 | DAQ45*34*4.2 | 32.92*3.53 |
| 48 | 37 | 4.2 | DAQ48*37*4.2 | 36.09*3.53 |
| 50 | 39 | 4.2 | DAQ50*39*4.2 | 37.70*3.53 |
| 50 | 34.5 | 6.3 | DAQ50*34.5*6.3 | 32.69*3.53 |
| 52 | 41 | 4.2 | DAQ52*41*4.2 | 40.87*3.53 |
| 55 | 44 | 4.2 | DAQ55*44*4.2 | 44.04*3.53 |
| 60 | 49 | 4.2 | DAQ60*49*4.2 | 47.22*3.53 |
| 63 | 52 | 4.2 | DAQ63*52*4.2 | 50.39*3.53 |
| 63 | 47.5 | 6.3 | DAQ63*47.5*6.3 | 46.99*3.53 |
| 65 | 54 | 4.2 | DAQ65*54*4.2 | 53.57*3.53 |



D A Q

| Bore Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimension |
|-----------|-------------------|---------------------|--|------------------|
| d h9 | D ₁ H9 | L ₁ +0.2 | | |
| 70 | 59 | 4.2 | DAQ70*59*4.2 DAQ70*54.5*6.3 DAQ75*64*4.2 | 56.74*3.53 |
| 70 | 54.5 | 6.3 | | 53.34*3.53 |
| 75 | 64 | 4.2 | | 63.09*3.53 |
| 80 | 64.5 | 6.3 | DAQ80*64.5*6.3 DAQ80*59*8.1 DAQ85*69.5*6.3 | 62.87*5.33 |
| 80 | 59 | 8.1 | | 58*7.0 |
| 85 | 69.5 | 6.3 | | 69.22*5.33 |
| 85 | 64 | 8.1 | DAQ85*64*8.1 | 63*7.0 |
| 90 | 74.5 | 6.3 | DAQ90*74.5*6.3 | 72.39*5.33 |
| 90 | 69 | 8.1 | DAQ90*69*8.1 | 68*7.0 |
| 95 | 79.5 | 6.3 | DAQ95*79.5*6.3 | 78.74*5.33 |
| 95 | 74 | 8.1 | DAQ95*74*8.1 | 73*7.0 |
| 100 | 84.5 | 6.3 | DAQ100*84.5*6.3 | 81.92*5.33 |
| 100 | 79 | 8.1 | DAQ100*79*8.1 | 78*7.0 |
| 105 | 89.5 | 6.3 | DAQ105*89.5*6.3 | 88.27*5.33 |
| 105 | 84 | 8.1 | DAQ105*84*8.1 | 83*7.0 |
| 110 | 94.5 | 6.3 | DAQ110*94.5*6.3 | 91.44*5.33 |
| 110 | 89 | 8.1 | DAQ110*89*8.1 | 88*7.0 |
| 115 | 99.5 | 6.3 | DAQ115*99.5*6.3 | 97.79*5.33 |
| 115 | 94 | 8.1 | DAQ115*94*8.1 | 93*7.0 |
| 120 | 104.5 | 6.3 | DAQ120*104.5*6.3 | 100.97*5.33 |
| 120 | 99 | 8.1 | DAQ120*99*8.1 | 98*7.0 |
| 125 | 109.5 | 6.3 | DAQ125*109.5*6.3 | 107.32*5.33 |
| 125 | 104 | 8.1 | DAQ125*104*8.1 | 103*7.0 |
| 130 | 114.5 | 6.3 | DAQ130*114.5*6.3 | 113.67*5.33 |
| 130 | 109 | 8.1 | DAQ130*109*8.1 | 108*7.0 |
| 135 | 114 | 8.1 | DAQ135*114*8.1 | 113.67*5.33 |
| 140 | 119 | 8.1 | DAQ140*119*8.1 | 116.84*7.0 |
| 150 | 129 | 8.1 | DAQ150*129*8.1 | 126.37*7.0 |
| 160 | 139 | 8.1 | DAQ160*139*8.1 | 135.89*7.0 |
| 170 | 149 | 8.1 | DAQ170*149*8.1 | 145.42*7.0 |
| 180 | 159 | 8.1 | DAQ180*159*8.1 | 158.12*7.0 |
| 190 | 169 | 8.1 | DAQ190*169*8.1 | 164.47*7.0 |
| 200 | 179 | 8.1 | DAQ200*179*8.1 | 177.17*7.0 |
| 210 | 189 | 8.1 | DAQ210*189*8.1 | 183.52*7.0 |
| 220 | 199 | 8.1 | DAQ220*199*8.1 | 196.22*7.0 |
| 230 | 209 | 8.1 | DAQ230*209*8.1 | 208.92*7.0 |
| 240 | 219 | 8.1 | DAQ240*219*8.1 | 215.27*7.0 |
| 250 | 229 | 8.1 | DAQ250*229*8.1 | 227.97*7.0 |
| 250 | 225.5 | 8.1 | DAQ250*225.5*8.1 | 227.97*7.0 |




D A Q

| Bore Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimension |
|-----------|-------------------|---------------------|-----------------|------------------|
| d h9 | D ₁ H9 | L ₁ +0.2 | | |
| 280 | 252 | 9.5 | DAQ280*252*9.5 | 250*8.4 |
| 300 | 272 | 9.5 | DAQ300*272*9.5 | 270*8.4 |
| 310 | 282 | 9.5 | DAQ310*282*9.5 | 280*8.4 |
| 320 | 292 | 9.5 | DAQ320*292*9.5 | 290*8.4 |
| 350 | 322 | 9.5 | DAQ350*322*9.5 | 320*8.4 |
| 400 | 372 | 9.5 | DAQ400*372*9.5 | 370*8.4 |
| 420 | 392 | 9.5 | DAQ420*392*9.5 | 390*8.4 |
| 450 | 422 | 9.5 | DAQ450*422*9.5 | 420*8.4 |
| 480 | 445 | 11.5 | DAQ480*445*11.5 | 444*10.0 |
| 500 | 465 | 11.5 | DAQ500*465*11.5 | 464*10.0 |
| 600 | 565 | 11.5 | DAQ600*565*11.5 | 465*10.0 |
| 700 | 665 | 11.5 | DAQ700*665*11.5 | 664*10.0 |



D A Q 2

1. Installation Recommendation



2. Installation Sizes

| Bore Diameter D_N H9 | | Groove Diameter | Groove Width | Radius | Radial Clearance S max. | | | O-Ring Cross Section | X-Ring Seal Cross Section |
|---------------------------|------------------------|-----------------|--------------|--------|----------------------------|-------|-------|----------------------|---------------------------|
| Standard Application | Heavy Duty Application | d_1 h9 | $L_1+0.2$ | R_1 | 10MPa | 20MPa | 30MPa | d_2 | W |
| 40 - 79.9 | 25 - 140 | D_N - 10.0 | 6.3 | 0.6 | 0.3 | 0.2 | 0.15 | 2.62 | 1.78 |
| 80 - 132.9 | 50 - 250 | D_N - 13.0 | 8.3 | 1.0 | 0.4 | 0.3 | 0.15 | 3.53 | 2.62 |
| 133 - 252.9 | 100 - 480 | D_N - 18.0 | 12.3 | 1.3 | 0.4 | 0.3 | 0.20 | 5.33 | 3.53 |
| 463 - 700 | 425 - 700 | D_N - 31.0 | 16.3 | 1.8 | 0.5 | 0.4 | 0.30 | 7.00 | 5.33 |

3. Application and properties

Apply to the working condition of fast speed, high pressure, and the necessary pressure keeping. Available for piston accumulator, clamping cylinder and positioning cylinder, especially recommended for heavy duty and large diameter applications. Double safety with low friction and high elasticity, Low gas permeability, excellent sliding performance in high pressure applications, no crawling phenomenon, simple groove structure, easy installation.



D A Q 2

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

X-Ring: NBR / FKM

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 40 - 1600mm | 0—60MPa | -30°C +200°C | 3 m/s | hydraulic oil, flame retardant liquid, water and others |

6. Installation Dimensions

| Bore Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimension |
|-----------|-------------------|---------------------|-------------------|------------------|
| d h9 | D ₁ H9 | L ₁ +0.2 | | |
| 40 | 30 | 6.3 | DAQ2-40*30*6.3 | 29.82*2.62 |
| 42 | 32 | 6.3 | DAQ2-42*32*6.3 | 31.42*2.62 |
| 45 | 35 | 6.3 | DAQ2-45*35*6.3 | 34.59*2.62 |
| 48 | 38 | 6.3 | DAQ2-48*38*6.3 | 37.77*2.62 |
| 50 | 40 | 6.3 | DAQ2-50*40*6.3 | 39.34*2.62 |
| 52 | 42 | 6.3 | DAQ2-52*42*6.3 | 40.94*2.62 |
| 55 | 45 | 6.3 | DAQ2-55*45*6.3 | 44.12*2.62 |
| 60 | 50 | 6.3 | DAQ2-60*50*6.3 | 48.90*2.62 |
| 63 | 53 | 6.3 | DAQ2-63*53*6.3 | 52.07*2.62 |
| 65 | 55 | 6.3 | DAQ2-65*55*6.3 | 53.64*2.62 |
| 70 | 60 | 6.3 | DAQ2-70*60*6.3 | 58.42*2.62 |
| 75 | 65 | 6.3 | DAQ2-75*65*6.3 | 63.17*2.62 |
| 80 | 67 | 8.3 | DAQ2-80*67*8.3 | 66.27*3.53 |
| 85 | 72 | 8.3 | DAQ2-85*72*8.3 | 69.44*3.53 |
| 90 | 77 | 8.3 | DAQ2-90*77*8.3 | 75.79*3.53 |
| 95 | 82 | 8.3 | DAQ2-95*82*8.3 | 78.97*3.53 |
| 100 | 87 | 8.3 | DAQ2-100*87*8.3 | 85.32*3.53 |
| 105 | 92 | 8.3 | DAQ2-105*92*8.3 | 91.67*3.53 |
| 110 | 97 | 8.3 | DAQ2-110*97*8.3 | 94.84*3.53 |
| 115 | 102 | 8.3 | DAQ2-115*102*8.3 | 101.19*3.53 |
| 120 | 107 | 8.3 | DAQ2-120*107*8.3 | 104.37*3.53 |
| 125 | 112 | 8.3 | DAQ2-125*112*8.3 | 110.72*3.53 |
| 130 | 117 | 8.3 | DAQ2-130*117*8.3 | 113.89*3.53 |
| 135 | 117 | 12.3 | DAQ2-135*117*12.3 | 113.67*5.33 |
| 140 | 122 | 12.3 | DAQ2-140*122*12.3 | 120.02*5.33 |
| 150 | 132 | 12.3 | DAQ2-150*132*12.3 | 129.54*5.33 |
| 160 | 142 | 12.3 | DAQ2-160*142*12.3 | 139.07*5.33 |




D A Q 2

| Bore Dia. | Groove Dia. | Groove Width | Order No. | O-Ring Dimension |
|-----------|-------------------|---------------------|-------------------|------------------|
| d h9 | D ₁ H9 | L ₁ +0.2 | | |
| 170 | 152 | 12.3 | DAQ2-170*152*12.3 | 148.49*5.33 |
| 180 | 162 | 12.3 | DAQ2-180*162*12.3 | 158.12*5.33 |
| 190 | 172 | 12.3 | DAQ2-190*172*12.3 | 170.82*5.33 |
| 200 | 182 | 12.3 | DAQ2-200*182*12.3 | 177.17*5.33 |
| 210 | 192 | 12.3 | DAQ2-210*192*12.3 | 189.87*5.33 |
| 220 | 202 | 12.3 | DAQ2-220*202*12.3 | 196.22*5.33 |
| 230 | 212 | 12.3 | DAQ2-230*212*12.3 | 208.92*5.33 |
| 240 | 222 | 12.3 | DAQ2-240*222*12.3 | 221.62*5.33 |
| 250 | 232 | 12.3 | DAQ2-250*232*12.3 | 227.97*5.33 |
| 280 | 262 | 12.3 | DAQ2-280*262*12.3 | 253.37*5.33 |
| 300 | 282 | 12.3 | DAQ2-300*282*12.3 | 278.77*5.33 |
| 320 | 302 | 12.3 | DAQ2-320*302*12.3 | 291.47*5.33 |
| 350 | 332 | 12.3 | DAQ2-350*332*12.3 | 329.57*5.33 |
| 400 | 382 | 12.3 | DAQ2-400*382*12.3 | 380.37*5.33 |
| 420 | 402 | 12.3 | DAQ2-420*402*12.3 | 405.26*5.33 |
| 450 | 432 | 12.3 | DAQ2-450*432*12.3 | 430.66*5.33 |
| 480 | 449 | 16.3 | DAQ2-480*449*16.3 | 443.36*7.0 |
| 500 | 469 | 16.3 | DAQ2-500*469*16.3 | 468.76*7.0 |
| 600 | 569 | 16.3 | DAQ2-600*569*16.3 | 557.66*7.0 |
| 700 | 669 | 16.3 | DAQ2-700*669*16.3 | 658.88*7.0 |



1. Installation Recommendation



2. Installation Sizes

| Bore Diameter | Groove Diameter | Groove Width | Radius | Radial Clearance S max. | | | |
|---------------|-----------------|---------------------|----------------|-------------------------|-------|-------|-------|
| D H8 | d h8 | L ₁ +0.2 | R ₁ | 16MPa | 26MPa | 32MPa | 40MPa |
| 55.0-149.9 | D-10.0 | 10.0 | 0.4 | 0.60 | 0.50 | 0.40 | 0.40 |
| 150.0-244.9 | D-12.5 | 12.5 | 0.4 | 0.75 | 0.65 | 0.55 | 0.50 |
| 245.0-500.0 | D-15.0 | 15.0 | 0.8 | 0.75 | 0.65 | 0.55 | 0.50 |
| 500.1-760.0 | D-17.5 | 17.5 | 1.2 | 0.75 | 0.65 | 0.55 | 0.50 |
| 760.1-999.9 | D-20.0 | 20.0 | 1.2 | 0.80 | 0.70 | 0.60 | 0.55 |
| ≥ 1000 | D-20.0 | 20.5 | 1.2 | 0.80 | 0.70 | 0.60 | 0.55 |

3. Application and properties

Applied to the hydraulic cylinder of heavy machinery and metallurgical equipment. Pressure resistance and corrosion resistance are strong, good thermal conductivity, structure anti-distortion, low friction, no crawling phenomenon.



G S F - W

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 40 - 1600mm | 0 - 60MPa | -30°C +100°C | 5 m/s | hydraulic oil, flame retardant liquid, water and others |

6. Installation Dimensions

| Bore Dia. | Groove Dia. | Groove Width | Order No. |
|-----------|-------------|--------------|-------------------|
| D H8 | d h8 | L+0.2 | |
| 55 | 40 | 10 | GSF-W55*40*10 |
| 60 | 45 | 10 | GSF-W60*45*10 |
| 70 | 55 | 10 | GSF-W70*55*10 |
| 80 | 60 | 10 | GSF-W80*60*10 |
| 90 | 70 | 10 | GSF-W90*70*10 |
| 100 | 80 | 10 | GSF-W100*80*10 |
| 110 | 90 | 10 | GSF-W110*90*10 |
| 115 | 95 | 10 | GSF-W115*95*10 |
| 120 | 100 | 10 | GSF-W120*100*10 |
| 130 | 110 | 10 | GSF-W130*110*10 |
| 140 | 120 | 10 | GSF-W140*120*10 |
| 150 | 125 | 12.5 | GSF-W150*125*12.5 |
| 160 | 135 | 12.5 | GSF-W160*135*12.5 |
| 165 | 140 | 12.5 | GSF-W165*140*12.5 |
| 170 | 145 | 12.5 | GSF-W170*145*12.5 |
| 180 | 155 | 12.5 | GSF-W180*155*12.5 |
| 185 | 160 | 12.5 | GSF-W185*160*12.5 |
| 190 | 165 | 12.5 | GSF-W190*165*12.5 |
| 200 | 175 | 12.5 | GSF-W200*175*12.5 |
| 205 | 180 | 12.5 | GSF-W205*180*12.5 |
| 210 | 185 | 12.5 | GSF-W210*185*12.5 |
| 215 | 190 | 12.5 | GSF-W215*190*12.5 |
| 220 | 195 | 12.5 | GSF-W220*195*12.5 |
| 225 | 200 | 12.5 | GSF-W225*200*12.5 |
| 230 | 205 | 12.5 | GSF-W230*205*12.5 |
| 240 | 215 | 12.5 | GSF-W240*215*12.5 |
| 245 | 215 | 15 | GSF-W245*215*15 |





G S F - W

| Bore Dia. | Groove Dia. | Groove Width | Order No. |
|-----------|-------------|--------------|-------------------|
| D H8 | d h8 | L+0.2 | |
| 250 | 220 | 15 | GSF-W250*220*15 |
| 260 | 230 | 15 | GSF-W260*230*15 |
| 270 | 240 | 15 | GSF-W270*240*15 |
| 275 | 245 | 15 | GSF-W275*245*15 |
| 280 | 250 | 15 | GSF-W280*250*15 |
| 285 | 255 | 15 | GSF-W285*255*15 |
| 290 | 260 | 15 | GSF-W290*260*15 |
| 300 | 270 | 15 | GSF-W300*270*15 |
| 305 | 275 | 15 | GSF-W305*275*15 |
| 310 | 280 | 15 | GSF-W310*280*15 |
| 320 | 290 | 15 | GSF-W320*290*15 |
| 325 | 295 | 15 | GSF-W325*295*15 |
| 330 | 300 | 15 | GSF-W330*300*15 |
| 335 | 305 | 15 | GSF-W335*305*15 |
| 340 | 310 | 15 | GSF-W340*310*15 |
| 350 | 320 | 15 | GSF-W350*320*15 |
| 355 | 325 | 15 | GSF-W355*325*15 |
| 360 | 330 | 15 | GSF-W360*330*15 |
| 370 | 340 | 15 | GSF-W370*340*15 |
| 380 | 350 | 15 | GSF-W380*350*15 |
| 390 | 360 | 15 | GSF-W390*360*15 |
| 400 | 370 | 15 | GSF-W400*370*15 |
| 455 | 420 | 17.5 | GSF-W455*420*17.5 |
| 460 | 425 | 17.5 | GSF-W460*425*17.5 |
| 470 | 435 | 17.5 | GSF-W470*435*17.5 |
| 475 | 440 | 17.5 | GSF-W475*440*17.5 |
| 510 | 475 | 17.5 | GSF-W510*475*17.5 |
| 530 | 495 | 17.5 | GSF-W530*495*17.5 |
| 540 | 505 | 17.5 | GSF-W540*505*17.5 |
| 550 | 515 | 17.5 | GSF-W550*515*17.5 |
| 560 | 525 | 17.5 | GSF-W560*525*17.5 |
| 570 | 535 | 17.5 | GSF-W570*535*17.5 |
| 580 | 545 | 17.5 | GSF-W580*545*17.5 |
| 590 | 555 | 17.5 | GSF-W590*555*17.5 |
| 600 | 565 | 17.5 | GSF-W600*565*17.5 |
| 610 | 575 | 17.5 | GSF-W610*575*17.5 |
| 620 | 585 | 17.5 | GSF-W620*585*17.5 |
| 630 | 595 | 17.5 | GSF-W630*595*17.5 |
| 640 | 605 | 17.5 | GSF-W640*605*17.5 |




G S F - W

| Bore Dia. | Groove Dia. | Groove Width | Order No. |
|-----------|-------------|--------------|-------------------|
| D H8 | d h8 | L+0.2 | |
| 650 | 615 | 17.5 | GSF-W650*615*17.5 |
| 655 | 620 | 17.5 | GSF-W655*620*17.5 |
| 660 | 625 | 17.5 | GSF-W660*625*17.5 |
| 670 | 635 | 17.5 | GSF-W670*635*17.5 |
| 680 | 645 | 17.5 | GSF-W680*645*17.5 |
| 690 | 655 | 17.5 | GSF-W690*655*17.5 |
| 700 | 665 | 17.5 | GSF-W700*665*17.5 |
| 720 | 685 | 17.5 | GSF-W720*685*17.5 |
| 750 | 715 | 17.5 | GSF-W750*715*17.5 |
| 780 | 740 | 20 | GSF-W780*740*20 |
| 800 | 760 | 20 | GSF-W800*760*20 |
| 820 | 780 | 20 | GSF-W820*780*20 |
| 850 | 810 | 20 | GSF-W850*810*20 |
| 880 | 840 | 20 | GSF-W880*840*20 |
| 900 | 860 | 20 | GSF-W900*860*20 |
| 950 | 910 | 20 | GSF-W950*910*20 |
| 980 | 940 | 20 | GSF-W980*940*20 |
| 1000 | 960 | 20 | GSF-W1000*960*20 |



1. Installation Recommendation



2. Application and properties

Apply to cylinder piston, consisting of a seal ring, an O-Ring, a pair of retaining rings and a pair of guide sleeves. The seal ring and cylinder bore conforming to be a symmetric section to achieve the sealing performance, with double acting sealing performance.

3. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

Back-up ring: filled PTFE / PA

Guide ring: filled PTFE / PA

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|-----------------------------------|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 40 - 1600mm | 0 - 45MPa | -30°C +200°C | 1 m/s | hydraulic oil, water and emulsion |



D D K K

5. Installation Dimensions

| D | d | b | d ₂ | d ₃ | a | c | f | e | Order No. |
|-----|-----|----|----------------|----------------|-----|------|-------|----|----------------|
| 40 | 26 | 32 | 32 | 36 | 3.5 | 15.5 | 8.25 | 7 | DDKK40*26*32 |
| 45 | 31 | 32 | 37 | 41 | 3 | 15.5 | 8.25 | 7 | DDKK45*31*32 |
| 50 | 34 | 39 | 42 | 46 | 3 | 20.5 | 9.25 | 7 | DDKK50*34*39 |
| 56 | 40 | 39 | 48 | 52 | 3 | 20.5 | 9.25 | 7 | DDKK56*40*39 |
| 60 | 44 | 39 | 52 | 56 | 3 | 20.5 | 9.25 | 7 | DDKK60*44*39 |
| 63 | 47 | 39 | 55 | 59 | 3 | 20.5 | 9.25 | 7 | DDKK63*47*39 |
| 65 | 49 | 39 | 57 | 61 | 3 | 20.5 | 9.25 | 7 | DDKK65*49*39 |
| 70 | 54 | 39 | 62 | 66 | 3 | 20.5 | 9.25 | 7 | DDKK70*54*39 |
| 75 | 59 | 39 | 67 | 71 | 3 | 20.5 | 9.25 | 7 | DDKK75*59*39 |
| 80 | 62 | 43 | 72 | 76 | 3 | 22.5 | 10.25 | 7 | DDKK80*62*43 |
| 85 | 67 | 43 | 77 | 81 | 3 | 22.5 | 10.25 | 7 | DDKK85*67*43 |
| 90 | 72 | 43 | 82 | 86 | 3 | 22.5 | 10.25 | 7 | DDKK90*72*43 |
| 95 | 77 | 43 | 87 | 91 | 3 | 22.5 | 10.25 | 7 | DDKK95*77*43 |
| 100 | 82 | 43 | 92 | 96 | 3 | 22.5 | 10.25 | 7 | DDKK100*82*43 |
| 105 | 87 | 43 | 97 | 101 | 3 | 22.5 | 10.25 | 10 | DDKK105*87*43 |
| 110 | 92 | 43 | 102 | 106 | 3 | 22.5 | 10.25 | 10 | DDKK110*92*43 |
| 115 | 97 | 43 | 107 | 111 | 3 | 22.5 | 10.25 | 10 | DDKK115*97*43 |
| 120 | 102 | 43 | 112 | 116 | 3 | 22.5 | 10.25 | 10 | DDKK120*102*43 |
| 125 | 103 | 53 | 115 | 121 | 4 | 26.5 | 13.25 | 10 | DDKK125*103*53 |
| 130 | 108 | 53 | 120 | 126 | 4 | 26.5 | 13.25 | 10 | DDKK130*108*53 |
| 140 | 118 | 53 | 130 | 136 | 4 | 26.5 | 13.25 | 10 | DDKK140*118*53 |
| 150 | 128 | 53 | 140 | 146 | 4 | 26.5 | 13.25 | 10 | DDKK150*128*53 |
| 160 | 138 | 53 | 150 | 156 | 4 | 26.5 | 13.25 | 10 | DDKK160*138*53 |
| 165 | 143 | 57 | 155 | 161 | 6 | 26.5 | 15.25 | 10 | DDKK165*143*57 |
| 170 | 148 | 57 | 160 | 166 | 6 | 26.5 | 15.25 | 10 | DDKK170*148*57 |
| 180 | 158 | 57 | 170 | 176 | 6 | 26.5 | 15.25 | 10 | DDKK180*158*57 |
| 190 | 165 | 64 | 180 | 186 | 4.5 | 31.5 | 16.25 | 10 | DDKK190*165*64 |
| 195 | 170 | 64 | 185 | 191 | 4.5 | 31.5 | 16.25 | 10 | DDKK195*170*64 |
| 200 | 175 | 64 | 190 | 196 | 4.5 | 31.5 | 16.25 | 10 | DDKK200*175*64 |
| 210 | 185 | 71 | 200 | 206 | 8 | 31.5 | 19.75 | 12 | DDKK210*185*71 |
| 220 | 195 | 71 | 210 | 216 | 8 | 31.5 | 19.75 | 12 | DDKK220*195*71 |
| 225 | 200 | 71 | 215 | 221 | 8 | 31.5 | 19.75 | 12 | DDKK225*200*71 |
| 230 | 205 | 85 | 220 | 226 | 15 | 31.5 | 26.75 | 12 | DDKK230*205*85 |
| 240 | 215 | 85 | 230 | 236 | 15 | 31.5 | 26.75 | 12 | DDKK240*215*85 |
| 250 | 225 | 85 | 240 | 246 | 15 | 31.5 | 26.75 | 12 | DDKK250*225*85 |
| 255 | 230 | 85 | 245 | 251 | 15 | 31.5 | 26.75 | 12 | DDKK255*230*85 |
| 270 | 245 | 85 | 260 | 266 | 15 | 31.5 | 26.75 | 12 | DDKK270*245*85 |
| 275 | 250 | 85 | 265 | 271 | 15 | 31.5 | 26.75 | 12 | DDKK275*250*85 |
| 280 | 255 | 85 | 270 | 276 | 15 | 31.5 | 26.75 | 12 | DDKK280*255*85 |




D D K K

| D | d | b | d ₂ | d ₃ | a | c | f | e | Order No. |
|-----|-----|----|----------------|----------------|-----|------|-------|----|----------------|
| 290 | 265 | 85 | 280 | 286 | 15 | 31.5 | 26.75 | 12 | DDKK290*265*85 |
| 300 | 275 | 85 | 290 | 296 | 15 | 31.5 | 26.75 | 12 | DDKK300*275*85 |
| 310 | 280 | 80 | 298 | 304 | 8.5 | 36.5 | 21.75 | 15 | DDKK310*280*80 |
| 320 | 290 | 80 | 308 | 314 | 8.5 | 36.5 | 21.75 | 15 | DDKK320*290*80 |
| 330 | 300 | 80 | 318 | 324 | 8.5 | 36.5 | 21.75 | 15 | DDKK330*300*80 |
| 340 | 310 | 80 | 328 | 334 | 8.5 | 36.5 | 21.75 | 15 | DDKK340*310*80 |
| 350 | 320 | 80 | 338 | 344 | 8.5 | 36.5 | 21.75 | 15 | DDKK350*320*80 |
| 360 | 330 | 80 | 348 | 354 | 8.5 | 36.5 | 21.75 | 15 | DDKK360*330*80 |
| 380 | 350 | 80 | 368 | 374 | 8.5 | 36.5 | 21.75 | 15 | DDKK380*350*80 |
| 400 | 370 | 80 | 388 | 394 | 8.5 | 36.5 | 21.75 | 15 | DDKK400*370*80 |
| 420 | 390 | 80 | 408 | 414 | 8.5 | 36.5 | 21.75 | 15 | DDKK420*390*80 |
| 450 | 420 | 80 | 438 | 444 | 8.5 | 36.5 | 21.75 | 15 | DDKK450*420*80 |



1. Installation Recommendation



2. Application and properties

Apply to cylinder piston. Consisting of a seal ring, an O-Ring, a pair of retaining rings and a pair of guide sleeves. The seal ring and cylinder bore conforming to be a symmetric section to achieve the sealing performance, with double acting sealing performance.

3. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

Guide ring: filled PTFE / PA

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|-----------------------------------|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 40 - 1600mm | 0 - 45MPa | -30°C +200°C | 1 m/s | hydraulic oil, water and emulsion |



D K D F

5. Installation Dimensions


| D | d | b | d ₂ | d ₃ | a | c | f | e | Order No. |
|-----|-----|----|----------------|----------------|-----|------|------|----|----------------|
| 40 | 26 | 30 | 32 | 36 | 3.5 | 15.5 | 7.25 | 7 | DKDF40*26*30 |
| 45 | 31 | 30 | 37 | 41 | 3 | 15.5 | 7.25 | 7 | DKDF45*31*30 |
| 50 | 34 | 32 | 42 | 46 | 3 | 20.5 | 5.8 | 7 | DKDF50*34*32 |
| 56 | 40 | 32 | 48 | 52 | 3 | 20.5 | 5.8 | 7 | DKDF56*40*32 |
| 60 | 44 | 32 | 52 | 56 | 3 | 20.5 | 5.8 | 7 | DKDF60*44*32 |
| 63 | 47 | 32 | 55 | 59 | 3 | 20.5 | 5.8 | 7 | DKDF63*47*32 |
| 65 | 49 | 32 | 57 | 61 | 3 | 20.5 | 5.8 | 7 | DKDF65*49*32 |
| 70 | 54 | 32 | 62 | 66 | 3 | 20.5 | 5.8 | 7 | DKDF70*54*32 |
| 75 | 59 | 32 | 67 | 71 | 3 | 20.5 | 5.8 | 7 | DKDF75*59*32 |
| 80 | 62 | 36 | 72 | 76 | 3 | 22.5 | 6.8 | 7 | DKDF80*62*36 |
| 85 | 67 | 36 | 77 | 81 | 3 | 22.5 | 6.8 | 7 | DKDF85*67*36 |
| 90 | 72 | 36 | 82 | 86 | 3 | 22.5 | 6.8 | 7 | DKDF90*72*36 |
| 95 | 77 | 36 | 87 | 91 | 3 | 22.5 | 6.8 | 7 | DKDF95*77*36 |
| 100 | 82 | 36 | 92 | 96 | 3 | 22.5 | 6.8 | 7 | DKDF100*82*36 |
| 105 | 87 | 36 | 97 | 101 | 3 | 22.5 | 6.8 | 10 | DKDF105*87*36 |
| 110 | 92 | 36 | 102 | 106 | 3 | 22.5 | 6.8 | 10 | DKDF110*92*36 |
| 115 | 97 | 36 | 107 | 111 | 3 | 22.5 | 6.8 | 10 | DKDF115*97*36 |
| 120 | 102 | 36 | 112 | 116 | 3 | 22.5 | 6.8 | 10 | DKDF120*102*36 |
| 125 | 103 | 43 | 115 | 121 | 4 | 26.5 | 8.3 | 10 | DKDF125*103*43 |
| 130 | 108 | 43 | 120 | 126 | 4 | 26.5 | 8.3 | 10 | DKDF130*108*43 |
| 135 | 113 | 43 | 125 | 131 | 4 | 26.5 | 8.3 | 10 | DKDF135*113*43 |
| 140 | 118 | 43 | 130 | 136 | 4 | 26.5 | 8.3 | 10 | DKDF140*118*43 |
| 145 | 123 | 43 | 135 | 141 | 4 | 26.5 | 8.3 | 10 | DKDF145*123*43 |
| 150 | 128 | 43 | 140 | 146 | 4 | 26.5 | 8.3 | 10 | DKDF150*128*43 |
| 155 | 133 | 43 | 145 | 151 | 4 | 26.5 | 8.3 | 10 | DKDF155*133*43 |
| 160 | 138 | 43 | 150 | 156 | 4 | 26.5 | 8.3 | 10 | DKDF160*138*43 |
| 170 | 148 | 48 | 160 | 166 | 6 | 26.5 | 10.8 | 10 | DKDF170*148*48 |
| 180 | 158 | 48 | 170 | 176 | 6 | 26.5 | 10.8 | 10 | DKDF180*158*48 |
| 190 | 165 | 48 | 180 | 186 | 4.5 | 31.5 | 8.3 | 10 | DKDF190*165*48 |
| 195 | 170 | 48 | 185 | 191 | 4.5 | 31.5 | 8.3 | 10 | DKDF195*170*48 |
| 200 | 175 | 48 | 190 | 196 | 4.5 | 31.5 | 8.3 | 10 | DKDF200*175*48 |
| 210 | 185 | 58 | 200 | 206 | 8 | 31.5 | 13.3 | 12 | DKDF210*185*58 |
| 220 | 195 | 58 | 210 | 216 | 8 | 31.5 | 13.3 | 12 | DKDF220*195*58 |
| 235 | 210 | 74 | 225 | 231 | 15 | 31.5 | 21.3 | 12 | DKDF235*210*74 |
| 240 | 215 | 74 | 230 | 236 | 15 | 31.5 | 21.3 | 12 | DKDF240*215*74 |
| 250 | 225 | 74 | 240 | 246 | 15 | 31.5 | 21.3 | 12 | DKDF250*225*74 |
| 265 | 240 | 74 | 255 | 261 | 15 | 31.5 | 21.3 | 12 | DKDF265*240*74 |
| 270 | 245 | 74 | 260 | 266 | 15 | 31.5 | 21.3 | 12 | DKDF270*245*74 |
| 275 | 250 | 74 | 265 | 271 | 15 | 31.5 | 21.3 | 12 | DKDF275*250*74 |



D K D F

| D | d | b | d ₂ | d ₃ | a | c | f | e | Order No. |
|-----|-----|----|----------------|----------------|----|------|------|----|----------------|
| 280 | 255 | 74 | 270 | 276 | 15 | 31.5 | 21.3 | 12 | DKDF280*255*74 |
| 290 | 265 | 74 | 280 | 286 | 15 | 31.5 | 21.3 | 12 | DKDF290*265*74 |
| 300 | 275 | 74 | 290 | 296 | 15 | 31.5 | 21.3 | 12 | DKDF300*275*74 |

1. Installation Recommendation



2. Installation Sizes

| D H8 | d h9 | L+0.2 | H |
|----------|--------|-------|------|
| <96 | D-16.8 | 8 | 7.5 |
| 96-190 | D-20 | 10 | 9.5 |
| 191-380 | D-28 | 13 | 12.5 |
| 381-1000 | D-36 | 20 | 19.5 |

3. Application and properties

Apply to hydraulic piston sealing. Consisting of a seal ring, two L-shaped POM back-up rings and an acting force O-Ring. The back-up ring acts as a support and guide to ensure a tight sealing environment. High wear resistance, low friction, no crawling phenomenon, easy installation.

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

L-Ring: POM / PA



D G D A

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 40 - 1600mm | 0 - 45MPa | -30°C +100°C | 1 m/s | hydraulic oil, flame retardant liquid, water and others |

6. Installation Dimensions

| D H8 | d h9 | H | L | e | Order No. |
|------|------|------|----|----|------------------|
| 40 | 23.2 | 7.5 | 8 | 7 | DGDA40*23.2*7.5 |
| 45 | 28.2 | 7.5 | 8 | 7 | DGDA45*28.2*7.5 |
| 50 | 33.2 | 7.5 | 8 | 7 | DGDA50*33.2*7.5 |
| 56 | 39.2 | 7.5 | 8 | 7 | DGDA56*39.2*7.5 |
| 63 | 46.2 | 7.5 | 8 | 7 | DGDA63*46.2*7.5 |
| 65 | 48.2 | 7.5 | 8 | 7 | DGDA65*48.2*7.5 |
| 70 | 53.2 | 7.5 | 8 | 7 | DGDA70*53.2*7.5 |
| 75 | 58.2 | 7.5 | 8 | 7 | DGDA75*58.2*7.5 |
| 80 | 63.2 | 7.5 | 8 | 7 | DGDA80*63.2*7.5 |
| 85 | 68.2 | 7.5 | 8 | 7 | DGDA85*68.2*7.5 |
| 90 | 73.2 | 7.5 | 8 | 7 | DGDA90*73.2*7.5 |
| 95 | 78.2 | 7.5 | 8 | 7 | DGDA95*78.2*7.5 |
| 100 | 80 | 9.5 | 10 | 10 | DGDA100*80*9.5 |
| 105 | 85 | 9.5 | 10 | 10 | DGDA105*85*9.5 |
| 110 | 90 | 9.5 | 10 | 10 | DGDA110*90*9.5 |
| 115 | 95 | 9.5 | 10 | 10 | DGDA115*95*9.5 |
| 120 | 100 | 9.5 | 10 | 10 | DGDA120*100*9.5 |
| 125 | 105 | 9.5 | 10 | 10 | DGDA125*105*9.5 |
| 130 | 110 | 9.5 | 10 | 10 | DGDA130*110*9.5 |
| 135 | 115 | 9.5 | 10 | 10 | DGDA135*115*9.5 |
| 140 | 120 | 9.5 | 10 | 10 | DGDA140*120*9.5 |
| 145 | 125 | 9.5 | 10 | 10 | DGDA145*125*9.5 |
| 150 | 130 | 9.5 | 10 | 10 | DGDA150*130*9.5 |
| 155 | 135 | 9.5 | 10 | 10 | DGDA155*135*9.5 |
| 160 | 140 | 9.5 | 10 | 10 | DGDA160*140*9.5 |
| 170 | 150 | 9.5 | 10 | 10 | DGDA170*150*9.5 |
| 180 | 160 | 9.5 | 10 | 10 | DGDA180*160*9.5 |
| 190 | 170 | 9.5 | 10 | 10 | DGDA190*170*9.5 |
| 200 | 172 | 12.5 | 13 | 12 | DGDA200*172*12.5 |
| 210 | 182 | 12.5 | 13 | 12 | DGDA210*182*12.5 |
| 220 | 192 | 12.5 | 13 | 12 | DGDA220*192*12.5 |
| 225 | 197 | 12.5 | 13 | 12 | DGDA225*197*12.5 |
| 235 | 207 | 12.5 | 13 | 12 | DGDA235*207*12.5 |




D G D A

| D H8 | d h9 | H | L | e | Order No. |
|------|------|------|----|----|-------------------|
| 240 | 212 | 12.5 | 13 | 12 | DGDA240*212*12.5 |
| 250 | 222 | 12.5 | 13 | 12 | DGDA250*222*12.5 |
| 265 | 237 | 12.5 | 13 | 12 | DGDA265*237*12.5 |
| 275 | 247 | 12.5 | 13 | 12 | DGDA275*247*12.5 |
| 280 | 252 | 12.5 | 13 | 12 | DGDA280*252*12.5 |
| 290 | 262 | 12.5 | 13 | 12 | DGDA290*262*12.5 |
| 300 | 272 | 12.5 | 13 | 12 | DGDA300*272*12.5 |
| 310 | 282 | 12.5 | 13 | 15 | DGDA310*282*12.5 |
| 320 | 292 | 12.5 | 13 | 15 | DGDA320*292*12.5 |
| 340 | 312 | 12.5 | 13 | 15 | DGDA340*312*12.5 |
| 350 | 322 | 12.5 | 13 | 15 | DGDA350*322*12.5 |
| 360 | 332 | 12.5 | 13 | 15 | DGDA360*332*12.5 |
| 380 | 352 | 12.5 | 13 | 15 | DGDA380*352*12.5 |
| 400 | 364 | 19.5 | 20 | 15 | DGDA400*364*19.5 |
| 420 | 384 | 19.5 | 20 | 15 | DGDA420*384*19.5 |
| 425 | 389 | 19.5 | 20 | 15 | DGDA425*389*19.5 |
| 450 | 414 | 19.5 | 20 | 15 | DGDA450*414*19.5 |
| 480 | 444 | 19.5 | 20 | 15 | DGDA480*444*19.5 |
| 500 | 464 | 19.5 | 20 | 15 | DGDA500*464*19.5 |
| 560 | 524 | 19.5 | 20 | 18 | DGDA560*524*19.5 |
| 600 | 564 | 19.5 | 20 | 18 | DGDA600*564*19.5 |
| 630 | 594 | 19.5 | 20 | 18 | DGDA630*594*19.5 |
| 650 | 614 | 19.5 | 20 | 18 | DGDA650*614*19.5 |
| 700 | 664 | 19.5 | 20 | 18 | DGDA700*664*19.5 |
| 720 | 684 | 19.5 | 20 | 18 | DGDA720*684*19.5 |
| 750 | 714 | 19.5 | 20 | 18 | DGDA750*714*19.5 |
| 780 | 744 | 19.5 | 20 | 18 | DGDA780*744*19.5 |
| 800 | 764 | 19.5 | 20 | 18 | DGDA800*764*19.5 |
| 850 | 814 | 19.5 | 20 | 18 | DGDA850*814*19.5 |
| 900 | 864 | 19.5 | 20 | 18 | DGDA900*864*19.5 |
| 950 | 914 | 19.5 | 20 | 18 | DGDA950*914*19.5 |
| 1000 | 964 | 19.5 | 20 | 18 | DGDA1000*964*19.5 |



1. Installation Recommendation



2. Application and properties

Suitable for long stroke, a wide range of fluids and high temperature occasions. The application of heavy duty double acting piston sealing under high pressure conditions is excellent. Applicable to larger piston clearance , it has good leakage control, extrusion resistance and wear resistance in heavy duty and construction machinery cylinder piston sealing system. Good static sealing property, simple groove structure, larger extrusion clearances can be allowed, be able to work in dusty condition.

3. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

Back-up ring: POM / PA

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|---------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 50 - 350mm | 0 - 50MPa | -30°C +100°C | 1.5 m/s | hydraulic oil, flame retardant liquid, water and others |



5. Installation Dimensions


| Nominal Size of Packing, and Housing dimensions | | | L+0.2 | Order No. |
|---|----------------|------|-------|------------------|
| D ₁ | d _N | H | | |
| 50 | 36 | 8.5 | 9 | SPGW50*36*8.5 |
| 55 | 41 | 8.5 | 9 | SPGW55*41*8.5 |
| 60 | 46 | 8.5 | 9 | SPGW60*46*8.5 |
| 63 | 48 | 10.5 | 11 | SPGW63*48*10.5 |
| 65 | 50 | 10.5 | 11 | SPGW65*50*10.5 |
| 70 | 55 | 10.5 | 11 | SPGW70*55*10.5 |
| 75 | 60 | 10.5 | 11 | SPGW75*60*10.5 |
| 80 | 65 | 10.5 | 11 | SPGW80*65*10.5 |
| 85 | 70 | 10.5 | 11 | SPGW85*70*10.5 |
| 90 | 75 | 10.5 | 11 | SPGW90*75*10.5 |
| 95 | 80 | 10.5 | 11 | SPGW95*80*10.5 |
| 100 | 85 | 12 | 12.5 | SPGW100*85*12 |
| 105 | 90 | 12 | 12.5 | SPGW105*90*12 |
| 110 | 95 | 12 | 12.5 | SPGW110*95*12 |
| 115 | 100 | 12 | 12.5 | SPGW115*100*12 |
| 120 | 105 | 12 | 12.5 | SPGW120*105*12 |
| 125 | 102 | 15.5 | 16 | SPGW125*102*15.5 |
| 130 | 107 | 15.5 | 16 | SPGW130*107*15.5 |
| 135 | 112 | 15.5 | 16 | SPGW135*112*15.5 |
| 140 | 117 | 15.5 | 16 | SPGW140*117*15.5 |
| 145 | 122 | 15.5 | 16 | SPGW145*122*15.5 |
| 150 | 127 | 15.5 | 16 | SPGW150*127*15.5 |
| 155 | 132 | 15.5 | 16 | SPGW155*132*15.5 |
| 160 | 137 | 15.5 | 16 | SPGW160*137*15.5 |
| 165 | 142 | 15.5 | 16 | SPGW165*142*15.5 |
| 170 | 147 | 15.5 | 16 | SPGW170*147*15.5 |
| 180 | 157 | 15.5 | 16 | SPGW180*157*15.5 |
| 185 | 162 | 15.5 | 16 | SPGW185*162*15.5 |
| 190 | 167 | 15.5 | 16 | SPGW190*167*15.5 |
| 200 | 177 | 15.5 | 16 | SPGW200*177*15.5 |
| 210 | 187 | 15.5 | 16 | SPGW210*187*15.5 |
| 220 | 197 | 15.5 | 16 | SPGW220*197*15.5 |
| 225 | 202 | 17 | 17.5 | SPGW225*202*15.5 |
| 230 | 207 | 17 | 17.5 | SPGW230*207*15.5 |
| 240 | 217 | 17 | 17.5 | SPGW240*217*15.5 |
| 250 | 222 | 17 | 17.5 | SPGW250*222*17 |
| 260 | 232 | 17 | 17.5 | SPGW260*232*17 |
| 270 | 242 | 17 | 17.5 | SPGW270*242*17 |
| 280 | 252 | 17 | 17.5 | SPGW280*252*17 |



SPGW

| Nominal Size of Packing, and Housing dimensions | | | L+0.2 | Order No. |
|---|----------------|----|-------|----------------|
| D ₁ | d _N | H | | |
| 300 | 272 | 17 | 17.5 | SPGW300*272*17 |
| 320 | 292 | 17 | 17.5 | SPGW320*292*17 |
| 350 | 322 | 17 | 17.5 | SPGW350*322*17 |

1. Installation Recommendation



2. Application and properties

TPM/DBM is a double acting sealing and guiding element, Consisting of an elastomer, two back-up rings and two guide rings. Dynamic and static properties of the elastomer play a good sealing role, The back-up ring prevents the elastomer from being squeezed into the sealing gap, the function of the guide ring is to guide the piston in the cylinder and absorb the radial force. The sealing is mainly used for piston and hydraulic cylinder, such as bulldozers, excavators, loaders, hydraulic gates and agricultural machinery.

3. Standard materials

Guide ring: POM

Back-up ring: TPU polymer

Elastomer: NBR

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|---------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 20-250mm | 0-35MPa | -30°C +120°C | 0.5 m/s | petroleum base hydraulic oil, nonflammable hydraulic oil, environmental protection hydraulic oil |



TPM / DBM

5. Installation Dimensions

| Cylinder Dia. | Groove Size | | | | | Order No. |
|------------------|-------------------|----------------|---------------------|-------------------|--------------------|--------------------|
| | D _N H9 | d ₁ | L ₁ +0.2 | d ₂ h9 | d ₃ h11 | |
| 20 | 11 | 13.5 | 17 | 19 | 2.1 | TPM20*11*13.5*2.1 |
| | 13 | 13.5 | 19 | 21 | 2.1 | TPM22*13*13.5*2.1 |
| | 15 | 12 | 21 | 23 | 4 | TPM25*15*12*4 |
| 25 | 15 | 12.5 | 22 | 24 | 4 | TPM25*15*12.5*4 |
| | 15 | 16.4 | 21.45 | 23.5 | 6.35 | TPM25*15*16.4*6.35 |
| | 16 | 13.5 | 22 | 24 | 2.1 | TPM25*16*13.5*2.1 |
| 28 | 19 | 13.5 | 25 | 27 | 2.1 | TPM28*19*13.5*2.1 |
| | 17 | 15.4 | 26.5 | 28.5 | 6.35 | TPM30*17*15.4*6.35 |
| | 21 | 13.5 | 27 | 29 | 2.1 | TPM30*21*13.5*2.1 |
| 32 | 22 | 15.5 | 28 | 31 | 2.6 | TPM32*22*15.5*2.6 |
| | 22 | 16.4 | 28.5 | 30.5 | 6.35 | TPM32*22*16.4*6.35 |
| | 25 | 15.5 | 31 | 34 | 2.6 | TPM35*25*15.5*2.6 |
| 35 | 25 | 16.4 | 31.4 | 33.5 | 6.35 | TPM35*25*16.4*6.35 |
| | 24 | 18.4 | 35.4 | 38.5 | 6.35 | TPM40*24*18.4*6.35 |
| | 26 | 15.5 | 36 | 39 | 2.6 | TPM40*26*15.5*2.6 |
| 40 | 30 | 12.5 | 36 | 38 | 4 | TPM40*30*12.5*4 |
| | 30 | 12.5 | 37 | 39 | 4 | TPM40*30*12.5*4 |
| | 30 | 16.4 | 35.4 | 38.5 | 6.35 | TPM40*30*16.4*6.35 |
| 42 | 28 | 15.5 | 38 | 41 | 2.6 | TPM42*28*15.5*2.6 |
| | 29 | 18.4 | 40.4 | 43.5 | 6.35 | TPM45*29*18.4*6.35 |
| | 31 | 15.5 | 41 | 44 | 2.6 | TPM45*31*15.5*2.6 |
| 45 | 35 | 16.4 | 40.4 | 43.5 | 6.35 | TPM45*35*16.4*6.35 |
| | 34 | 18.4 | 45.4 | 48.5 | 6.35 | TPM50*34*18.4*6.35 |
| | 34 | 20.5 | 46 | 49 | 3.1 | TPM50*34*20.5*3.1 |
| 55 | 39 | 18.4 | 50.36 | 53.5 | 6.35 | TPM55*39*18.4*6.35 |
| | 39 | 20.5 | 51 | 54 | 3.1 | TPM55*39*20.5*3.1 |
| | 40 | 20.5 | 52 | 55 | 3.1 | TPM56*40*20.5*3.1 |
| 60 | 44 | 18.4 | 55.4 | 58.5 | 6.35 | TPM60*44*18.4*6.35 |
| | 44 | 20.5 | 56 | 59 | 3.1 | TPM60*44*20.5*3.1 |
| | 47 | 18.4 | 58.4 | 61.5 | 6.35 | TPM63*47*18.4*6.35 |
| 63 | 47 | 19.4 | 58.4 | 61.5 | 6.35 | TPM63*47*19.4*6.35 |
| | 47 | 20.5 | 59 | 62 | 3.1 | TPM63*47*20.5*3.1 |
| | 49 | 20.5 | 61 | 64 | 3.1 | TPM65*49*20.5*3.1 |
| 65 | 50 | 18.4 | 60.4 | 63.5 | 6.35 | TPM65*50*18.4*6.35 |
| | 50 | 22.4 | 64.2 | 68.3 | 6.35 | TPM70*50*22.4*6.35 |
| | 54 | 20.5 | 66 | 69 | 3.1 | TPM70*54*20.5*3.1 |

| Cylinder Dia. | Groove Size | | | | | Order No. |
|------------------|-------------------|----------------|---------------------|-------------------|--------------------|------------------------|
| | D _N H9 | d ₁ | L ₁ +0.2 | d ₂ h9 | d ₃ h11 | |
| 75 | 55 | 22.4 | 69.2 | 73.3 | 6.35 | TPM75*55*22.4*6.35 |
| 75 | 59 | 20.5 | 71 | 74 | 3.1 | TPM75*59*20.5*3.1 |
| 80 | 60 | 22.4 | 74.15 | 78.3 | 6.35 | TPM80*60*22.4*6.35 |
| 80 | 62 | 22.5 | 76 | 79 | 3.6 | TPM80*62*22.5*3.6 |
| 85 | 65 | 22.4 | 79.15 | 83.3 | 6.35 | TPM85*65*22.4*6.35 |
| 90 | 70 | 22.4 | 84.15 | 88.3 | 6.35 | TPM90*70*22.4*6.35 |
| 90 | 72 | 22.5 | 86 | 89 | 3.6 | TPM90*72*22.5*3.6 |
| 95 | 75 | 22.4 | 89.15 | 93.3 | 6.35 | TPM95*75*22.4*6.35 |
| 100 | 75 | 22.4 | 93.15 | 98 | 6.35 | TPM100*75*22.4*6.35 |
| 100 | 82 | 22.5 | 96 | 99 | 3.6 | TPM100*82*22.5*3.6 |
| 105 | 80 | 22.4 | 98.1 | 103 | 6.35 | TPM105*80*22.4*6.35 |
| 110 | 85 | 22.4 | 103.1 | 108 | 6.35 | TPM110*85*22.4*6.35 |
| 110 | 92 | 22.5 | 106 | 109 | 3.6 | TPM110*92*22.5*3.6 |
| 115 | 90 | 22.4 | 108.1 | 113 | 6.35 | TPM115*90*22.4*6.35 |
| 115 | 97 | 22.5 | 111 | 114 | 3.6 | TPM115*97*22.5*3.6 |
| 120 | 95 | 22.4 | 113.1 | 118.1 | 6.35 | TPM120*95*22.4*6.35 |
| 125 | 100 | 22.4 | 118.1 | 123 | 6.35 | TPM125*100*22.4*6.35 |
| 125 | 103 | 25.4 | 121 | 124 | 5.1 | TPM125*103*25.4*5.1 |
| 130 | 105 | 22.4 | 123.1 | 128 | 6.35 | TPM130*105*22.4*6.35 |
| 130 | 105 | 22.4 | 122.6 | 127.5 | 9.5 | TPM130*105*22.4*9.5 |
| 133 | 115 | 22.4 | 125.6 | 130.5 | 9.52 | TPM133*115*22.4*9.52 |
| 135 | 110 | 25.4 | 128.1 | 133 | 6.35 | TPM135*110*25.4*6.35 |
| 135 | 110 | 25.4 | 127.6 | 132.5 | 9.5 | TPM135*110*25.4*9.5 |
| 140 | 115 | 25.4 | 133 | 138 | 6.35 | TPM140*115*25.4*6.35 |
| 140 | 115 | 25.4 | 132.6 | 137.5 | 9.5 | TPM140*115*25.4*9.5 |
| 140 | 118 | 26.5 | 136 | 139 | 5.1 | TPM140*118*26.5*5.1 |
| 145 | 120 | 25.4 | 138.3 | 142.95 | 6.35 | TPM145*120*25.4*6.35 |
| 145 | 120 | 25.4 | 137.6 | 142.5 | 9.5 | TPM145*120*25.4*9.5 |
| 150 | 125 | 25.4 | 142.6 | 147.5 | 9.5 | TPM150*125*25.4*9.5 |
| 150 | 125 | 25.4 | 143 | 148 | 6.35 | TPM150*125*25.4*6.35 |
| 150 | 128 | 26.5 | 146 | 149 | 5.1 | TPM150*128*26.5*5.1 |
| 152.4 | 127 | 31.75 | 145 | 149.91 | 9.5 | TPM152.4*127*31.75*9.5 |
| 155 | 130 | 25.4 | 147.6 | 152.5 | 9.5 | TPM155*130*25.4*9.5 |
| 155 | 130 | 25.4 | 148 | 153 | 6.35 | TPM155*130*25.4*6.35 |
| 160 | 130 | 25.4 | 153 | 157.5 | 6.35 | TPM160*130*25.4*6.35 |
| 160 | 130 | 25.4 | 152.6 | 157.5 | 9.5 | TPM160*130*25.4*9.5 |




TPM / DBM

| Cylinder Dia. | Groove Size | | | | | Order No. |
|-------------------|----------------|---------------------|-------------------|--------------------|---------------------|----------------------|
| D _N H9 | d ₁ | L ₁ +0.2 | d ₂ h9 | d ₃ h11 | L ₂ +0.1 | |
| 160 | 135 | 25.4 | 152.6 | 157.5 | 9.5 | TPM160*135*25.4*9.5 |
| 160 | 138 | 26.5 | 156 | 159 | 9.1 | TPM160*138*26.5*9.1 |
| 165 | 140 | 25.4 | 157.6 | 162.5 | 9.5 | TPM165*140*25.4*9.5 |
| 170 | 145 | 25.4 | 161.7 | 167.1 | 12.7 | TPM170*145*25.4*12.7 |
| 170 | 148 | 26.5 | 166 | 169 | 5.1 | TPM170*148*26.5*5.1 |
| 175 | 150 | 25.4 | 166.7 | 172.1 | 12.7 | TPM175*150*25.4*12.7 |
| 180 | 150 | 35.4 | 172.95 | 177.87 | 6.35 | TPM180*150*35.4*6.35 |
| 180 | 155 | 25.4 | 171.7 | 177.1 | 12.7 | TPM180*155*25.4*12.7 |
| 185 | 160 | 25.4 | 176.7 | 182.1 | 12.7 | TPM185*160*25.4*12.7 |
| 190 | 165 | 25.4 | 181.7 | 187 | 12.7 | TPM190*165*25.4*12.7 |
| 195 | 170 | 25.4 | 186.7 | 192 | 12.7 | TPM195*170*25.4*12.7 |
| 200 | 175 | 25.4 | 191.6 | 197 | 12.7 | TPM200*175*25.4*12.7 |
| 200 | 175 | 31.5 | 196 | 199 | 6.6 | TPM200*175*31.5*6.6 |
| 210 | 185 | 25.4 | 201.6 | 207 | 12.7 | TPM210*185*25.4*12.7 |
| 220 | 190 | 25.4 | 212.7 | 217.9 | 6.35 | TPM220*190*25.4*6.35 |
| 220 | 195 | 25.4 | 211.6 | 217 | 12.7 | TPM220*195*25.4*12.7 |
| 230 | 205 | 25.4 | 221.6 | 227 | 12.7 | TPM230*205*25.4*12.7 |
| 240 | 215 | 25.4 | 231.6 | 237 | 12.7 | TPM240*215*25.4*12.7 |
| 250 | 220 | 35.4 | 242.9 | 247.85 | 6.35 | TPM250*220*35.4*6.35 |
| 250 | 225 | 25.4 | 241.6 | 247 | 12.7 | TPM250*225*25.4*12.7 |



OK

1. Installation Recommendation



2. Installation Sizes

The installation groove must be carefully deburred and cleaned. The cylinder bore must have a leading edge chamfer. Profile OK can be snapped into closed grooves.

3. Application and properties

Extreme wear resistance, easy installation on single-part piston without assembly aids due to the split design of the sealing ring. Assembly on one-part piston is possible. Insensitive to extreme pressure peaks. Extreme high extreme pressure resistance. High pressure and large gaps due to the special compound properties of the seal ring. Dimensions according to ISO 7425-1. Short axial assembly length. Installation in closed and undercut housings. Additional sizes of machined products available on short notice.

4. Standard materials

Sealing ring: filled modified thermoplast

O-ring: NBR



OK

5. Working Conditions

| Working Conditions | | | |
|--------------------|----------------|-------------------|-------|
| Diameter Range | Pressure Range | Temperature Range | Speed |
| 25 - 480mm | 0 - 80MPa | -30°C +110°C | 1 m/s |

6. Installation Dimensions

| D ₁ | d ₁ | L | Order No. |
|----------------|----------------|-----|----------------|
| 25 | 16 | 4.2 | OK25*16*4.2 |
| 32 | 21 | 4.2 | OK32*21*4.2 |
| 40 | 26.3 | 5.8 | OK40*26.3*5.8 |
| 40 | 29 | 4.2 | OK40*29*4.2 |
| 50 | 34.5 | 6.3 | OK50*34.5*6.3 |
| 50 | 36.3 | 5.8 | OK50*36.3*5.8 |
| 50 | 37 | 8 | OK50*37*8 |
| 50 | 39 | 4.2 | OK50*39*4.2 |
| 55 | 44 | 4.2 | OK55*44*4.2 |
| 60 | 41.7 | 7 | OK60*41.7*7 |
| 60 | 49 | 4.2 | OK60*49*4.2 |
| 63 | 44.7 | 7 | OK63*44.7*7 |
| 63 | 47.5 | 6.3 | OK63*47.5*6.3 |
| 63 | 52 | 4.2 | OK63*52*4.2 |
| 70 | 51.7 | 7 | OK70*51.7*7 |
| 70 | 54.5 | 6.3 | OK70*54.5*6.3 |
| 70 | 59 | 4.2 | OK70*59*4.2 |
| 75 | 54 | 8 | OK75*54*8 |
| 75 | 59.5 | 6.3 | OK75*59.5*6.3 |
| 80 | 59 | 8 | OK80*59*8 |
| 80 | 64.5 | 6.3 | OK80*64.5*6.3 |
| 85 | 64 | 8 | OK85*64*8 |
| 90 | 69 | 8 | OK90*69*8 |
| 90 | 74.5 | 6.3 | OK90*74.5*6.3 |
| 95 | 74 | 8 | OK95*74*8 |
| 100 | 79 | 8 | OK100*79*8 |
| 100 | 84.5 | 6.3 | OK100*84.5*6.3 |
| 105 | 84 | 8 | OK105*84*8 |
| 110 | 89 | 8 | OK110*89*8 |
| 110 | 94.5 | 6.3 | OK110*94.5*6.3 |
| 115 | 94 | 8 | OK115*94*8 |
| 115 | 100 | 8 | OK115*100*8 |
| 120 | 99 | 8 | OK120*99*8 |




OK

| D ₁ | d ₁ | L | Order No. |
|----------------|----------------|-----|-----------------|
| 125 | 104 | 8 | OK125*104*8 |
| 125 | 109.5 | 6.3 | OK125*109.5*6.3 |
| 130 | 109 | 8 | OK130*109*8 |
| 130 | 114.5 | 6.3 | OK130*114.5*6.3 |
| 130 | 115 | 8 | OK130*115*8 |
| 135 | 114 | 8 | OK135*114*8 |
| 135 | 119.5 | 6.3 | OK135*119.5*6.3 |
| 140 | 119 | 8 | OK140*119*8 |
| 140 | 125 | 8 | OK140*125*8 |
| 145 | 124 | 8 | OK145*124*8 |
| 150 | 129 | 8 | OK150*129*8 |
| 150 | 135 | 8 | OK150*135*8 |
| 152.4 | 131.5 | 8 | OK152.4*131.5*8 |
| 160 | 139 | 8 | OK160*139*8 |
| 160 | 148 | 8 | OK160*148*8 |
| 165 | 144 | 8 | OK165*144*8 |
| 170 | 149 | 8 | OK170*149*8 |
| 175 | 154 | 8 | OK175*154*8 |
| 180 | 159 | 8 | OK180*159*8 |
| 190 | 169 | 8 | OK190*169*8 |
| 200 | 179 | 8 | OK200*179*8 |
| 210 | 189 | 8 | OK210*189*8 |
| 220 | 199 | 8 | OK220*199*8 |
| 220 | 205 | 8 | OK220*205*8 |
| 230 | 209 | 8 | OK230*209*8 |
| 240 | 225 | 8 | OK240*225*8 |
| 250 | 229 | 8 | OK250*229*8 |
| 260 | 239 | 8 | OK260*239*8 |
| 270 | 249 | 8 | OK270*249*8 |
| 280 | 255.5 | 8 | OK280*255.5*8 |
| 290 | 271 | 9.5 | OK290*271*9.5 |
| 300 | 272 | 9.5 | OK300*272*9.5 |
| 320 | 292 | 9.5 | OK320*292*9.5 |
| 330 | 302 | 9.5 | OK330*302*9.5 |
| 350 | 322 | 9.5 | OK350*322*9.5 |
| 370 | 342 | 9.5 | OK370*342*9.5 |
| 420 | 392 | 9.5 | OK420*392*9.5 |
| 450 | 422 | 9.5 | OK450*422*9.5 |
| 480 | 452 | 9.5 | OK480*452*9.5 |



D D A

1. Installation Recommendation



2. Application and properties

Apply to the hydraulic cylinder of piston sealing, generally used in conjunction with the guide sleeve. The seal ring and piston conforming to be a symmetric section to achieve the sealing performance. The Non-standard Y-ring has the function of sealing and provides the elastic force to the sealing ring and compensates for the abrasion. Very high pressure stability under pressure and harsh conditions, high wear resistance, low friction, no crawling phenomenon.

3. Standard materials

Sealing ring: filled PTFE

Y-Ring: NBR / PU

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 40 - 1600mm | 0 - 45MPa | -30°C +100°C | 1 m/s | hydraulic oil, flame retardant liquid, water and others |



D D A

5. Installation Dimensions

| D H 8 | d h 9 | H | L+0.2 | e | Order No. |
|-------|-------|----|-------|----|---------------|
| 40 | 32 | 7 | 7.5 | 6 | DDA40*32*7.5 |
| 43 | 35 | 7 | 7.5 | 6 | DDA43*35*7.5 |
| 44 | 36 | 7 | 7.5 | 6 | DDA44*36*7.5 |
| 45 | 37 | 7 | 7.5 | 6 | DDA45*37*7.5 |
| 48 | 40 | 7 | 7.5 | 6 | DDA48*40*7.5 |
| 50 | 42 | 7 | 7.5 | 6 | DDA50*42*7.5 |
| 55 | 45 | 7 | 7.5 | 6 | DDA55*45*7.5 |
| 60 | 45 | 12 | 13 | 6 | DDA60*45*13 |
| 63 | 53 | 8 | 8.5 | 6 | DDA63*53*8.5 |
| 63 | 48 | 12 | 13 | 6 | DDA63*48*13 |
| 65 | 50 | 12 | 8.5 | 6 | DDA65*50*8.5 |
| 65 | 50 | 12 | 13 | 6 | DDA65*50*13 |
| 70 | 55 | 12 | 13 | 6 | DDA70*55*13 |
| 75 | 60 | 12 | 13 | 6 | DDA75*60*13 |
| 78 | 63 | 12 | 13 | 6 | DDA78*63*13 |
| 80 | 65 | 12 | 13 | 6 | DDA80*65*13 |
| 85 | 70 | 12 | 13 | 6 | DDA85*70*13 |
| 87 | 72 | 12 | 13 | 6 | DDA87*72*13 |
| 90 | 75 | 12 | 13 | 7 | DDA90*75*13 |
| 95 | 80 | 12 | 13 | 7 | DDA95*80*13 |
| 100 | 85 | 12 | 13 | 7 | DDA100*85*13 |
| 105 | 90 | 12 | 13 | 7 | DDA105*90*13 |
| 110 | 95 | 12 | 13 | 7 | DDA110*95*13 |
| 115 | 100 | 12 | 13 | 7 | DDA115*100*13 |
| 120 | 105 | 12 | 13 | 7 | DDA120*105*13 |
| 125 | 110 | 12 | 13 | 7 | DDA125*110*13 |
| 130 | 115 | 12 | 13 | 7 | DDA130*115*13 |
| 140 | 120 | 12 | 13 | 7 | DDA140*120*13 |
| 145 | 125 | 12 | 13 | 10 | DDA145*125*13 |
| 150 | 130 | 12 | 13 | 10 | DDA150*130*13 |
| 160 | 140 | 12 | 13 | 10 | DDA160*140*13 |
| 160 | 140 | 16 | 17 | 10 | DDA160*140*17 |
| 170 | 150 | 16 | 17 | 10 | DDA170*150*17 |
| 180 | 160 | 16 | 17 | 10 | DDA180*160*17 |
| 185 | 165 | 16 | 17 | 10 | DDA185*165*17 |
| 190 | 170 | 16 | 17 | 10 | DDA190*170*17 |
| 200 | 180 | 16 | 17 | 10 | DDA200*180*17 |
| 210 | 190 | 16 | 17 | 10 | DDA210*190*17 |
| 220 | 200 | 16 | 17 | 10 | DDA220*200*17 |




D D A

| D H8 | d h9 | H | L+0.2 | e | Order No. |
|------|------|----|-------|----|---------------|
| 240 | 220 | 16 | 17 | 10 | DDA240*220*17 |
| 245 | 225 | 16 | 17 | 10 | DDA245*225*17 |
| 250 | 230 | 16 | 17 | 10 | DDA250*230*17 |
| 260 | 240 | 16 | 17 | 10 | DDA260*240*17 |
| 270 | 250 | 16 | 17 | 10 | DDA270*250*17 |
| 280 | 260 | 16 | 17 | 10 | DDA280*260*17 |
| 300 | 280 | 16 | 17 | 10 | DDA300*280*17 |
| 310 | 290 | 16 | 17 | 10 | DDA310*290*17 |
| 320 | 300 | 16 | 17 | 10 | DDA320*300*17 |
| 350 | 320 | 20 | 21 | 15 | DDA350*320*21 |
| 370 | 345 | 16 | 17 | 15 | DDA370*345*17 |
| 380 | 350 | 20 | 21 | 15 | DDA380*350*21 |
| 390 | 360 | 20 | 21 | 15 | DDA390*360*21 |
| 410 | 380 | 20 | 21 | 15 | DDA410*380*21 |
| 430 | 400 | 20 | 21 | 15 | DDA430*400*21 |
| 450 | 420 | 20 | 21 | 15 | DDA450*420*21 |
| 455 | 425 | 20 | 21 | 15 | DDA455*425*21 |
| 480 | 450 | 20 | 21 | 15 | DDA480*450*21 |
| 500 | 475 | 16 | 17 | 15 | DDA500*475*17 |
| 510 | 480 | 20 | 21 | 15 | DDA510*480*21 |
| 540 | 510 | 20 | 21 | 15 | DDA540*510*21 |
| 590 | 560 | 20 | 21 | 15 | DDA590*560*21 |
| 600 | 570 | 20 | 21 | 15 | DDA600*570*21 |
| 640 | 610 | 20 | 21 | 15 | DDA640*610*21 |
| 670 | 640 | 20 | 21 | 15 | DDA670*640*21 |



DDMA

1. Installation Recommendation



2. Application and properties

Suitable for seals of pistons and plungers, tandem seals for a variety of liquid applications are internal seals. Before installation, the sealing lip is protruded outwards, and the cylinder liner is pressed tightly after installation to provide elasticity for the wear ring, excellent sealing results can be achieved even in the absence of pressure. It can separate the liquid on both sides of the sealing ring, so it is also suitable for the sealing of the oil chamber, and the invasion of other liquids can be prevented. High wear resistance, low friction, no crawling phenomenon.

3. Standard materials

Sealing ring: filled PTFE

Elastomer: NBR / PU

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 40 - 1600mm | 0 - 25MPa | -30°C +100°C | 1 m/s | hydraulic oil, flame retardant liquid, water and others |



DDMA

5. Installation Dimensions

| D H8 | d h9 | H | L+0.2 | e | Order No. |
|------|------|----|-------|----|----------------|
| 40 | 30 | 15 | 16 | 7 | DDMA40*30*16 |
| 45 | 35 | 15 | 16 | 7 | DDMA45*35*16 |
| 50 | 40 | 15 | 16 | 7 | DDMA50*40*16 |
| 56 | 46 | 15 | 16 | 7 | DDMA56*46*16 |
| 63 | 53 | 15 | 16 | 7 | DDMA63*53*16 |
| 65 | 55 | 15 | 16 | 7 | DDMA65*55*16 |
| 70 | 60 | 15 | 16 | 7 | DDMA70*60*16 |
| 75 | 65 | 15 | 16 | 7 | DDMA75*65*16 |
| 80 | 70 | 15 | 16 | 7 | DDMA80*70*16 |
| 85 | 75 | 15 | 16 | 7 | DDMA85*75*16 |
| 90 | 80 | 15 | 16 | 7 | DDMA90*80*16 |
| 95 | 85 | 15 | 16 | 7 | DDMA95*85*16 |
| 100 | 90 | 15 | 16 | 7 | DDMA100*90*16 |
| 105 | 95 | 15 | 16 | 7 | DDMA105*95*16 |
| 115 | 105 | 15 | 16 | 7 | DDMA115*105*16 |
| 120 | 110 | 15 | 16 | 7 | DDMA120*110*16 |
| 125 | 113 | 15 | 16 | 10 | DDMA125*113*16 |
| 130 | 118 | 15 | 16 | 10 | DDMA130*118*16 |
| 135 | 123 | 15 | 16 | 10 | DDMA135*123*16 |
| 140 | 128 | 15 | 16 | 10 | DDMA140*128*16 |
| 145 | 133 | 15 | 16 | 10 | DDMA145*133*16 |
| 150 | 138 | 15 | 16 | 10 | DDMA150*138*16 |
| 155 | 143 | 15 | 16 | 10 | DDMA155*143*16 |
| 160 | 148 | 15 | 16 | 10 | DDMA160*148*16 |
| 170 | 158 | 15 | 16 | 10 | DDMA170*158*16 |
| 180 | 168 | 15 | 16 | 10 | DDMA180*168*16 |
| 190 | 178 | 15 | 16 | 10 | DDMA190*178*16 |
| 200 | 188 | 15 | 16 | 10 | DDMA200*188*16 |
| 210 | 198 | 15 | 16 | 10 | DDMA210*198*16 |
| 220 | 208 | 15 | 16 | 10 | DDMA220*208*16 |
| 225 | 213 | 15 | 16 | 10 | DDMA225*213*16 |
| 235 | 223 | 15 | 16 | 10 | DDMA235*223*16 |
| 240 | 228 | 15 | 16 | 10 | DDMA240*228*16 |
| 250 | 238 | 15 | 16 | 10 | DDMA250*238*16 |
| 265 | 253 | 15 | 16 | 10 | DDMA265*253*16 |
| 275 | 263 | 15 | 16 | 10 | DDMA275*263*16 |
| 280 | 268 | 15 | 16 | 10 | DDMA280*268*16 |
| 290 | 278 | 15 | 16 | 10 | DDMA290*278*16 |
| 300 | 288 | 15 | 16 | 15 | DDMA300*288*16 |




DDMA

| D H8 | d h9 | H | L+0.2 | e | Order No. |
|------|------|----|-------|----|----------------|
| 310 | 296 | 15 | 16 | 15 | DDMA310*296*16 |
| 320 | 306 | 15 | 16 | 15 | DDMA320*306*16 |
| 340 | 326 | 15 | 16 | 15 | DDMA340*326*16 |
| 350 | 336 | 15 | 16 | 15 | DDMA350*336*16 |
| 360 | 346 | 15 | 16 | 15 | DDMA360*346*16 |
| 380 | 366 | 15 | 16 | 15 | DDMA380*366*16 |
| 400 | 384 | 15 | 16 | 15 | DDMA400*384*16 |
| 420 | 404 | 15 | 16 | 15 | DDMA420*404*16 |
| 425 | 409 | 15 | 16 | 15 | DDMA425*409*16 |
| 450 | 434 | 15 | 16 | 15 | DDMA450*434*16 |
| 480 | 464 | 15 | 16 | 15 | DDMA480*464*16 |
| 500 | 484 | 15 | 16 | 15 | DDMA500*484*16 |
| 560 | 544 | 15 | 16 | 15 | DDMA560*544*16 |
| 600 | 584 | 15 | 16 | 15 | DDMA600*584*16 |
| 630 | 614 | 15 | 16 | 15 | DDMA630*614*16 |



1. Installation Recommendation



2. Installation Sizes

| Bore Diameter D_N H9 | | Groove Diameter | Groove Width | Radial Clearance S max. | | Radius | O-Ring Cross-Section |
|---------------------------|--------------------|--------------------|-----------------|----------------------------|-------|--------|-------------------------|
| Standard Range | Available range | d_1 h9 | $L_1+0.2$ | 32MPa | 50MPa | R_1 | d_2 |
| 8-39.9 | 8-135.0 | D_N -4.9 | 2.2 | 0.15 | 0.10 | 0.40 | 1.78 |
| 40-79.9 | 14-250.0 | D_N -7.5 | 3.2 | 0.20 | 0.15 | 0.60 | 2.62 |
| 80-132.9 | 22-460.0 | D_N -11.0 | 4.2 | 0.25 | 0.20 | 1.00 | 3.53 |
| 133-329.9 | 40-675.0 | D_N -15.5 | 6.3 | 0.30 | 0.25 | 1.30 | 5.33 |
| 330-669.9 | 133-690.0 | D_N -21.0 | 8.1 | 0.30 | 0.25 | 1.80 | 7.00 |
| 670-999.9 | 670-999.9 | D_N -28.0 | 9.5 | 0.45 | 0.30 | 2.50 | 8.40 |

3. Application and properties

Suitable for sealing with rotating or swinging rods, shafts, pins, rotary joints, etc. It is a rotary sealing ring that can withstand both sides pressure or alternating pressure role of the double acting effect, used in construction machinery, building machinery and automotive equipment. It can be applied on occasions where piston rod and piston seal are required, low friction, non viscous phenomenon, simple groove, good abrasion resistance and dimensional stability.



G N S

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3 - 1600mm | 0 - 30MPa | -30°C +200°C | 1 m/s | hydraulic oil, flame retardant liquid, water and others |

6. Installation Dimensions

| Bore Dia. | Groove Dia. | Groove Width | Order No. |
|-----------|-------------------|---------------------|----------------|
| D H9 | d ₁ h9 | L ₁ +0.2 | |
| 8 | 3.1 | 2.2 | GNS8*3.1*2.2 |
| 10 | 5.1 | 2.2 | GNS10*5.1*2.2 |
| 12 | 7.1 | 2.2 | GNS12*7.1*2.2 |
| 14 | 9.1 | 2.2 | GNS14*9.1*2.2 |
| 15 | 10.1 | 2.2 | GNS15*10.1*2.2 |
| 16 | 11.1 | 2.2 | GNS16*11.1*2.2 |
| 17 | 12.1 | 2.2 | GNS17*12.1*2.2 |
| 18 | 13.1 | 2.2 | GNS18*13.1*2.2 |
| 20 | 15.1 | 2.2 | GNS20*15.1*2.2 |
| 22 | 17.1 | 2.2 | GNS22*17.1*2.2 |
| 25 | 20.1 | 2.2 | GNS25*20.1*2.2 |
| 28 | 23.1 | 2.2 | GNS28*23.1*2.2 |
| 30 | 25.1 | 2.2 | GNS30*25.1*2.2 |
| 32 | 27.1 | 2.2 | GNS32*27.1*2.2 |
| 35 | 30.1 | 2.2 | GNS35*30.1*2.2 |
| 36 | 31.1 | 2.2 | GNS36*31.1*2.2 |
| 38 | 33.1 | 2.2 | GNS38*33.1*2.2 |
| 40 | 32.5 | 3.2 | GNS40*32.5*3.2 |
| 42 | 34.5 | 3.2 | GNS42*34.5*3.2 |
| 45 | 37.5 | 3.2 | GNS45*37.5*3.2 |
| 48 | 40.5 | 3.2 | GNS48*40.5*3.2 |
| 50 | 42.5 | 3.2 | GNS50*42.5*3.2 |
| 52 | 44.5 | 3.2 | GNS52*44.5*3.2 |
| 53 | 45.5 | 3.2 | GNS53*45.5*3.2 |
| 55 | 47.5 | 3.2 | GNS55*47.5*3.2 |
| 60 | 52.5 | 3.2 | GNS60*52.5*3.2 |
| 63 | 55.5 | 3.2 | GNS63*55.5*3.2 |



G N S

| Bore Dia. | Groove Dia. | Groove Width | Order No. |
|-----------|-------------------|---------------------|--|
| D H9 | d ₁ h9 | L ₁ +0.2 | |
| 65 | 57.5 | 3.2 | GNS65*57.5*3.2 GNS70*62.5*3.2 GNS75*67.5*3.2 |
| 70 | 62.5 | 3.2 | |
| 75 | 67.5 | 3.2 | |
| 80 | 69 | 4.2 | GNS80*69*4.2 GNS85*74*4.2 GNS90*79*4.2 |
| 85 | 74 | 4.2 | |
| 90 | 79 | 4.2 | |
| 95 | 84 | 4.2 | GNS95*84*4.2 GNS100*89*4.2 GNS102*91*4.2 |
| 100 | 89 | 4.2 | |
| 102 | 91 | 4.2 | |
| 105 | 94 | 4.2 | GNS105*94*4.2 GNS110*99*4.2 GNS115*104*4.2 |
| 110 | 99 | 4.2 | |
| 115 | 104 | 4.2 | |
| 120 | 109 | 4.2 | GNS120*109*4.2 GNS125*114*4.2 GNS130*119*4.2 |
| 125 | 114 | 4.2 | |
| 130 | 119 | 4.2 | |
| 135 | 119.5 | 6.3 | GNS135*119.5*6.3 GNS140*124.5*6.3 GNS150*134.5*6.3 |
| 140 | 124.5 | 6.3 | |
| 150 | 134.5 | 6.3 | |
| 160 | 144.5 | 6.3 | GNS160*144.5*6.3 GNS170*154.5*6.3 GNS175*159.5*6.3 |
| 170 | 154.5 | 6.3 | |
| 175 | 159.5 | 6.3 | |
| 180 | 164.5 | 6.3 | GNS180*164.5*6.3 GNS190*174.5*6.3 GNS200*184.5*6.3 |
| 190 | 174.5 | 6.3 | |
| 200 | 184.5 | 6.3 | |
| 210 | 194.5 | 6.3 | GNS210*194.5*6.3 GNS220*204.5*6.3 GNS230*214.5*6.3 |
| 220 | 204.5 | 6.3 | |
| 230 | 214.5 | 6.3 | |
| 240 | 224.5 | 6.3 | GNS240*224.5*6.3 GNS250*234.5*6.3 GNS280*264.5*6.3 |
| 250 | 234.5 | 6.3 | |
| 280 | 264.5 | 6.3 | |
| 300 | 284.5 | 6.3 | GNS300*284.5*6.3 GNS310*294.5*6.3 GNS320*304.5*6.3 |
| 310 | 294.5 | 6.3 | |
| 320 | 304.5 | 6.3 | |
| 350 | 329 | 8.1 | GNS350*329*8.1 GNS360*339*8.1 GNS400*379*8.1 |
| 360 | 339 | 8.1 | |
| 400 | 379 | 8.1 | |
| 420 | 399 | 8.1 | GNS420*399*8.1 GNS450*429*8.1 GNS480*459*8.1 |
| 450 | 429 | 8.1 | |
| 480 | 459 | 8.1 | |




G N S

| Bore Dia. | Groove Dia. | Groove Width | Order No. |
|-----------|-------------------|---------------------|----------------|
| D H9 | d ₁ h9 | L ₁ +0.2 | |
| 500 | 479 | 8.1 | GNS500*479*8.1 |
| 510 | 489 | 8.1 | GNS510*489*8.1 |
| 520 | 499 | 8.1 | GNS520*499*8.1 |
| 550 | 529 | 8.1 | GNS550*529*8.1 |
| 600 | 579 | 8.1 | GNS600*579*8.1 |
| 650 | 629 | 8.1 | GNS650*629*8.1 |



1. Installation Recommendation



2. Installation Sizes

| Rod Diameter $D_N H9$ | | Groove Diameter | Groove Width | Radial Clearance $S_{max.}$ | | Radius | O-Ring Cross-Section |
|--------------------------|-------------------------|--------------------|-----------------|--------------------------------|-------|--------|-------------------------|
| Standard Application | Extended Application | $D_N H9$ | $L_1+0.2$ | 32MPa | 50MPa | R_1 | d_2 |
| 6-18.9 | 6-130.0 | $d_1+4.9$ | 2.20 | 0.15 | 0.10 | 0.40 | 1.78 |
| 19-37.9 | 10-245.0 | $d_1+7.5$ | 3.20 | 0.20 | 0.15 | 0.60 | 2.62 |
| 38-199.9 | 19-455.0 | $d_1+11.0$ | 4.20 | 0.25 | 0.20 | 1.00 | 3.53 |
| 200-255.9 | 38-655.0 | $d_1+15.5$ | 6.30 | 0.30 | 0.25 | 1.30 | 5.33 |
| 256-649.9 | 120-655.0 | $d_1+21.0$ | 8.10 | 0.30 | 0.25 | 1.80 | 7.00 |
| 650-999.9 | 650-999.9 | $d_1+28.0$ | 9.50 | 0.45 | 0.30 | 2.50 | 8.40 |

3. Application and properties

Suitable for sealing with rotating or swinging rods, shafts, pins, rotary joints, etc. It is a rotary sealing ring that can withstand both sides pressure or alternating pressure role of the bidirectional effect, used in construction machinery, building machinery and automotive equipment. It can be applied on occasions where piston rod and piston seal are required, low friction, non viscous phenomenon, simple groove, good abrasion resistance and dimensional stability.



GRS

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3 - 1600mm | 0 - 30MPa | -30°C +200°C | 1 m/s | hydraulic oil, flame retardant liquid, water and others |

6. Installation Dimensions

| Rod Dia. | Groove Dia. | Groove Width | Order No. |
|----------|-------------------|---------------------|----------------|
| d h9 | D _N H9 | L ₁ +0.2 | |
| 6 | 10.9 | 2.2 | GRS6*10.9*2.2 |
| 8 | 12.9 | 2.2 | GRS8*12.9*2.2 |
| 10 | 14.9 | 2.2 | GRS10*14.9*2.2 |
| 12 | 16.9 | 2.2 | GRS12*16.9*2.2 |
| 14 | 18.9 | 2.2 | GRS14*18.9*2.2 |
| 15 | 19.9 | 2.2 | GRS15*19.9*2.2 |
| 16 | 20.9 | 2.2 | GRS16*20.9*2.2 |
| 18 | 22.9 | 2.2 | GRS18*22.9*2.2 |
| 20 | 27.5 | 3.2 | GRS20*27.5*3.2 |
| 22 | 29.5 | 3.2 | GRS22*29.5*3.2 |
| 25 | 32.5 | 3.2 | GRS25*32.5*3.2 |
| 26 | 33.5 | 3.2 | GRS26*33.5*3.2 |
| 28 | 35.5 | 3.2 | GRS28*35.5*3.2 |
| 30 | 37.5 | 3.2 | GRS30*37.5*3.2 |
| 32 | 39.5 | 3.2 | GRS32*39.5*3.2 |
| 35 | 42.5 | 3.2 | GRS35*42.5*3.2 |
| 36 | 43.5 | 3.2 | GRS36*43.5*3.2 |
| 40 | 51 | 4.2 | GRS40*51*4.2 |
| 42 | 53 | 4.2 | GRS42*53*4.2 |
| 44 | 55 | 4.2 | GRS44*55*4.2 |
| 45 | 56 | 4.2 | GRS45*56*4.2 |
| 48 | 59 | 4.2 | GRS48*59*4.2 |
| 50 | 61 | 4.2 | GRS50*61*4.2 |
| 52 | 63 | 4.2 | GRS52*63*4.2 |
| 55 | 66 | 4.2 | GRS55*66*4.2 |
| 56 | 67 | 4.2 | GRS56*67*4.2 |
| 60 | 71 | 4.2 | GRS60*71*4.2 |



GRS

| Rod Dia. | Groove Dia. | Groove Width | Order No. |
|----------|-------------------|---------------------|------------------|
| d h9 | D _N H9 | L ₁ +0.2 | |
| 63 | 74 | 4.2 | GRS63*74*4.2 |
| 65 | 76 | 4.2 | GRS65*76*4.2 |
| 70 | 81 | 4.2 | GRS70*81*4.2 |
| 75 | 86 | 4.2 | GRS75*86*4.2 |
| 80 | 91 | 4.2 | GRS80*91*4.2 |
| 85 | 96 | 4.2 | GRS85*96*4.2 |
| 90 | 101 | 4.2 | GRS90*101*4.2 |
| 95 | 106 | 4.2 | GRS95*106*4.2 |
| 100 | 111 | 4.2 | GRS100*111*4.2 |
| 105 | 116 | 4.2 | GRS105*116*4.2 |
| 110 | 121 | 4.2 | GRS110*121*4.2 |
| 115 | 126 | 4.2 | GRS115*126*4.2 |
| 120 | 131 | 4.2 | GRS120*131*4.2 |
| 125 | 136 | 4.2 | GRS125*136*4.2 |
| 130 | 141 | 4.2 | GRS130*141*4.2 |
| 135 | 146 | 4.2 | GRS135*146*4.2 |
| 140 | 151 | 4.2 | GRS140*151*4.2 |
| 145 | 156 | 4.2 | GRS145*156*4.2 |
| 150 | 161 | 4.2 | GRS150*161*4.2 |
| 155 | 166 | 4.2 | GRS155*166*4.2 |
| 160 | 171 | 4.2 | GRS160*171*4.2 |
| 170 | 181 | 4.2 | GRS170*181*4.2 |
| 180 | 191 | 4.2 | GRS180*191*4.2 |
| 190 | 201 | 4.2 | GRS190*201*4.2 |
| 200 | 215.5 | 6.3 | GRS200*215.5*6.3 |
| 210 | 225.5 | 6.3 | GRS210*225.5*6.3 |
| 220 | 235.5 | 6.3 | GRS220*235.5*6.3 |
| 240 | 255.5 | 6.3 | GRS240*255.5*6.3 |
| 250 | 265.5 | 6.3 | GRS250*265.5*6.3 |
| 280 | 301 | 8.1 | GRS280*301*8.1 |
| 300 | 321 | 8.1 | GRS300*321*8.1 |
| 320 | 341 | 8.1 | GRS320*341*8.1 |
| 350 | 371 | 8.1 | GRS350*371*8.1 |
| 360 | 381 | 8.1 | GRS360*381*8.1 |
| 400 | 421 | 8.1 | GRS400*421*8.1 |
| 420 | 441 | 8.1 | GRS420*441*8.1 |
| 450 | 471 | 8.1 | GRS450*471*8.1 |
| 480 | 501 | 8.1 | GRS480*501*8.1 |
| 500 | 521 | 8.1 | GRS500*521*8.1 |




GRS

| Rod Dia. | Groove Dia. | Groove Width | Order No. |
|----------|-------------------|---------------------|----------------|
| d h9 | D _N H9 | L ₁ +0.2 | |
| 520 | 541 | 8.1 | GRS520*541*8.1 |
| 530 | 551 | 8.1 | GRS530*551*8.1 |
| 550 | 571 | 8.1 | GRS550*571*8.1 |
| 600 | 621 | 8.1 | GRS600*621*8.1 |
| 650 | 678 | 9.5 | GRS650*678*9.5 |
| 700 | 728 | 9.5 | GRS700*728*9.5 |



1. Installation Recommendation



2. Installation Sizes

| Rod Diameter | Groove Diameter | Seal Width | Groove Width | Guide Clearance S max | |
|--------------|-----------------|------------|--------------|-----------------------|-----------|
| d e8 | D H9 | H | L | 0-10MPa | 15-36MPa |
| 50-79 | d+10.0 | 4.5 | 5.0 | 0.40-0.30 | 0.30-0.25 |
| 80-109 | d+13.8 | 7.0 | 7.5 | 0.45-0.35 | 0.35-0.30 |
| 110-299 | d+20.0 | 9.5 | 10.0 | 0.55-0.45 | 0.45-0.35 |
| 300-600 | d+24.0 | 12.5 | 13.0 | 0.60-0.55 | 0.55-0.45 |

3. Application and properties

Applicable to construction machinery, building machinery and automotive equipment and other industrial fields. Consisting of a sealing ring, a O-Ring and two retaining rings, the sealing surface profile is specially designed to accommodate high pressure and low speed, the design of the back of the seal ring increases the contact surface and prevents rotation with the rod or shaft. Low friction, non viscous phenomenon, simple groove, good abrasion resistance and dimensional stability.

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR

Back-up ring: POM / PA



O I

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|---------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3 - 1600mm | 0 - 36MPa | -36°C +100°C | 0.5 m/s | hydraulic oil, flame retardant liquid, water and others |

6. Installation Dimensions


| d e8 | D H9 | H | L | e | Order No. |
|------|-------|------|-----|----|----------------|
| 50 | 60 | 4.5 | 5 | 7 | OI50*60*4.5 |
| 56 | 66 | 4.5 | 5 | 7 | OI56*66*4.5 |
| 63 | 73 | 4.5 | 5 | 7 | OI63*73*4.5 |
| 65 | 75 | 4.5 | 5 | 7 | OI65*75*4.5 |
| 70 | 80 | 4.5 | 5 | 7 | OI70*80*4.5 |
| 75 | 85 | 4.5 | 5 | 7 | OI75*85*4.5 |
| 80 | 93.8 | 7.0 | 7.5 | 7 | OI80*93.8*7 |
| 85 | 98.8 | 7.0 | 7.5 | 7 | OI85*98.8*7 |
| 90 | 103.8 | 7.0 | 7.5 | 7 | OI90*103.8*7 |
| 95 | 108.8 | 7.0 | 7.5 | 7 | OI95*108.8*7 |
| 100 | 113.8 | 7.0 | 7.5 | 7 | OI100*113.8*7 |
| 110 | 130 | 9.5 | 10 | 10 | OI110*130*9.5 |
| 115 | 135 | 9.5 | 10 | 10 | OI115*135*9.5 |
| 120 | 140 | 9.5 | 10 | 10 | OI120*140*9.5 |
| 125 | 140 | 9.5 | 10 | 10 | OI125*140*9.5 |
| 130 | 150 | 9.5 | 10 | 10 | OI130*150*9.5 |
| 140 | 160 | 9.5 | 10 | 10 | OI140*160*9.5 |
| 150 | 170 | 9.5 | 10 | 10 | OI150*170*9.5 |
| 160 | 180 | 9.5 | 10 | 10 | OI160*180*9.5 |
| 170 | 190 | 9.5 | 10 | 10 | OI170*190*9.5 |
| 180 | 200 | 9.5 | 10 | 10 | OI180*200*9.5 |
| 190 | 210 | 9.5 | 10 | 10 | OI190*210*9.5 |
| 200 | 220 | 9.5 | 10 | 10 | OI200*220*9.5 |
| 220 | 240 | 9.5 | 10 | 10 | OI220*240*9.5 |
| 225 | 245 | 9.5 | 10 | 10 | OI225*245*9.5 |
| 230 | 250 | 9.5 | 10 | 10 | OI230*250*9.5 |
| 250 | 270 | 9.5 | 10 | 10 | OI250*270*9.5 |
| 280 | 300 | 9.5 | 10 | 10 | OI280*300*9.5 |
| 290 | 310 | 9.5 | 10 | 10 | OI290*310*9.5 |
| 300 | 324 | 12.5 | 13 | 15 | OI300*324*12.5 |
| 320 | 344 | 12.5 | 13 | 15 | OI320*344*12.5 |
| 350 | 374 | 12.5 | 13 | 15 | OI350*374*12.5 |
| 360 | 384 | 12.5 | 13 | 15 | OI360*384*12.5 |



O I

| d e8 | D H9 | H | L | e | Order No. |
|------|------|------|----|----|----------------|
| 380 | 404 | 12.5 | 13 | 15 | OI380*404*12.5 |
| 400 | 424 | 12.5 | 13 | 15 | OI400*424*12.5 |
| 420 | 444 | 12.5 | 13 | 15 | OI420*444*12.5 |
| 450 | 474 | 12.5 | 13 | 15 | OI450*474*12.5 |
| 480 | 504 | 12.5 | 13 | 15 | OI480*504*12.5 |
| 500 | 524 | 12.5 | 13 | 15 | OI500*524*12.5 |
| 550 | 574 | 12.5 | 13 | 15 | OI550*574*12.5 |
| 560 | 584 | 12.5 | 13 | 15 | OI560*584*12.5 |
| 600 | 624 | 12.5 | 13 | 15 | OI600*624*12.5 |

1. Installation Recommendation



2. Installation Sizes

| Bore Diameter | Groove Diameter | Seal Width | Groove Width | Guide Clearance S max | |
|---------------|-----------------|------------|--------------|-----------------------|-----------|
| D H9 | d e8 | H | L+0.2 | 0-10MPa | 15-36MPa |
| 50-124 | D-16 | 7.5 | 8 | 0.45-0.35 | 0.35-0.30 |
| 125-199 | D-20 | 9.5 | 10 | 0.55-0.45 | 0.45-0.35 |
| 200-600 | D-26 | 12.5 | 13 | 0.60-0.55 | 0.55-0.45 |

3. Application and properties

Applicable to construction machinery, building machinery and automotive equipment and other industrial fields. Consisting of a sealing ring, a O-ring and two retaining rings, the sealing surface profile is specially designed to accommodate high pressure and low speed, the design of the back of the seal ring increases the contact surface and prevents rotation with the rod or shaft. Low friction, non viscous phenomenon, simple groove, good abrasion resistance and dimensional stability.

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

Back-up ring: POM / PA



O A

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|---------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3 - 1600mm | 0 - 36MPa | -36°C +100°C | 0.5 m/s | hydraulic oil, flame retardant liquid, water and others |

6. Installation Dimensions

| d e8 | D H9 | H | L | e | Order No. |
|------|------|------|----|----|----------------|
| 50 | 34 | 7.5 | 8 | 7 | OA50*34*7.5 |
| 56 | 40 | 7.5 | 8 | 7 | OA56*40*7.5 |
| 63 | 47 | 7.5 | 8 | 7 | OA63*47*7.5 |
| 70 | 54 | 7.5 | 8 | 7 | OA70*54*7.5 |
| 80 | 64 | 7.5 | 8 | 7 | OA80*64*7.5 |
| 90 | 74 | 7.5 | 8 | 7 | OA90*74*7.5 |
| 95 | 79 | 7.5 | 8 | 7 | OA95*79*7.5 |
| 100 | 84 | 7.5 | 8 | 10 | OA100*84*7.5 |
| 110 | 94 | 7.5 | 8 | 10 | OA110*94*7.5 |
| 115 | 99 | 7.5 | 8 | 10 | OA115*99*7.5 |
| 120 | 104 | 7.5 | 8 | 10 | OA120*104*7.5 |
| 125 | 105 | 9.5 | 10 | 10 | OA125*105*9.5 |
| 130 | 110 | 9.5 | 10 | 10 | OA130*110*9.5 |
| 140 | 120 | 9.5 | 10 | 10 | OA140*120*9.5 |
| 150 | 130 | 9.5 | 10 | 10 | OA150*130*9.5 |
| 160 | 140 | 9.5 | 10 | 10 | OA160*140*9.5 |
| 180 | 160 | 9.5 | 10 | 10 | OA180*160*9.5 |
| 190 | 170 | 9.5 | 10 | 10 | OA190*170*9.5 |
| 200 | 174 | 12.5 | 10 | 12 | OA200*174*12.5 |
| 220 | 194 | 12.5 | 10 | 12 | OA220*194*12.5 |
| 225 | 199 | 12.5 | 10 | 12 | OA225*199*12.5 |
| 250 | 224 | 12.5 | 10 | 12 | OA250*224*12.5 |
| 280 | 254 | 12.5 | 10 | 12 | OA280*254*12.5 |
| 290 | 264 | 12.5 | 10 | 12 | OA290*264*12.5 |
| 300 | 274 | 12.5 | 10 | 12 | OA250*224*12.5 |
| 320 | 294 | 12.5 | 10 | 15 | OA280*254*12.5 |
| 350 | 324 | 12.5 | 13 | 15 | OA290*264*12.5 |
| 380 | 354 | 12.5 | 13 | 15 | OA380*354*12.5 |
| 400 | 374 | 12.5 | 13 | 15 | OA400*374*12.5 |
| 420 | 394 | 12.5 | 13 | 15 | OA420*394*12.5 |
| 450 | 424 | 12.5 | 13 | 15 | OA450*424*12.5 |
| 480 | 454 | 12.5 | 13 | 15 | OA480*454*12.5 |
| 500 | 474 | 12.5 | 13 | 15 | OA500*474*12.5 |




OA

| d e8 | D H9 | H | L | e | Order No. |
|------|------|------|----|----|----------------|
| 560 | 534 | 12.5 | 13 | 15 | OA560*534*12.5 |
| 580 | 554 | 12.5 | 13 | 15 | OA580*554*12.5 |
| 600 | 574 | 12.5 | 13 | 15 | OA600*574*12.5 |



1. Installation Recommendation



2. Installation Sizes

| Rod Diameter | Groove Diameter | Groove Width | Diameter | Step Width | O-Ring Cross-Section |
|----------------------|----------------------|--------------|--------------------|------------|----------------------|
| d _N f8/h9 | D H9 | L+0.2 | D ₃ H11 | a min | d ₂ |
| 19.0-39.9 | d _N +7.6 | 4.2 | d+1.5 | 3.0 | 2.62 |
| 40.0-69.9 | d _N +8.8 | 6.3 | d+1.5 | 3.0 | 2.62 |
| 70.0-139.9 | d _N +12.2 | 8.1 | d+2.0 | 4.0 | 3.53 |
| 140.0-399.9 | d _N +16.0 | 9.5 | d+2.5 | 5.0 | 5.33 |
| 400.0-649.9 | d _N +24.0 | 14.0 | d+2.5 | 8.0 | 7.00 |
| 650.0-999.9 | d _N +27.3 | 16.0 | d+2.5 | 10.0 | 8.40 |
| ≥1000.0 | d _N +27.3 | 16.0 | d+2.5 | 10.0 | 8.40 |

3. Application and properties

Suitable for cold and dusty environments and high frequency reciprocating motion. Mainly used in hydraulic and pneumatic devices, servo systems, chemical and food equipment. Excellent sliding performance, no stick-slip behavior, no viscosity, compensate for the distortion of the piston rod and plunger, compatibility with hydraulic media is very good, the remaining oil film adhered to the surface of the piston rod can be effectively blocked from the inside.



GSZ

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|--------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3 - 1600mm | - | -30°C +200°C | 15 m/s | hydraulic oil, flame retardant liquid, water and others |

6. Installation Dimensions

| Rod Dia. | Groove Dia. | Groove Width | a | Oder No. |
|----------|-------------|--------------|---|------------------|
| d f8 | D H9 | L | | |
| 20 | 27.6 | 4.2 | 3 | GSZ20*27.6*4.2 |
| 25 | 32.6 | 4.2 | 3 | GSZ25*32.6*4.2 |
| 28 | 35.6 | 4.2 | 3 | GSZ28*35.6*4.2 |
| 30 | 37.6 | 4.2 | 3 | GSZ30*37.6*4.2 |
| 32 | 39.6 | 4.2 | 3 | GSZ32*39.6*4.2 |
| 36 | 43.6 | 4.2 | 3 | GSZ36*43.6*4.2 |
| 40 | 48.8 | 6.3 | 3 | GSZ40*48.8*6.3 |
| 42 | 50.8 | 6.3 | 3 | GSZ42*50.8*6.3 |
| 45 | 53.8 | 6.3 | 3 | GSZ45*53.8*6.3 |
| 50 | 58.8 | 6.3 | 3 | GSZ50*58.8*6.3 |
| 55 | 63.8 | 6.3 | 3 | GSZ55*63.8*6.3 |
| 56 | 64.8 | 6.3 | 3 | GSZ56*64.8*6.3 |
| 60 | 68.8 | 6.3 | 3 | GSZ60*68.8*6.3 |
| 63 | 71.8 | 6.3 | 3 | GSZ63*71.8*6.3 |
| 65 | 73.8 | 6.3 | 3 | GSZ65*73.8*6.3 |
| 70 | 82.2 | 8.1 | 4 | GSZ70*82.2*8.1 |
| 75 | 87.2 | 8.1 | 4 | GSZ75*87.2*8.1 |
| 80 | 92.2 | 8.1 | 4 | GSZ80*92.2*8.1 |
| 85 | 97.2 | 8.1 | 4 | GSZ85*97.2*8.1 |
| 90 | 102.2 | 8.1 | 4 | GSZ90*102.2*8.1 |
| 95 | 107.2 | 8.1 | 4 | GSZ95*107.2*8.1 |
| 100 | 112.2 | 8.1 | 4 | GSZ100*112.2*8.1 |
| 105 | 117.2 | 8.1 | 4 | GSZ105*117.2*8.1 |
| 110 | 122.2 | 8.1 | 4 | GSZ110*122.2*8.1 |
| 115 | 127.2 | 8.1 | 4 | GSZ115*127.2*8.1 |
| 120 | 132.2 | 8.1 | 4 | GSZ120*132.2*8.1 |
| 125 | 137.2 | 8.1 | 4 | GSZ125*137.2*8.1 |



G S Z

| Rod Dia. | Groove Dia. | Groove Width | a | Order No. |
|----------|-------------|--------------|----|------------------|
| d f8 | D H9 | L | | |
| 130 | 142.2 | 8.1 | 4 | GSZ130*142.2*8.1 |
| 135 | 147.2 | 8.1 | 4 | GSZ135*147.2*8.1 |
| 140 | 156 | 9.5 | 5 | GSZ140*156*9.5 |
| 145 | 161 | 9.5 | 5 | GSZ145*161*9.5 |
| 150 | 166 | 9.5 | 5 | GSZ150*166*9.5 |
| 155 | 171 | 9.5 | 5 | GSZ155*171*9.5 |
| 160 | 176 | 9.5 | 5 | GSZ160*176*9.5 |
| 165 | 181 | 9.5 | 5 | GSZ165*181*9.5 |
| 170 | 186 | 9.5 | 5 | GSZ170*186*9.5 |
| 175 | 191 | 9.5 | 5 | GSZ175*191*9.5 |
| 180 | 196 | 9.5 | 5 | GSZ180*196*9.5 |
| 190 | 206 | 9.5 | 5 | GSZ190*206*9.5 |
| 200 | 216 | 9.5 | 5 | GSZ200*216*9.5 |
| 210 | 226 | 9.5 | 5 | GSZ210*226*9.5 |
| 220 | 236 | 9.5 | 5 | GSZ220*236*9.5 |
| 240 | 256 | 9.5 | 5 | GSZ240*256*9.5 |
| 250 | 266 | 9.5 | 5 | GSZ250*266*9.5 |
| 260 | 276 | 9.5 | 5 | GSZ260*276*9.5 |
| 270 | 286 | 9.5 | 5 | GSZ270*286*9.5 |
| 280 | 296 | 9.5 | 5 | GSZ280*296*9.5 |
| 300 | 316 | 9.5 | 5 | GSZ300*316*9.5 |
| 320 | 336 | 9.5 | 5 | GSZ320*336*9.5 |
| 330 | 346 | 9.5 | 5 | GSZ330*346*9.5 |
| 350 | 366 | 9.5 | 5 | GSZ350*366*9.5 |
| 360 | 376 | 9.5 | 5 | GSZ360*376*9.5 |
| 380 | 396 | 9.5 | 5 | GSZ380*396*9.5 |
| 400 | 424 | 14 | 8 | GSZ400*424*14 |
| 440 | 464 | 14 | 8 | GSZ440*464*14 |
| 450 | 474 | 14 | 8 | GSZ450*474*14 |
| 480 | 504 | 14 | 8 | GSZ480*504*14 |
| 500 | 524 | 14 | 8 | GSZ500*524*14 |
| 560 | 584 | 14 | 8 | GSZ560*584*14 |
| 600 | 624 | 14 | 8 | GSZ600*624*14 |
| 650 | 677.3 | 16 | 10 | GSZ650*677.3*16 |
| 680 | 707.3 | 16 | 10 | GSZ680*707.3*16 |
| 700 | 727.3 | 16 | 10 | GSZ700*727.3*16 |
| 770 | 797.3 | 16 | 10 | GSZ770*797.3*16 |
| 785 | 812.3 | 16 | 10 | GSZ785*812.3*16 |
| 800 | 827.3 | 16 | 10 | GSZ800*827.3*16 |






G S Z

| Rod Dia. | Groove Dia. | Groove Width | a | Order No. |
|----------|-------------|--------------|----|-------------------|
| d f8 | D H9 | L | | |
| 810 | 837.3 | 16 | 10 | GSZ810*837.3*16 |
| 900 | 927.3 | 16 | 10 | GSZ900*927.3*16 |
| 950 | 977.3 | 16 | 10 | GSZ950*977.3*16 |
| 1000 | 1027.3 | 16 | 10 | GSZ1000*1027.3*16 |



G S Z 2

1. Installation Recommendation



2. Installation Sizes

| Rod Diameter | Groove Diameter | Groove Width | Diameter | Step Width | O-Ring Cross-Section |
|---------------|-----------------|--------------|-----------|------------|----------------------|
| $d_N f8/h9$ | $D H9$ | $L +0.2$ | $D_3 H11$ | a min | d_2 |
| 4.0-11.9 | $d_N+4.8$ | 3.7 | $d+1.5$ | 2.0 | 1.78 |
| 12.0-64.9 | $d_N+6.8$ | 5 | $d+1.5$ | 2.0 | 2.62 |
| 65.0-250.9 | $d_N+8.8$ | 6 | $d+1.5$ | 3.0 | 3.53 |
| 251.0-420.9 | $d_N+12.2$ | 8.4 | $d+2.0$ | 4.0 | 5.33 |
| 421.0-650.9 | $d_N+16.0$ | 11 | $d+2.0$ | 4.0 | 7.00 |
| 651.0-999.9 | $d_N+20.0$ | 14 | $d+2.5$ | 5.0 | 8.40 |
| ≥ 1000.0 | $d_N+20.0$ | 14 | $d+2.5$ | 5.0 | 8.40 |

3. Application and properties

Suitable for cold and dusty environments and high frequency reciprocating motion. Mainly used in hydraulic and pneumatic devices, servo systems, chemical and food equipment. Excellent sliding performance, no stick-slip behavior, no viscosity, compensate for the distortion of the piston rod and plunger, compatibility with hydraulic media is very good, the remaining oil film adhered to the surface of the piston rod can be effectively blocked from the inside.



G S Z 2

4. Standard materials

Sealing ring: filled PTFE

O-Ring: NBR / FKM

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3 - 1600 | - | -30°C +200°C | 5 m/s | hydraulic oil, flame retardant liquid, water and others |

6. Installation Dimensions

| Rod Dia. | Groove Dia. | Groove Width | a | Oder No. |
|----------|-------------|--------------|---|------------------|
| d f8 | D H9 | L+0.2 | | |
| 6 | 10.8 | 3.7 | 2 | GSZ2-6*10.8*3.7 |
| 8 | 12.8 | 3.7 | 2 | GSZ2-8*12.8*3.7 |
| 10 | 14.8 | 3.7 | 2 | GSZ2-10*14.8*3.7 |
| 12 | 18.8 | 5 | 2 | GSZ2-12*18.8*5 |
| 14 | 20.8 | 5 | 2 | GSZ2-14*20.8*5 |
| 15 | 21.8 | 5 | 2 | GSZ2-15*21.8*5 |
| 16 | 22.8 | 5 | 2 | GSZ2-16*22.8*5 |
| 18 | 24.8 | 5 | 2 | GSZ2-18*24.8*5 |
| 20 | 26.8 | 5 | 2 | GSZ2-20*26.8*5 |
| 22 | 28.8 | 5 | 2 | GSZ2-22*28.8*5 |
| 25 | 31.8 | 5 | 2 | GSZ2-25*31.8*5 |
| 30 | 36.8 | 5 | 2 | GSZ2-30*36.8*5 |
| 32 | 38.8 | 5 | 2 | GSZ2-32*38.8*5 |
| 35 | 41.8 | 5 | 2 | GSZ2-35*41.8*5 |
| 36 | 42.8 | 5 | 2 | GSZ2-36*42.8*5 |
| 37 | 43.8 | 5 | 2 | GSZ2-37*43.8*5 |
| 40 | 46.8 | 5 | 2 | GSZ2-40*46.8*5 |
| 42 | 48.8 | 5 | 2 | GSZ2-42*48.8*5 |
| 45 | 51.8 | 5 | 2 | GSZ2-45*51.8*5 |
| 50 | 56.8 | 5 | 2 | GSZ2-50*56.8*5 |
| 55 | 61.8 | 5 | 2 | GSZ2-55*61.8*5 |
| 56 | 62.8 | 5 | 2 | GSZ2-56*62.8*5 |
| 60 | 66.8 | 5 | 2 | GSZ2-60*66.8*5 |
| 63 | 69.8 | 5 | 2 | GSZ2-63*69.8*5 |
| 65 | 73.8 | 6 | 3 | GSZ2-65*73.8*6 |
| 70 | 78.8 | 6 | 3 | GSZ2-70*78.8*6 |
| 75 | 83.8 | 6 | 3 | GSZ2-75*83.8*6 |



GSZ 2

| Rod Dia. | Groove Dia. | Groove Width | a | Oder No. |
|----------|-------------|--------------|---|--------------------|
| d f8 | D H9 | L+0.2 | | |
| 80 | 88.8 | 6 | 3 | GSZ2-80*88.8*6 |
| 85 | 93.8 | 6 | 3 | GSZ2-85*93.8*6 |
| 90 | 98.8 | 6 | 3 | GSZ2-90*98.8*6 |
| 95 | 103.8 | 6 | 3 | GSZ2-95*103.8*6 |
| 100 | 108.8 | 6 | 3 | GSZ2-100*108.8*6 |
| 105 | 113.8 | 6 | 3 | GSZ2-105*113.8*6 |
| 110 | 118.8 | 6 | 3 | GSZ2-110*118.8*6 |
| 115 | 123.8 | 6 | 3 | GSZ2-115*123.8*6 |
| 120 | 128.8 | 6 | 3 | GSZ2-120*128.8*6 |
| 125 | 133.8 | 6 | 3 | GSZ2-125*133.8*6 |
| 130 | 138.8 | 6 | 3 | GSZ2-130*138.8*6 |
| 135 | 143.8 | 6 | 3 | GSZ2-135*143.8*6 |
| 140 | 148.8 | 6 | 3 | GSZ2-140*148.8*6 |
| 145 | 153.8 | 6 | 3 | GSZ2-145*153.8*6 |
| 150 | 158.8 | 6 | 3 | GSZ2-150*158.8*6 |
| 160 | 168.8 | 6 | 3 | GSZ2-160*168.8*6 |
| 170 | 178.8 | 6 | 3 | GSZ2-170*178.8*6 |
| 180 | 188.8 | 6 | 3 | GSZ2-180*188.8*6 |
| 190 | 198.8 | 6 | 3 | GSZ2-190*198.8*6 |
| 200 | 208.8 | 6 | 3 | GSZ2-200*208.8*6 |
| 210 | 218.8 | 6 | 3 | GSZ2-210*218.8*6 |
| 220 | 228.8 | 6 | 3 | GSZ2-220*228.8*6 |
| 230 | 238.8 | 6 | 3 | GSZ2-230*238.8*6 |
| 240 | 248.8 | 6 | 3 | GSZ2-240*248.8*6 |
| 250 | 258.8 | 6 | 3 | GSZ2-250*258.8*6 |
| 260 | 272.2 | 8.4 | 4 | GSZ2-260*272.2*8.4 |
| 280 | 292.2 | 8.4 | 4 | GSZ2-280*292.2*8.4 |
| 300 | 312.2 | 8.4 | 4 | GSZ2-300*312.2*8.4 |
| 320 | 332.2 | 8.4 | 4 | GSZ2-320*332.2*8.4 |
| 350 | 362.2 | 8.4 | 4 | GSZ2-350*362.2*8.4 |
| 360 | 372.2 | 8.4 | 4 | GSZ2-360*372.2*8.4 |
| 370 | 382.2 | 8.4 | 4 | GSZ2-370*382.2*8.4 |
| 400 | 412.2 | 8.4 | 4 | GSZ2-400*412.2*8.4 |
| 440 | 456 | 11 | 4 | GSZ2-440*456*11 |
| 480 | 496 | 11 | 4 | GSZ2-480*496*11 |
| 600 | 616 | 11 | 4 | GSZ2-600*616*11 |
| 630 | 646 | 11 | 4 | GSZ2-630*646*11 |
| 680 | 700 | 14 | 5 | GSZ2-680*700*14 |
| 700 | 720 | 14 | 5 | GSZ2-700*720*14 |




G S Z 2

| Rod Dia. | Groove Dia. | Groove Width | a | Order No. |
|----------|-------------|--------------|---|-------------------|
| d f8 | D H9 | L+0.2 | | |
| 770 | 790 | 14 | 5 | GSZ2-770*790*14 |
| 820 | 840 | 14 | 5 | GSZ2-820*840*14 |
| 880 | 900 | 14 | 5 | GSZ2-880*900*14 |
| 900 | 920 | 14 | 5 | GSZ2-900*920*14 |
| 1030 | 1050 | 14 | 5 | GSZ2-1030*1050*14 |



D P T 1

1. Installation Recommendation



2. Installation Sizes

| Rod Diameter | Groove Diameter | Groove Width | Bore Diameter | Radius | Step Width |
|--------------|-----------------|--------------|---------------------|--------|------------|
| d f8/h9 | D H9 | L+0.2 | D ₁ ±0.1 | R | a |
| 20-39.9 | d+7.6 | 4.2 | d+1.0 | 0.4 | 3.0 |
| 40-69.9 | d+8.8 | 6.3 | d+1.5 | 1.0 | 3.0 |
| 70-139.9 | d+12.2 | 8.1 | d+2.0 | 1.2 | 4.0 |
| 140-399.9 | d+16.0 | 11.5 | d+2.0 | 2.0 | 5.0 |
| 400-649.9 | d+24.0 | 15.5 | d+2.5 | 2.5 | 8.0 |
| 650-999.9 | d+27.3 | 18.0 | d+2.5 | 2.5 | 10.0 |

3. Application and properties

For a wide range of applications, such as agricultural machinery, injection molding machines, forklifts, cranes and so on. Consisting of a sealing ring and two O-Rings for improving overall tightness, low friction, non stick slip phenomenon, good adjustment and positioning ability, high reliability, accepting the full load of work pressure in a short time.

4. Standard materials

Sealing ring: filled PTFE / PU

O-Ring: NBR / FKM



D P T 1

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3 - 1600mm | - | -30°C +200°C | 5 m/s | hydraulic oil, flame retardant liquid, water and others |

6. Installation Dimensions

| d f8 | D H9 | H | L+0.2 | Order No. |
|------|-------|-----|-------|-------------------|
| 20 | 27.6 | 4.0 | 4.2 | DPT1-20*27.6*4.2 |
| 25 | 32.6 | 4.0 | 4.2 | DPT1-25*32.6*4.2 |
| 28 | 35.6 | 4.0 | 4.2 | DPT1-28*35.6*4.2 |
| 30 | 37.6 | 4.0 | 4.2 | DPT1-30*37.6*4.2 |
| 32 | 39.6 | 4.0 | 4.2 | DPT1-32*39.6*4.2 |
| 35 | 42.6 | 4.0 | 4.2 | DPT1-35*42.6*4.2 |
| 36 | 43.6 | 4.0 | 4.2 | DPT1-36*43.6*4.2 |
| 40 | 48.8 | 6.0 | 6.3 | DPT1-40*48.8*6.3 |
| 42 | 50.8 | 6.0 | 6.3 | DPT1-42*50.8*6.3 |
| 45 | 53.8 | 6.0 | 6.3 | DPT1-45*53.8*6.3 |
| 50 | 58.8 | 6.0 | 6.3 | DPT1-50*58.8*6.3 |
| 55 | 63.8 | 6.0 | 6.3 | DPT1-55*63.8*6.3 |
| 56 | 64.8 | 6.0 | 6.3 | DPT1-56*64.8*6.3 |
| 60 | 68.8 | 6.0 | 6.3 | DPT1-60*68.8*6.3 |
| 63 | 71.8 | 6.0 | 6.3 | DPT1-63*71.8*6.3 |
| 65 | 73.8 | 6.0 | 6.3 | DPT1-65*73.8*6.3 |
| 70 | 82.2 | 7.7 | 8.1 | DPT1-70*82.2*8.1 |
| 75 | 87.2 | 7.7 | 8.1 | DPT1-75*87.2*8.1 |
| 80 | 92.2 | 7.7 | 8.1 | DPT1-80*92.2*8.1 |
| 85 | 97.2 | 7.7 | 8.1 | DPT1-85*97.2*8.1 |
| 90 | 102.2 | 7.7 | 8.1 | DPT1-90*102*8.1 |
| 95 | 107.2 | 7.7 | 8.1 | DPT1-95*107*8.1 |
| 100 | 112.2 | 7.7 | 8.1 | DPT1-100*112*8.1 |
| 105 | 117.2 | 7.7 | 8.1 | DPT1-105*117*8.1 |
| 110 | 122.2 | 7.7 | 8.1 | DPT1-110*122*8.1 |
| 115 | 127.2 | 7.7 | 8.1 | DPT1-115*127*8.1 |
| 120 | 132.2 | 7.7 | 8.1 | DPT1-120*132*8.1 |
| 125 | 137.2 | 7.7 | 8.1 | DPT1-125*137*8.1 |
| 130 | 142.2 | 7.7 | 8.1 | DPT1-130*142*8.1 |
| 135 | 147.2 | 7.7 | 8.1 | DPT1-135*147*8.1 |
| 140 | 156 | 11 | 11.5 | DPT1-140*156*11.5 |
| 145 | 161 | 11 | 11.5 | DPT1-145*161*11.5 |
| 150 | 166 | 11 | 11.5 | DPT1-150*166*11.5 |



D P T 1

| d f8 | D H9 | H | L+0.2 | Order No. |
|------|-------|------|-------|-------------------|
| 155 | 171 | 11 | 11.5 | DPT1-155*171*11.5 |
| 160 | 176 | 11 | 11.5 | DPT1-160*176*11.5 |
| 165 | 181 | 11 | 11.5 | DPT1-165*181*11.5 |
| 170 | 186 | 11 | 11.5 | DPT1-170*186*11.5 |
| 175 | 191 | 11 | 11.5 | DPT1-175*191*11.5 |
| 180 | 196 | 11 | 11.5 | DPT1-180*196*11.5 |
| 190 | 206 | 11 | 11.5 | DPT1-190*206*11.5 |
| 200 | 216 | 11 | 11.5 | DPT1-200*216*11.5 |
| 210 | 226 | 11 | 11.5 | DPT1-210*226*11.5 |
| 220 | 236 | 11 | 11.5 | DPT1-220*236*11.5 |
| 230 | 246 | 11 | 11.5 | DPT1-230*246*11.5 |
| 240 | 256 | 11 | 11.5 | DPT1-240*256*11.5 |
| 250 | 266 | 11 | 11.5 | DPT1-250*266*11.5 |
| 260 | 276 | 11 | 11.5 | DPT1-260*276*11.5 |
| 265 | 281 | 11 | 11.5 | DPT1-265*281*11.5 |
| 270 | 286 | 11 | 11.5 | DPT1-270*286*11.5 |
| 280 | 296 | 11 | 11.5 | DPT1-280*296*11.5 |
| 290 | 306 | 11 | 11.5 | DPT1-290*306*11.5 |
| 300 | 316 | 11 | 11.5 | DPT1-300*316*11.5 |
| 330 | 346 | 11 | 11.5 | DPT1-330*346*11.5 |
| 350 | 366 | 11 | 11.5 | DPT1-350*366*11.5 |
| 370 | 386 | 11 | 11.5 | DPT1-370*386*11.5 |
| 380 | 396 | 11 | 11.5 | DPT1-380*396*11.5 |
| 400 | 424 | 14.8 | 15.5 | DPT1-400*416*11.5 |
| 420 | 444 | 14.8 | 15.5 | DPT1-420*444*15.5 |
| 450 | 474 | 14.8 | 15.5 | DPT1-450*474*15.5 |
| 470 | 494 | 14.8 | 15.5 | DPT1-470*494*15.5 |
| 480 | 504 | 14.8 | 15.5 | DPT1-480*504*15.5 |
| 500 | 524 | 14.8 | 15.5 | DPT1-500*524*15.5 |
| 520 | 544 | 14.8 | 15.5 | DPT1-520*544*15.5 |
| 550 | 574 | 14.8 | 15.5 | DPT1-550*574*15.5 |
| 585 | 609 | 14.8 | 15.5 | DPT1-585*609*15.5 |
| 600 | 624 | 14.8 | 15.5 | DPT1-600*624*15.5 |
| 620 | 644 | 14.8 | 15.5 | DPT1-620*644*15.5 |
| 635 | 659 | 14.8 | 15.5 | DPT1-635*659*15.5 |
| 675 | 702.3 | 17.2 | 18 | DPT1-675*702*18 |
| 690 | 717.3 | 17.2 | 18 | DPT1-690*717*18 |
| 700 | 727.3 | 17.2 | 18 | DPT1-700*727*18 |
| 710 | 737.3 | 17.2 | 18 | DPT1-710*737*18 |




DPT1

| d f8 | D H9 | H | L+0.2 | Order No. |
|------|-------|------|-------|-----------------|
| 750 | 777.3 | 17.2 | 18 | DPT1-750*777*18 |
| 780 | 807.3 | 17.2 | 18 | DPT1-780*807*18 |
| 800 | 827.3 | 17.2 | 18 | DPT1-800*827*18 |
| 810 | 837.3 | 17.2 | 18 | DPT1-810*837*18 |
| 820 | 847.3 | 17.2 | 18 | DPT1-820*847*18 |
| 830 | 857.3 | 17.2 | 18 | DPT1-830*857*18 |
| 850 | 877.3 | 17.2 | 18 | DPT1-850*877*18 |
| 870 | 897.3 | 17.2 | 18 | DPT1-870*897*18 |
| 880 | 907.3 | 17.2 | 18 | DPT1-880*907*18 |
| 890 | 917.3 | 17.2 | 18 | DPT1-890*917*18 |
| 900 | 927.3 | 17.2 | 18 | DPT1-900*927*18 |
| 910 | 937.3 | 17.2 | 18 | DPT1-910*937*18 |



D P T 2

1. Installation Recommendation



2. Installation Sizes

| Rod Diameter d f8/h9 | Groove Diameter | Groove Width | Step Diameter | Radius | Step Width | |
|-------------------------|----------------------|--------------|---------------------|---------------------|------------|-----|
| Standard Application | Suitable Application | D H9 | L ₁ +0.2 | D ₁ ±0.1 | R | a |
| 140.0-229.9 | 100.0-450.0 | d+22.2 | 6.3 | d+10.7 | 1.2 | 4.2 |
| 230.0-299.9 | 220.0-450.0 | d+24.2 | 6.3 | d+10.7 | 1.2 | 4.2 |
| 300.0-629.9 | 250.0-650.0 | d+33.0 | 8.1 | d+15.1 | 1.2 | 6.3 |
| 630.0-999.9 | 550.0-999.9 | d+36.5 | 9.5 | d+15.1 | 2.0 | 6.3 |

3. Application and properties

Applicable to agricultural hydraulic press, injection molding machine, metallurgical equipment, etc. Consisting of a sealing ring and two O-Rings as preload element, good dust scraping effect, low friction, no stick slip phenomenon, good ability of adjustment and positioning, especially for large diameter piston rods.

4. Standard materials

Sealing ring: filled PTFE / PU

O-Ring: NBR / FKM



D P T 2

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3 - 1600mm | - | -30°C +200°C | 5 m/s | hydraulic oil, flame retardant liquid, water and others |

6. Installation Dimensions

| d f8 | D H9 | H | L ₁ +0.2 | L ₁ | Order No. |
|------|-------|------|---------------------|----------------|--------------------|
| 100 | 122.2 | 13.5 | 6.3 | 4.2 | DPT2-100*122.2*6.3 |
| 110 | 132.2 | 13.5 | 6.3 | 4.2 | DPT2-110*132.2*6.3 |
| 120 | 142.2 | 13.5 | 6.3 | 4.2 | DPT2-120*142.2*6.3 |
| 130 | 152.2 | 13.5 | 6.3 | 4.2 | DPT2-130*152.2*6.3 |
| 140 | 162.2 | 13.5 | 6.3 | 4.2 | DPT2-140*162.2*6.3 |
| 150 | 172.2 | 13.5 | 6.3 | 4.2 | DPT2-150*172.2*6.3 |
| 160 | 182.2 | 13.5 | 6.3 | 4.2 | DPT2-160*182.2*6.3 |
| 170 | 192.2 | 13.5 | 6.3 | 4.2 | DPT2-170*192.2*6.3 |
| 180 | 202.2 | 13.5 | 6.3 | 4.2 | DPT2-180*202.2*6.3 |
| 190 | 212.2 | 13.5 | 6.3 | 4.2 | DPT2-190*212.2*6.3 |
| 200 | 222.2 | 13.5 | 6.3 | 4.2 | DPT2-200*222.2*6.3 |
| 210 | 232.2 | 13.5 | 6.3 | 4.2 | DPT2-210*232.2*6.3 |
| 220 | 242.2 | 13.5 | 6.3 | 4.2 | DPT2-220*242.2*6.3 |
| 230 | 252.2 | 13.5 | 6.3 | 4.2 | DPT2-230*252.2*6.3 |
| 240 | 262.2 | 13.5 | 6.3 | 4.2 | DPT2-240*262.2*6.3 |
| 250 | 272.2 | 13.5 | 6.3 | 4.2 | DPT2-250*272.2*6.3 |
| 260 | 282.2 | 13.5 | 6.3 | 4.2 | DPT2-260*282.2*6.3 |
| 270 | 292.2 | 13.5 | 6.3 | 4.2 | DPT2-270*292.2*6.3 |
| 275 | 297.2 | 13.5 | 6.3 | 4.2 | DPT2-275*297.2*6.3 |
| 280 | 302.2 | 13.5 | 6.3 | 4.2 | DPT2-280*302.2*6.3 |
| 290 | 312.2 | 13.5 | 6.3 | 4.2 | DPT2-290*312.2*6.3 |
| 295 | 317.2 | 13.5 | 6.3 | 4.2 | DPT2-295*317.2*6.3 |
| 300 | 333 | 18.4 | 8.1 | 6.3 | DPT2-300*333*8.1 |
| 320 | 353 | 18.4 | 8.1 | 6.3 | DPT2-320*353*8.1 |
| 340 | 373 | 18.4 | 8.1 | 6.3 | DPT2-340*373*8.1 |
| 350 | 383 | 18.4 | 8.1 | 6.3 | DPT2-350*383*8.1 |
| 360 | 393 | 18.4 | 8.1 | 6.3 | DPT2-360*393*8.1 |
| 370 | 403 | 18.4 | 8.1 | 6.3 | DPT2-370*403*8.1 |
| 380 | 413 | 18.4 | 8.1 | 6.3 | DPT2-380*413*8.1 |
| 385 | 418 | 18.4 | 8.1 | 6.3 | DPT2-385*418*8.1 |
| 390 | 423 | 18.4 | 8.1 | 6.3 | DPT2-390*423*8.1 |
| 400 | 433 | 18.4 | 8.1 | 6.3 | DPT2-400*433*8.1 |
| 410 | 443 | 18.4 | 8.1 | 6.3 | DPT2-410*443*8.1 |




D P T 2

| d f8 | D H9 | H | L ₁ +0.2 | L ₁ | Order No. |
|------|--------|------|---------------------|----------------|----------------------|
| 420 | 453 | 18.4 | 8.1 | 6.3 | DPT2-420*453*8.1 |
| 430 | 463 | 18.4 | 8.1 | 6.3 | DPT2-430*463*8.1 |
| 440 | 473 | 18.4 | 8.1 | 6.3 | DPT2-440*473*8.1 |
| 450 | 483 | 18.4 | 8.1 | 6.3 | DPT2-450*483*8.1 |
| 470 | 503 | 18.4 | 8.1 | 6.3 | DPT2-470*503*8.1 |
| 480 | 513 | 18.4 | 8.1 | 6.3 | DPT2-480*513*8.1 |
| 500 | 533 | 18.4 | 8.1 | 6.3 | DPT2-500*533*8.1 |
| 510 | 543 | 18.4 | 8.1 | 6.3 | DPT2-510*543*8.1 |
| 550 | 583 | 18.4 | 8.1 | 6.3 | DPT2-550*583*8.1 |
| 560 | 593 | 18.4 | 8.1 | 6.3 | DPT2-560*593*8.1 |
| 600 | 633 | 18.4 | 8.1 | 6.3 | DPT2-600*633*8.1 |
| 630 | 666.5 | 19.8 | 9.5 | 6.3 | DPT2-630*666.5*9.5 |
| 640 | 676.5 | 19.8 | 9.5 | 6.3 | DPT2-640*676.5*9.5 |
| 660 | 696.5 | 19.8 | 9.5 | 6.3 | DPT2-660*696.5*9.5 |
| 670 | 706.5 | 19.8 | 9.5 | 6.3 | DPT2-670*706.5*9.5 |
| 700 | 736.5 | 19.8 | 9.5 | 6.3 | DPT2-700*736.5*9.5 |
| 740 | 776.5 | 19.8 | 9.5 | 6.3 | DPT2-740*776.5*9.5 |
| 750 | 786.5 | 19.8 | 9.5 | 6.3 | DPT2-750*786.5*9.5 |
| 795 | 831.5 | 19.8 | 9.5 | 4.2 | DPT2-795*831.5*9.5 |
| 800 | 836.5 | 19.8 | 9.5 | 4.2 | DPT2-800*836.5*9.5 |
| 820 | 856.5 | 19.8 | 9.5 | 4.2 | DPT2-820*856.5*9.5 |
| 830 | 866.5 | 19.8 | 9.5 | 4.2 | DPT2-830*866.5*9.5 |
| 850 | 886.5 | 19.8 | 9.5 | 6.3 | DPT2-850*886.5*9.5 |
| 890 | 926.5 | 19.8 | 9.5 | 6.3 | DPT2-890*926.5*9.5 |
| 950 | 986.5 | 19.8 | 9.5 | 6.3 | DPT2-950*986.5*9.5 |
| 970 | 1006.5 | 19.8 | 9.5 | 6.3 | DPT2-970*1006.5*9.5 |
| 1130 | 1166.5 | 19.8 | 9.5 | 6.3 | DPT2-1130*1166.5*9.5 |
| 1150 | 1186.5 | 19.8 | 9.5 | 6.3 | DPT2-1150*1186.5*9.5 |
| 1160 | 1196.5 | 19.8 | 9.5 | 6.3 | DPT2-1160*1196.5*9.5 |
| 1320 | 1356.5 | 19.8 | 9.5 | 6.3 | DPT2-1320*1356.5*9.5 |



K Z T

1. Installation Recommendation



2. Application and properties

Dust rings are used in conjunction with piston seals and wear rings, it could prevent the impurities to damage the sealing elements in the cylinder, to ensure the longer life of the sealing element. When used in conjunction with piston rod seals and metal bushings, it could protect the damage for the piston rods. There is an incision and an oil pressure bypass slot to prevent the accumulation of oil pressure.

3. Standard materials

Sealing ring: filled PTFE

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|---------|---|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3 - 1600mm | - | -55°C +225°C | 1.5 m/s | general hydraulic oil, water glycol hydraulic oil, oil / water emulsion type hydraulic oil. |



K Z T

5. Installation Dimensions

| Bore Dia. | Groove Dia. | Groove Width | Order No. |
|-----------|-------------|--------------|----------------|
| D | d | H | |
| 70 | 62 | 4 | KZT70*62*4 |
| 75 | 67 | 4 | KZT75*67*4 |
| 80 | 72 | 4 | KZT80*72*4 |
| 85 | 77 | 4 | KZT85*77*4 |
| 90 | 82 | 4 | KZT90*82*4 |
| 80 | 72 | 6 | KZT80*72*6 |
| 85 | 77 | 6 | KZT85*77*6 |
| 90 | 82 | 6 | KZT90*82*6 |
| 95 | 87 | 6 | KZT95*87*6 |
| 100 | 92 | 6 | KZT100*92*6 |
| 105 | 97 | 6 | KZT105*97*6 |
| 110 | 102 | 6 | KZT110*102*6 |
| 115 | 107 | 6 | KZT115*107*6 |
| 120 | 112 | 6 | KZT120*112*6 |
| 125 | 117 | 6 | KZT125*117*6 |
| 130 | 122 | 6 | KZT130*122*6 |
| 135 | 127 | 6 | KZT135*127*6 |
| 140 | 132 | 6 | KZT140*132*6 |
| 145 | 137 | 6 | KZT145*137*6 |
| 150 | 142 | 6 | KZT150*142*6 |
| 160 | 152 | 6 | KZT160*152*6 |
| 170 | 162 | 6 | KZT170*162*6 |
| 180 | 172 | 6 | KZT180*172*6 |
| 190 | 182 | 6 | KZT190*182*6 |
| 100 | 92 | 7.9 | KZT100*92*7.9 |
| 105 | 97 | 7.9 | KZT105*97*7.9 |
| 110 | 102 | 7.9 | KZT110*102*7.9 |
| 115 | 107 | 7.9 | KZT115*107*7.9 |
| 120 | 112 | 7.9 | KZT120*112*7.9 |
| 125 | 117 | 7.9 | KZT125*117*7.9 |
| 130 | 122 | 7.9 | KZT130*122*7.9 |
| 135 | 127 | 7.9 | KZT135*127*7.9 |
| 140 | 132 | 7.9 | KZT140*132*7.9 |
| 145 | 137 | 7.9 | KZT145*137*7.9 |
| 150 | 142 | 7.9 | KZT150*142*7.9 |
| 160 | 152 | 7.9 | KZT160*152*7.9 |
| 170 | 162 | 7.9 | KZT170*162*7.9 |
| 180 | 172 | 7.9 | KZT180*172*7.9 |
| 190 | 182 | 7.9 | KZT190*182*7.9 |






K Z T

| Bore Dia. | Groove Dia. | Groove Width | Order No. |
|-----------|-------------|--------------|-----------------|
| D | d | H | |
| 200 | 192 | 7.9 | KZT200*192*7.9 |
| 100 | 92 | 9.5 | KZT100*92*9.5 |
| 105 | 97 | 9.5 | KZT105*97*9.5 |
| 110 | 102 | 9.5 | KZT110*102*9.5 |
| 115 | 107 | 9.5 | KZT115*107*9.5 |
| 120 | 112 | 9.5 | KZT120*112*9.5 |
| 125 | 117 | 9.5 | KZT125*117*9.5 |
| 130 | 122 | 9.5 | KZT130*122*9.5 |
| 135 | 127 | 9.5 | KZT135*127*9.5 |
| 140 | 132 | 9.5 | KZT140*132*9.5 |
| 145 | 137 | 9.5 | KZT145*137*9.5 |
| 150 | 142 | 9.5 | KZT150*142*9.5 |
| 160 | 152 | 9.5 | KZT160*152*9.5 |
| 170 | 162 | 9.5 | KZT170*162*9.5 |
| 180 | 172 | 9.5 | KZT180*172*9.5 |
| 190 | 182 | 9.5 | KZT190*182*9.5 |
| 200 | 192 | 9.5 | KZT200*192*9.5 |
| 90 | 82 | 14.8 | KZT90*82*14.8 |
| 95 | 87 | 14.8 | KZT95*87*14.8 |
| 100 | 92 | 14.8 | KZT100*92*14.8 |
| 105 | 97 | 14.8 | KZT105*97*14.8 |
| 110 | 102 | 14.8 | KZT110*102*14.8 |
| 115 | 107 | 14.8 | KZT115*107*14.8 |
| 120 | 112 | 14.8 | KZT120*112*14.8 |
| 125 | 117 | 14.8 | KZT125*117*14.8 |
| 130 | 122 | 14.8 | KZT130*122*14.8 |
| 135 | 127 | 14.8 | KZT135*127*14.8 |
| 140 | 132 | 14.8 | KZT140*132*14.8 |
| 145 | 137 | 14.8 | KZT145*137*14.8 |
| 150 | 142 | 14.8 | KZT150*142*14.8 |



1. Installation Recommendation



2. Application and properties

Applicable to the guiding of piston and piston rod of hydraulic cylinder and air cylinder, has the function of supporting and guiding. The guide strips with the thickness which equal to or greater than 2mm, double sided embossing could be provided, the embossing structure is conducive to the formation of lubrication micro-pit, improve micro lubrication, at the same time, it is helpful to embed tiny foreign objects and protect the sealing system.

3. Standard materials

Filled PTFE

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|--------|------------------------------------|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| Custom as Required | — | -55°C +225°C | 15 m/s | hydraulic oil, emulsion, and water |

Piston: $L = C \times (D - W) - k$ [mm] D = Piston Dia. [mm] W = Thickness [mm]

Rod: $L = C \times (d + W) - k$ [mm] d = Rod Dia. [mm] C = 3.14 k=0.8



G S T

5. Length of whole roll

| | | | | | | | | |
|----------------------------|----|-----|----|-----|----|----|----|---|
| Thickness | 1 | 1.5 | 2 | 2.5 | 3 | 4 | 5 | 6 |
| Length of whole roll (m) | 55 | 35 | 27 | 22 | 18 | 13 | 10 | 8 |

Above data only for reference, it shall follow the actual products.

Standard groove width

| | | | | | | | | | | | | | | | | | | |
|--------------------|-----|-----|---|-----|-----|---|-----|-----|-----|----|----|----|----|----|----|----|----|----|
| Groove width L2 | 2.5 | 3.2 | 4 | 4.2 | 5.6 | 6 | 6.3 | 8.1 | 9.7 | 10 | 12 | 15 | 18 | 20 | 25 | 30 | 40 | 50 |
|--------------------|-----|-----|---|-----|-----|---|-----|-----|-----|----|----|----|----|----|----|----|----|----|

The products of various width could be provided.


Standard thickness of product

| | | | | | | | | | |
|-------------|---|-----|------|---|-----|---|---|---|---|
| Thickness W | 1 | 1.5 | 1.55 | 2 | 2.5 | 3 | 4 | 5 | 6 |
|-------------|---|-----|------|---|-----|---|---|---|---|

The products of various thickness could be provided.



1. Installation Recommendation



2. Application and properties

Applicable to the guide sleeve of piston rod, can support and guide the piston rod. Excellent vibration reducing performance, installation is simple and secure. The metal and plastic material pairing can prevent the "stagnation" and "seizure" phenomenon.

3. Standard materials

Filled PTFE / PA / POM

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|--|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 20 - 1000mm | - | -55°C +225°C | 3 m/s | general hydraulic oil, emulsion, water |



DFI

5. Installation Dimensions

| d | D | D ₁ | H | c | a | Order No. |
|-----|-----|----------------|----|----|-----|---------------|
| 20 | 26 | 23 | 19 | 6 | 6.5 | DFI20*26*19 |
| 22 | 28 | 25 | 19 | 6 | 6.5 | DFI22*28*19 |
| 25 | 31 | 28 | 19 | 6 | 6.5 | DFI25*31*19 |
| 28 | 34 | 31 | 19 | 6 | 6.5 | DFI28*34*19 |
| 30 | 36 | 33 | 19 | 6 | 6.5 | DFI30*36*19 |
| 36 | 42 | 39 | 19 | 6 | 6.5 | DFI36*42*19 |
| 40 | 46 | 43 | 19 | 6 | 6.5 | DFI40*46*19 |
| 42 | 48 | 45 | 19 | 6 | 6.5 | DFI42*48*19 |
| 45 | 51 | 48 | 19 | 6 | 6.5 | DFI45*51*19 |
| 50 | 56 | 53 | 19 | 6 | 6.5 | DFI50*56*19 |
| 55 | 61 | 58 | 19 | 6 | 6.5 | DFI55*61*19 |
| 56 | 62 | 59 | 19 | 6 | 6.5 | DFI56*62*19 |
| 60 | 70 | 65 | 24 | 7 | 8.5 | DFI60*70*24 |
| 63 | 73 | 68 | 24 | 7 | 8.5 | DFI63*73*24 |
| 65 | 75 | 70 | 24 | 7 | 8.5 | DFI65*75*24 |
| 70 | 80 | 75 | 24 | 7 | 8.5 | DFI70*80*24 |
| 72 | 82 | 77 | 24 | 7 | 8.5 | DFI72*82*24 |
| 75 | 85 | 80 | 24 | 7 | 8.5 | DFI75*85*24 |
| 80 | 90 | 85 | 24 | 7 | 8.5 | DFI80*90*24 |
| 85 | 95 | 90 | 24 | 7 | 8.5 | DFI85*95*24 |
| 90 | 100 | 95 | 24 | 7 | 8.5 | DFI90*100*24 |
| 95 | 105 | 100 | 24 | 7 | 8.5 | DFI95*105*24 |
| 96 | 106 | 101 | 24 | 7 | 8.5 | DFI96*106*24 |
| 100 | 110 | 105 | 24 | 7 | 8.5 | DFI100*110*24 |
| 105 | 115 | 110 | 24 | 7 | 8.5 | DFI105*115*24 |
| 110 | 120 | 115 | 24 | 7 | 8.5 | DFI110*120*24 |
| 115 | 125 | 120 | 24 | 7 | 8.5 | DFI115*125*24 |
| 120 | 130 | 125 | 24 | 7 | 8.5 | DFI120*130*24 |
| 125 | 135 | 130 | 24 | 7 | 8.5 | DFI125*135*24 |
| 130 | 140 | 135 | 24 | 7 | 8.5 | DFI130*140*24 |
| 140 | 150 | 145 | 24 | 7 | 9.5 | DFI140*150*24 |
| 150 | 162 | 156 | 35 | 15 | 10 | DFI150*162*35 |
| 155 | 167 | 161 | 35 | 15 | 10 | DFI155*167*35 |
| 160 | 172 | 166 | 35 | 15 | 10 | DFI160*172*35 |
| 165 | 177 | 171 | 35 | 15 | 10 | DFI165*177*35 |
| 170 | 182 | 176 | 35 | 15 | 10 | DFI170*182*35 |
| 180 | 192 | 186 | 35 | 15 | 10 | DFI180*192*35 |
| 190 | 202 | 196 | 35 | 15 | 10 | DFI190*202*35 |
| 200 | 212 | 206 | 35 | 15 | 10 | DFI200*212*35 |




DFI

| d | D | D ₁ | H | c | a | Order No. |
|-----|-----|----------------|----|----|----|---------------|
| 220 | 232 | 226 | 35 | 15 | 10 | DFI220*232*35 |
| 225 | 237 | 231 | 35 | 15 | 10 | DFI225*237*35 |
| 240 | 252 | 246 | 35 | 15 | 10 | DFI240*252*35 |
| 250 | 262 | 256 | 35 | 15 | 10 | DFI250*262*35 |
| 280 | 292 | 286 | 35 | 15 | 10 | DFI280*292*35 |
| 300 | 312 | 306 | 35 | 15 | 10 | DFI300*312*35 |
| 350 | 362 | 356 | 35 | 15 | 10 | DFI350*362*35 |
| 400 | 412 | 406 | 35 | 15 | 10 | DFI400*412*35 |
| 450 | 462 | 456 | 35 | 15 | 10 | DFI450*462*35 |
| 500 | 512 | 506 | 35 | 15 | 10 | DFI500*512*35 |
| 600 | 612 | 606 | 35 | 15 | 10 | DFI600*612*35 |
| 630 | 642 | 636 | 35 | 15 | 10 | DFI630*642*35 |



DFA

1. Installation Recommendation



2. Application and properties

Applicable to the guide sleeve of piston rod, can support and guide the piston rod. Excellent vibration reducing performance, installation is simple and secure. The metal and plastic material pairing can prevent the "stagnation" and "seizure" phenomenon.

3. Standard materials

Filled PTFE / PA / POM

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|--|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 40 - 1000mm | - | -55°C +225°C | 3 m/s | general hydraulic oil, emulsion, water |



DFA

5. Installation Dimensions

| D | d | D ₁ | H | c | a | Order No. |
|-----|-----|----------------|------|-----|------|-----------------|
| 40 | 32 | 36 | 12 | 3.5 | 4.7 | DFA40*32*12 |
| 45 | 37 | 41 | 12 | 3 | 4.7 | DFA45*37*12 |
| 50 | 42 | 46 | 12 | 3 | 6.2 | DFA50*42*12 |
| 55 | 47 | 51 | 12 | 3 | 6.2 | DFA55*47*12 |
| 56 | 48 | 52 | 12 | 3 | 6.2 | DFA56*48*12 |
| 57 | 49 | 53 | 12 | 3 | 6.2 | DFA57*49*12 |
| 58 | 50 | 54 | 12 | 3 | 6.2 | DFA58*50*12 |
| 60 | 52 | 56 | 12 | 3 | 6.2 | DFA60*52*12 |
| 63 | 55 | 59 | 12 | 3 | 6.2 | DFA63*55*12 |
| 65 | 57 | 61 | 12 | 3 | 6.2 | DFA65*57*12 |
| 70 | 62 | 66 | 12 | 3 | 6.2 | DFA70*62*12 |
| 75 | 67 | 71 | 12 | 3 | 6.2 | DFA75*67*12 |
| 80 | 72 | 76 | 14 | 3 | 7.2 | DFA80*72*14 |
| 85 | 77 | 81 | 14 | 3 | 7.2 | DFA85*77*14 |
| 90 | 82 | 86 | 14 | 3 | 7.2 | DFA90*82*14 |
| 95 | 87 | 91 | 14 | 3 | 7.2 | DFA95*87*14 |
| 100 | 92 | 96 | 14 | 3 | 7.2 | DFA100*92*14 |
| 105 | 97 | 101 | 14 | 3 | 7.2 | DFA105*97*14 |
| 110 | 102 | 106 | 14 | 3 | 7.2 | DFA110*102*14 |
| 115 | 107 | 111 | 14 | 3 | 7.2 | DFA115*107*14 |
| 120 | 112 | 116 | 14 | 3 | 7.2 | DFA120*112*14 |
| 125 | 115 | 121 | 17.5 | 4 | 9.2 | DFA125*115*17.5 |
| 130 | 120 | 126 | 17.5 | 4 | 4.3 | DFA130*120*12.3 |
| 135 | 125 | 131 | 17.5 | 4 | 9.2 | DFA135*125*17.5 |
| 140 | 130 | 136 | 17.5 | 4 | 9.2 | DFA140*130*17.5 |
| 145 | 135 | 141 | 17.5 | 4 | 9.2 | DFA145*135*17.5 |
| 150 | 140 | 146 | 17.5 | 4 | 9.2 | DFA150*140*17.5 |
| 155 | 145 | 151 | 17.5 | 4 | 9.2 | DFA155*145*17.5 |
| 160 | 150 | 156 | 17.5 | 4 | 9.2 | DFA160*150*17.5 |
| 170 | 160 | 166 | 20 | 6 | 9.2 | DFA170*160*20 |
| 180 | 170 | 176 | 20 | 6 | 9.2 | DFA180*170*20 |
| 190 | 180 | 186 | 20 | 4.5 | 11.7 | DFA190*180*20 |
| 200 | 190 | 196 | 20 | 4.5 | 11.7 | DFA200*190*20 |
| 210 | 200 | 206 | 25 | 8 | 11.7 | DFA210*200*25 |
| 220 | 210 | 216 | 25 | 8 | 11.7 | DFA220*210*25 |
| 225 | 215 | 221 | 25 | 8 | 11.7 | DFA225*215*25 |
| 230 | 220 | 226 | 25 | 8 | 11.7 | DFA230*220*25 |
| 250 | 240 | 246 | 33 | 15 | 11.7 | DFA250*240*33 |
| 265 | 255 | 261 | 33 | 15 | 11.7 | DFA265*255*33 |




D F A

| d | D | D ₁ | H | c | a | Order No. |
|------|-----|----------------|----|-----|-------|----------------|
| 280 | 270 | 276 | 33 | 15 | 11.7 | DFA280*270*33 |
| 300 | 290 | 296 | 33 | 15 | 11.7 | DFA300*290*33 |
| 350 | 338 | 344 | 35 | 8.5 | 13.25 | DFA350*338*35 |
| 400 | 388 | 394 | 35 | 8.5 | 13.25 | DFA400*388*35 |
| 450 | 438 | 444 | 35 | 8.5 | 13.25 | DFA450*438*35 |
| 500 | 488 | 494 | 35 | 8.5 | 13.25 | DFA500*488*35 |
| 560 | 548 | 554 | 35 | 8.5 | 13.25 | DFA560*548*35 |
| 600 | 588 | 594 | 35 | 8.5 | 13.25 | DFA600*588*35 |
| 650 | 638 | 644 | 35 | 8.5 | 13.25 | DFA650*638*35 |
| 700 | 688 | 694 | 35 | 8.5 | 13.25 | DFA700*688*35 |
| 800 | 788 | 794 | 35 | 8.5 | 13.25 | DFA800*788*35 |
| 1000 | 988 | 994 | 35 | 8.5 | 13.25 | DFA1000*988*35 |



1. Installation Recommendation



2. Application and properties

Applicable to the guide sleeve of piston rod, can support and guide the piston rod. Excellent vibration reducing performance, installation is simple and secure. The metal and plastic material pairing can prevent the "stagnation" and "seizure" phenomenon.

3. Standard materials

Filled PTFE / PA / POM

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|--|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 28 - 1000mm | - | -55°C +225°C | 3 m/s | general hydraulic oil, emulsion, water |



D F A I

5. Installation Dimensions

| d | D | D ₁ | H | L | c | a | Order No. |
|-----|-----|----------------|----|----|----|-----|----------------|
| 28 | 34 | 31 | 19 | 17 | 6 | 6.5 | DFAI28*34*19 |
| 30 | 36 | 33 | 19 | 17 | 6 | 6.5 | DFAI30*36*19 |
| 36 | 42 | 39 | 19 | 17 | 6 | 6.5 | DFAI36*42*19 |
| 40 | 46 | 43 | 19 | 17 | 6 | 6.5 | DFAI40*46*19 |
| 42 | 48 | 45 | 19 | 17 | 6 | 6.5 | DFAI42*48*19 |
| 45 | 51 | 48 | 19 | 17 | 6 | 6.5 | DFAI45*51*19 |
| 50 | 56 | 53 | 19 | 17 | 6 | 6.5 | DFAI50*56*19 |
| 55 | 61 | 58 | 19 | 17 | 6 | 6.5 | DFAI55*61*19 |
| 56 | 62 | 59 | 19 | 17 | 6 | 6.5 | DFAI56*62*19 |
| 60 | 70 | 65 | 24 | 21 | 7 | 8.5 | DFAI60*70*24 |
| 63 | 73 | 68 | 24 | 21 | 7 | 8.5 | DFAI63*73*24 |
| 65 | 75 | 70 | 24 | 21 | 7 | 8.5 | DFAI65*75*24 |
| 70 | 80 | 75 | 24 | 21 | 7 | 8.5 | DFAI70*80*24 |
| 72 | 82 | 77 | 24 | 21 | 7 | 8.5 | DFAI72*82*24 |
| 75 | 85 | 80 | 24 | 21 | 7 | 8.5 | DFAI75*85*24 |
| 80 | 90 | 85 | 24 | 21 | 7 | 8.5 | DFAI80*90*24 |
| 85 | 95 | 90 | 24 | 21 | 7 | 8.5 | DFAI85*95*24 |
| 90 | 100 | 95 | 24 | 21 | 7 | 8.5 | DFAI90*100*24 |
| 95 | 105 | 100 | 24 | 21 | 7 | 8.5 | DFAI95*105*24 |
| 100 | 110 | 105 | 24 | 21 | 7 | 8.5 | DFAI100*110*24 |
| 105 | 115 | 110 | 24 | 21 | 7 | 8.5 | DFAI105*115*24 |
| 110 | 120 | 115 | 24 | 21 | 7 | 8.5 | DFAI110*120*24 |
| 115 | 125 | 120 | 24 | 21 | 7 | 8.5 | DFAI115*125*24 |
| 120 | 130 | 125 | 24 | 21 | 7 | 8.5 | DFAI120*130*24 |
| 125 | 135 | 130 | 24 | 21 | 7 | 8.5 | DFAI125*135*24 |
| 130 | 140 | 135 | 24 | 21 | 7 | 8.5 | DFAI130*140*24 |
| 140 | 150 | 145 | 24 | 21 | 7 | 8.5 | DFAI140*150*24 |
| 150 | 162 | 156 | 35 | 31 | 15 | 10 | DFAI150*162*35 |
| 160 | 172 | 166 | 35 | 31 | 15 | 10 | DFAI160*172*35 |
| 165 | 177 | 171 | 35 | 31 | 15 | 10 | DFAI165*177*35 |
| 170 | 182 | 176 | 35 | 31 | 15 | 10 | DFAI170*182*35 |
| 180 | 192 | 186 | 35 | 31 | 15 | 10 | DFAI180*192*35 |
| 190 | 202 | 196 | 35 | 31 | 15 | 10 | DFAI190*202*35 |
| 200 | 212 | 206 | 35 | 31 | 15 | 10 | DFAI200*212*35 |
| 220 | 232 | 226 | 35 | 31 | 15 | 10 | DFAI220*232*35 |
| 225 | 237 | 231 | 35 | 31 | 15 | 10 | DFAI225*237*35 |
| 240 | 252 | 246 | 35 | 31 | 15 | 10 | DFAI240*252*35 |
| 250 | 262 | 256 | 35 | 31 | 15 | 10 | DFAI250*262*35 |
| 260 | 272 | 266 | 35 | 31 | 15 | 10 | DFAI260*272*35 |




D F A I

| d | D | D ₁ | H | L | c | a | Order No. |
|-----|-----|----------------|----|----|----|----|----------------|
| 280 | 292 | 286 | 35 | 31 | 15 | 10 | DFAI280*292*35 |
| 290 | 302 | 296 | 35 | 31 | 15 | 10 | DFAI290*302*35 |
| 300 | 312 | 306 | 35 | 31 | 15 | 10 | DFAI300*312*35 |
| 320 | 332 | 326 | 35 | 31 | 15 | 10 | DFAI320*332*35 |
| 350 | 362 | 356 | 35 | 31 | 15 | 10 | DFAI350*362*35 |
| 360 | 372 | 366 | 35 | 31 | 15 | 10 | DFAI360*372*35 |
| 380 | 392 | 386 | 35 | 31 | 15 | 10 | DFAI380*392*35 |
| 400 | 412 | 406 | 35 | 31 | 15 | 10 | DFAI400*412*35 |
| 450 | 462 | 456 | 35 | 31 | 15 | 10 | DFAI450*462*35 |
| 500 | 512 | 506 | 35 | 31 | 15 | 10 | DFAI500*512*35 |
| 600 | 612 | 606 | 35 | 31 | 15 | 10 | DFAI600*612*35 |
| 630 | 642 | 636 | 35 | 31 | 15 | 10 | DFAI630*642*35 |

1. Installation Recommendation

| Standard Groove | | | | | Widen groove | | | | |
|-----------------|------|-----|------|------|----------------|------|-----|------|------|
| Type | Code | APS | 103A | 400A | Type | Code | APS | 103A | 400A |
| Rod and Piston | DEPA | | | | Rod and Piston | DEPB | | | |
| Rod | DRPA | | | | Rod | DRPB | | | |



2. Installation Sizes

| Rod Diameter | Groove Diameter | Groove Width | Radius | Step Height | Radial Clearance S max. | | | |
|--------------|-----------------|--------------|----------------|-------------|-------------------------|-------|-------|-------|
| | | | | | 2MPa | 10MPa | 20MPa | 40MPa |
| d h9 | D H9 | L+0.2 | r ₁ | h | 0.20 | 0.10 | 0.08 | 0.05 |
| 3.0-9.9 | C+2.9 | 2.4 | 0.4 | 0.4 | 0.20 | 0.10 | 0.08 | 0.05 |
| 10.0-19.9 | C+4.5 | 3.6 | 0.4 | 0.6 | 0.25 | 0.15 | 0.10 | 0.07 |
| 20.0-39.9 | C+6.2 | 4.8 | 0.6 | 0.7 | 0.35 | 0.20 | 0.15 | 0.08 |
| 40.0-119.9 | C+9.4 | 7.1 | 0.8 | 0.8 | 0.50 | 0.25 | 0.20 | 0.10 |
| 120.0-630.0 | C+12.2 | 9.5 | 0.8 | 0.8 | 0.60 | 0.30 | 0.25 | 0.12 |

3. Application and properties

Applicable to harsh conditions and some special media requirements, it is a recommended seal for applications that do not crawl, chemical resistant, and resistant to most media applications. Could be used for reciprocating and rotary motion, with small friction coefficient, wear resistance and dimensional stability.

4. Standard materials

Sealing ring: filled PTFE / PU

Spring: stainless steel



D R P / D E P

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|--------|-----------------------------------|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3-1000mm | 0—45MPa | -40°C +260°C | 15 m/s | all liquids, chemicals, and gases |

6. Installation Dimensions

| Rod Dia. | Groove Dia. | Groove Width | Order No. |
|----------|-------------|--------------|----------------|
| d h9 | D H9 | L +0.2 | |
| 3 | 5.9 | 2.4 | DRP3*5.9*2.4 |
| 4 | 6.9 | 2.4 | DRP4*6.9*2.4 |
| 5 | 7.9 | 2.4 | DRP5*7.9*2.4 |
| 6 | 8.9 | 2.4 | DRP6*8.9*2.4 |
| 8 | 10.9 | 2.4 | DRP8*10.9*2.4 |
| 10 | 14.5 | 3.6 | DRP10*14.5*3.6 |
| 12 | 16.5 | 3.6 | DRP12*16.5*3.6 |
| 14 | 18.5 | 3.6 | DRP14*18.5*3.6 |
| 15 | 19.5 | 3.6 | DRP15*19.5*3.6 |
| 16 | 20.5 | 3.6 | DRP16*20.5*3.6 |
| 18 | 22.5 | 3.6 | DRP18*22.5*3.6 |
| 20 | 26.2 | 4.8 | DRP20*26.2*4.8 |
| 22 | 28.2 | 4.8 | DRP22*28.2*4.8 |
| 25 | 31.2 | 4.8 | DRP25*31.2*4.8 |
| 28 | 34.2 | 4.8 | DRP28*34.2*4.8 |
| 30 | 36.2 | 4.8 | DRP30*36.2*4.8 |
| 32 | 38.2 | 7.1 | DRP32*38.2*7.1 |
| 35 | 41.2 | 7.1 | DRP35*41.2*7.1 |
| 36 | 42.2 | 7.1 | DRP36*42.2*7.1 |
| 40 | 49.4 | 7.1 | DRP40*49.4*7.1 |
| 42 | 51.4 | 7.1 | DRP42*51.4*7.1 |
| 45 | 54.4 | 7.1 | DRP45*54.4*7.1 |
| 48 | 57.4 | 7.1 | DRP48*57.4*7.1 |
| 50 | 59.4 | 7.1 | DRP50*59.4*7.1 |
| 52 | 61.4 | 7.1 | DRP52*61.4*7.1 |
| 55 | 64.4 | 7.1 | DRP55*64.4*7.1 |
| 56 | 65.4 | 7.1 | DRP56*65.4*7.1 |
| 60 | 69.4 | 7.1 | DRP60*69.4*7.1 |
| 63 | 72.4 | 7.1 | DRP63*72.4*7.1 |
| 65 | 74.4 | 7.1 | DRP65*74.4*7.1 |
| 70 | 79.4 | 7.1 | DRP70*79.4*7.1 |
| 75 | 84.4 | 7.1 | DRP75*84.4*7.1 |
| 80 | 89.4 | 7.1 | DRP80*89.4*7.1 |



DRP / DEP


| Rod Dia. | Groove Dia. | Groove Width | Order No. |
|----------|-------------|--------------|------------------|
| d h9 | D H9 | L +0.2 | |
| 85 | 94.4 | 7.1 | DRP85*94.4*7.1 |
| 90 | 99.4 | 7.1 | DRP90*99.4*7.1 |
| 95 | 104.4 | 7.1 | DRP95*104.4*7.1 |
| 100 | 109.4 | 7.1 | DRP100*109.4*7.1 |
| 105 | 114.4 | 7.1 | DRP105*114.4*7.1 |
| 110 | 119.4 | 7.1 | DRP110*119.4*7.1 |
| 115 | 124.4 | 7.1 | DRP115*124.4*7.1 |
| 120 | 132.4 | 7.1 | DRP120*132.4*7.1 |
| 125 | 137.2 | 9.5 | DRP125*137.2*9.5 |
| 130 | 142.2 | 9.5 | DRP130*142.2*9.5 |
| 135 | 147.2 | 9.5 | DRP135*147.2*9.5 |
| 140 | 152.2 | 9.5 | DRP140*152.2*9.5 |
| 150 | 162.2 | 9.5 | DRP150*162.2*9.5 |
| 160 | 172.2 | 9.5 | DRP160*172.2*9.5 |
| 170 | 182.2 | 9.5 | DRP170*182.2*9.5 |
| 180 | 192.2 | 9.5 | DRP180*192.2*9.5 |
| 190 | 202.2 | 9.5 | DRP190*202.2*9.5 |
| 200 | 212.2 | 9.5 | DRP200*212.2*9.5 |
| 210 | 222.2 | 9.5 | DRP210*222.2*9.5 |
| 220 | 232.2 | 9.5 | DRP220*232.2*9.5 |
| 230 | 242.2 | 9.5 | DRP230*242.2*9.5 |
| 240 | 252.2 | 9.5 | DRP240*252.2*9.5 |
| 250 | 262.2 | 9.5 | DRP250*262.2*9.5 |
| 280 | 292.2 | 9.5 | DRP280*292.2*9.5 |
| 300 | 312.2 | 9.5 | DRP300*312.2*9.5 |
| 350 | 362.2 | 9.5 | DRP350*362.2*9.5 |
| 400 | 412.2 | 9.5 | DRP400*412.2*9.5 |



D E G / D E P

1. Installation Recommendation

| Standard Groove | | | | | | Widen groove | | | | | |
|-----------------|------|-----|------|------|----------------|--------------|-----|------|------|--|--|
| Type | Code | APS | 103A | 400A | Type | Code | APS | 103A | 400A | | |
| Rod and Piston | DEPA | | | | Rod and Piston | DEPB | | | | | |
| Piston | DEGA | | | | Rod | DEGB | | | | | |



2. Installation Sizes

| Bore Diameter | Groove Diameter | Groove Width | Radius | Step Height | Radial Clearance S max. | | | |
|---------------|-----------------|---------------------|----------------|-------------|-------------------------|-------|-------|-------|
| D H9 | d h9 | L ₁ +0.2 | r ₁ | h | 2MPa | 10MPa | 20MPa | 40MPa |
| 6.0-19.9 | B-2.9 | 2.4 | 0.4 | 0.4 | 0.20 | 0.10 | 0.08 | 0.05 |
| 14.0-24.9 | B-4.5 | 3.6 | 0.4 | 0.6 | 0.25 | 0.15 | 0.10 | 0.07 |
| 25.0-45.9 | B-6.2 | 4.8 | 0.6 | 0.7 | 0.35 | 0.20 | 0.15 | 0.08 |
| 46.0-124.9 | B-9.4 | 7.1 | 0.8 | 0.8 | 0.50 | 0.25 | 0.20 | 0.10 |
| 125.0-999.9 | B-12.2 | 9.5 | 0.8 | 0.8 | 0.60 | 0.30 | 0.25 | 0.12 |

3. Application and properties

Applicable to harsh conditions and some special media requirements, it is a recommended seal for applications that do not crawl, chemical resistant, and resistant to most media applications. Could be used for reciprocating and rotary motion, with small friction coefficient, wear resistance and dimensional stability

4. Standard materials

Sealing ring: filled PTFE

Spring: stainless steel



D E G / D E P

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|--------|-----------------------------------|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3-1000mm | 0—45MPa | -40°C +260°C | 15 m/s | all liquids, chemicals, and gases |

6. Installation Dimensions

| Rod Dia. | Groove Dia. | Groove Width | Order No. |
|----------|-------------|--------------|-----------------|
| D H9 | d h9 | L +0.2 | |
| 6 | 3.1 | 2.4 | DEG6*3.1*2.4 |
| 8 | 5.1 | 2.4 | DEG8*5.1*2.4 |
| 10 | 7.1 | 2.4 | DEG10*7.1*2.4 |
| 12 | 9.1 | 2.4 | DEG12*9.1*2.4 |
| 14 | 9.5 | 3.6 | DEG14*9.5*3.6 |
| 15 | 10.5 | 3.6 | DEG15*10.5*3.6 |
| 16 | 11.5 | 3.6 | DEG16*11.5*3.6 |
| 18 | 13.5 | 3.6 | DEG18*13.5*3.6 |
| 20 | 15.5 | 3.6 | DEG20*15.5*3.6 |
| 22 | 17.5 | 3.6 | DEG22*17.5*3.6 |
| 25 | 18.8 | 4.8 | DEG25*18.8*4.8 |
| 28 | 21.8 | 4.8 | DEG28*21.8*4.8 |
| 30 | 23.8 | 4.8 | DEG30*23.8*4.8 |
| 32 | 25.8 | 4.8 | DEG32*25.8*4.8 |
| 35 | 28.8 | 4.8 | DEG35*28.8*4.8 |
| 40 | 33.8 | 4.8 | DEG40*33.8*4.8 |
| 42 | 35.8 | 4.8 | DEG42*35.8*4.8 |
| 45 | 38.8 | 4.8 | DEG45*38.8*4.8 |
| 48 | 38.6 | 7.1 | DEG48*38.6*7.1 |
| 50 | 40.6 | 7.1 | DEG50*40.6*7.1 |
| 52 | 42.6 | 7.1 | DEG52*42.6*7.1 |
| 55 | 45.6 | 7.1 | DEG55*45.6*7.1 |
| 56 | 46.6 | 7.1 | DEG56*46.6*7.1 |
| 60 | 50.6 | 7.1 | DEG60*50.6*7.1 |
| 63 | 53.6 | 7.1 | DEG63*53.6*7.1 |
| 65 | 55.6 | 7.1 | DEG65*55.6*7.1 |
| 70 | 60.6 | 7.1 | DEG70*60.6*7.1 |
| 75 | 65.6 | 7.1 | DEG75*65.6*7.1 |
| 80 | 70.6 | 7.1 | DEG80*70.6*7.1 |
| 85 | 75.6 | 7.1 | DEG85*75.6*7.1 |
| 90 | 80.6 | 7.1 | DEG90*80.6*7.1 |
| 95 | 85.6 | 7.1 | DEG95*85.6*7.1 |
| 100 | 90.6 | 7.1 | DEG100*90.6*7.1 |




D E G / D E P

| Rod Dia. | Groove Dia. | Groove Width | Order No. |
|----------|-------------|--------------|------------------|
| d h9 | D H9 | L +0.2 | |
| 110 | 100.6 | 7.1 | DEG110*100.6*7.1 |
| 115 | 105.6 | 7.1 | DEG115*105.6*7.1 |
| 120 | 110.6 | 7.1 | DEG120*110.6*7.1 |
| 125 | 112.8 | 9.5 | DEG125*112.8*9.5 |
| 130 | 117.8 | 9.5 | DEG130*117.8*9.5 |
| 135 | 122.8 | 9.5 | DEG135*122.8*9.5 |
| 140 | 127.8 | 9.5 | DEG140*127.8*9.5 |
| 150 | 137.8 | 9.5 | DEG150*137.8*9.5 |
| 160 | 147.8 | 9.5 | DEG160*147.8*9.5 |
| 170 | 157.8 | 9.5 | DEG170*157.8*9.5 |
| 180 | 167.8 | 9.5 | DEG180*167.8*9.5 |
| 190 | 177.8 | 9.5 | DEG190*177.8*9.5 |
| 200 | 187.8 | 9.5 | DEG200*187.8*9.5 |
| 210 | 197.8 | 9.5 | DEG210*197.8*9.5 |
| 220 | 207.8 | 9.5 | DEG220*207.8*9.5 |
| 230 | 217.8 | 9.5 | DEG230*217.8*9.5 |
| 240 | 227.8 | 9.5 | DEG240*227.8*9.5 |
| 250 | 237.8 | 9.5 | DEG250*237.8*9.5 |
| 280 | 267.8 | 9.5 | DEG280*267.8*9.5 |
| 300 | 287.8 | 9.5 | DEG300*287.8*9.5 |
| 320 | 307.8 | 9.5 | DEG320*307.8*9.5 |
| 350 | 337.8 | 9.5 | DEG350*337.8*9.5 |
| 400 | 387.8 | 9.5 | DEG400*387.8*9.5 |
| 420 | 407.8 | 9.5 | DEG420*407.8*9.5 |
| 450 | 437.8 | 9.5 | DEG450*437.8*9.5 |
| 480 | 467.8 | 9.5 | DEG480*467.8*9.5 |
| 500 | 487.8 | 9.5 | DEG500*487.8*9.5 |

1. Installation Recommendation

| Standard Groove | | | | | Widen groove | | | | |
|-------------------------|------|-----|------|------|-----------------------|------|-----|------|------|
| Type | Code | APS | 103A | 400A | Type | Code | APS | 103A | 400A |
| Equal Altitude Lips/Rod | DTVA | | | | High and Low Lips/Rod | DTVB | | | |



2. Installation Sizes

| Rod Diameter | Groove Diameter | | Groove Width | Radius | Step Height | Radial Clearance S max. | | |
|-------------------|----------------------|----------------------|---------------------|----------------|-------------|-------------------------|-------|-------|
| d _N f8 | D ₁ H9 | D ₂ H9 | L ₁ +0.2 | r ₁ | h | 2MPa | 10MPa | 20MPa |
| 5.0-19.9 | d _N +5.0 | d _N +9.0 | 3.6 | 0.8 | 0.3 | 0.25 | 0.15 | 0.10 |
| 20.0-39.9 | d _N +7.0 | d _N +12.5 | 4.8 | 1.1 | 0.4 | 0.35 | 0.20 | 0.15 |
| 40.0-399.9 | d _N +10.5 | d _N +17.5 | 7.1 | 1.4 | 0.5 | 0.50 | 0.25 | 0.20 |
| 400.0-999.9 | d _N +14.0 | d _N +22.0 | 9.5 | 1.6 | 0.6 | 0.60 | 0.30 | 0.25 |

3. Application and properties

Suitable for rotating, reciprocating, static sealing applications. Single action seals for rotating shafts. It is widely used in various hydraulic systems and chemical, pharmaceutical and food industries. Excellent scraping effect, no creeping phenomenon, good abrasion resistance and dimensional stability.

4. Standard materials

Sealing ring: filled PTFE

Spring: stainless steel



D T V

5. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|-----------------------------------|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3-1000mm | 0—25MPa | -40°C +260°C | 2 m/s | all liquids, chemicals, and gases |

6. Installation Dimensions

| Rod Dia. | Groove Dia. | | Groove Width | Order No. |
|----------|-------------|-------|--------------|-----------------|
| d f8 | D1 H9 | D2 H9 | L1 +0.2 | |
| 5 | 10 | 14 | 3.6 | DTV5*14*3.6 |
| 6 | 11 | 15 | 3.6 | DTV6*15*3.6 |
| 8 | 13 | 17 | 3.6 | DTV8*17*3.6 |
| 10 | 15 | 19 | 3.6 | DTV10*19*3.6 |
| 12 | 17 | 21 | 3.6 | DTV12*21*3.6 |
| 14 | 19 | 23 | 3.6 | DTV14*23*3.6 |
| 15 | 20 | 24 | 3.6 | DTV15*24*3.6 |
| 16 | 21 | 25 | 3.6 | DTV16*25*3.6 |
| 18 | 23 | 27 | 3.6 | DTV18*27*3.6 |
| 20 | 27 | 32.5 | 4.8 | DTV20*32.5*4.8 |
| 22 | 29 | 34.5 | 4.8 | DTV22*34.5*4.8 |
| 25 | 32 | 37.5 | 4.8 | DTV25*37.5*4.8 |
| 28 | 35 | 40.5 | 4.8 | DTV28*40.5*4.8 |
| 30 | 37 | 42.5 | 4.8 | DTV30*42.5*4.8 |
| 32 | 39 | 44.5 | 4.8 | DTV32*44.5*4.8 |
| 35 | 42 | 47.5 | 4.8 | DTV35*47.5*4.8 |
| 36 | 43 | 48.5 | 4.8 | DTV36*48.5*4.8 |
| 40 | 50.5 | 57.5 | 7.1 | DTV40*57.5*7.1 |
| 42 | 52.5 | 59.5 | 7.1 | DTV42*59.5*7.1 |
| 45 | 55.5 | 62.5 | 7.1 | DTV45*62.5*7.1 |
| 48 | 58.5 | 65.5 | 7.1 | DTV48*65.5*7.1 |
| 50 | 60.5 | 67.5 | 7.1 | DTV50*67.5*7.1 |
| 52 | 62.5 | 69.5 | 7.1 | DTV52*69.5*7.1 |
| 55 | 65.5 | 72.5 | 7.1 | DTV55*72.5*7.1 |
| 56 | 66.5 | 73.5 | 7.1 | DTV56*73.5*7.1 |
| 60 | 70.5 | 77.5 | 7.1 | DTV60*77.5*7.1 |
| 63 | 73.5 | 80.5 | 7.1 | DTV63*80.5*7.1 |
| 65 | 75.5 | 82.5 | 7.1 | DTV65*82.5*7.1 |
| 70 | 80.5 | 87.5 | 7.1 | DTV70*87.5*7.1 |
| 75 | 85.5 | 92.5 | 7.1 | DTV75*92.5*7.1 |
| 80 | 90.5 | 97.5 | 7.1 | DTV80*97.5*7.1 |
| 85 | 95.5 | 102.5 | 7.1 | DTV85*102.5*7.1 |
| 90 | 100.5 | 107.5 | 7.1 | DTV90*107.5*7.1 |



D T V


| Rod Dia. | Groove Dia. | | Groove Width | Order No. |
|----------|-------------|-------|--------------|------------------|
| d f8 | D1 H9 | D2 H9 | L1 +0.2 | |
| 95 | 105.5 | 112.5 | 7.1 | DTV95*112.5*7.1 |
| 100 | 110.5 | 117.5 | 7.1 | DTV100*117.5*7.1 |
| 105 | 115.5 | 122.5 | 7.1 | DTV105*122.5*7.1 |
| 110 | 120.5 | 127.5 | 7.1 | DTV110*127.5*7.1 |
| 115 | 125.5 | 132.5 | 7.1 | DTV115*132.5*7.1 |
| 120 | 130.5 | 137.5 | 7.1 | DTV120*137.5*7.1 |
| 125 | 135.5 | 142.5 | 7.1 | DTV125*142.5*7.1 |
| 130 | 140.5 | 147.5 | 7.1 | DTV130*147.5*7.1 |
| 135 | 145.5 | 152.5 | 7.1 | DTV135*152.5*7.1 |
| 140 | 150.5 | 157.5 | 7.1 | DTV140*157.5*7.1 |
| 150 | 160.5 | 167.5 | 7.1 | DTV150*167.5*7.1 |
| 160 | 170.5 | 177.5 | 7.1 | DTV160*177.5*7.1 |
| 170 | 180.5 | 187.5 | 7.1 | DTV170*187.5*7.1 |
| 180 | 190.5 | 197.5 | 7.1 | DTV180*197.5*7.1 |
| 190 | 200.5 | 207.5 | 7.1 | DTV190*207.5*7.1 |
| 200 | 210.5 | 217.5 | 7.1 | DTV200*217.5*7.1 |
| 210 | 220.5 | 227.5 | 7.1 | DTV210*227.5*7.1 |
| 220 | 230.5 | 237.5 | 7.1 | DTV220*237.5*7.1 |
| 230 | 240.5 | 247.5 | 7.1 | DTV230*247.5*7.1 |
| 240 | 250.5 | 257.5 | 7.1 | DTV240*257.5*7.1 |
| 250 | 260.5 | 267.5 | 7.1 | DTV250*267.5*7.1 |
| 280 | 290.5 | 297.5 | 7.1 | DTV280*297.5*7.1 |
| 300 | 310.5 | 317.5 | 7.1 | DTV300*317.5*7.1 |
| 320 | 330.5 | 337.5 | 7.1 | DTV320*337.5*7.1 |
| 350 | 360.5 | 367.5 | 7.1 | DTV350*367.5*7.1 |
| 360 | 370.5 | 377.5 | 7.1 | DTV360*377.5*7.1 |
| 400 | 410.5 | 417.5 | 7.1 | DTV400*417.5*7.1 |
| 420 | 434 | 442 | 9.5 | DTV420*442*9.5 |
| 450 | 464 | 472 | 9.5 | DTV450*472*9.5 |
| 480 | 494 | 502 | 9.5 | DTV480*502*9.5 |
| 500 | 514 | 522 | 9.5 | DTV500*522*9.5 |
| 600 | 614 | 622 | 9.5 | DTV600*622*9.5 |
| 700 | 714 | 722 | 9.5 | DTV700*722*9.5 |



D D V

1. Installation Recommendation

| Standard Groove | | | | | Widen groove | | | | |
|-----------------|------|-----|------|------|--------------|------|-----|------|------|
| Type | Code | APS | 103A | 400A | Type | Code | APS | 103A | 400A |
| Inner Seal | DDVI | | | | Lateral Seal | DDVO | | | |



2. Application and properties

Suitable for single operation, high pressure, static seal and pressure outside. For lighter gases, refrigerant and vacuum have a good sealing effect. It is widely used in various static and slow sealing occasions. It has good leakage resistance and excellent sealing ability on undesirable surface.

3. Standard materials

Sealing ring: filled PTFE

Spring: stainless steel

4. Working Conditions

| Working Conditions | | | | |
|--------------------|----------------|-------------------|-------|-----------------------------------|
| Diameter Range | Pressure Range | Temperature Range | Speed | Medium |
| 3-1000mm | 0-45MPa | -40°C +260°C | - | all liquids, chemicals, and gases |



D D V

5. Installation Dimensions


| Inner Side of End Face Spring Seal | | | | | | |
|------------------------------------|----------------------|--------------|--------------|------|--------|-----------|
| Lateral Dia. of grooves D H11 | | Groove Width | Groove Depth | | Radius | Order No. |
| Standard Range | Range of Application | min. | h | Tol. | Max. | |
| 10-13.9 | 10-40 | 2.4 | 1.45 | 0.03 | 0.4 | DDVI10 |
| 14-24.9 | 13-200 | 3.6 | 2.25 | 0.05 | 0.4 | DDVI11 |
| 25-45.9 | 18-400 | 4.8 | 3.10 | 0.08 | 0.6 | DDVI12 |
| 46-124.9 | 28-700 | 7.1 | 4.70 | 0.10 | 0.8 | DDVI13 |
| 125-999.9 | 45-1000 | 9.5 | 6.10 | 0.15 | 0.8 | DDVI14 |

| Lateral Side of End Face Spring Seal | | | | | | |
|--------------------------------------|----------------------|--------------|--------------|------|--------|-----------|
| Lateral Dia. of grooves D H11 | | Groove Width | Groove Depth | | Radius | Order No. |
| Standard Range | Range of Application | min. | h | Tol. | Max. | |
| 3-9.9 | 3-40 | 2.4 | 1.45 | 0.03 | 0.4 | DDVO0 |
| 10-19.9 | 8-200 | 3.6 | 2.25 | 0.05 | 0.4 | DDVO1 |
| 20-39.9 | 12-400 | 4.8 | 3.10 | 0.08 | 0.6 | DDVO2 |
| 40-119.9 | 20-700 | 7.1 | 4.70 | 0.10 | 0.8 | DDVO3 |
| 120-999.9 | 35-1000 | 9.5 | 6.10 | 0.15 | 0.8 | DDVO4 |



O - Ring

1. Installation Recommendation



2. Application and properties

Double acting seals, the sealing effect is achieved by the deformation of the section of the O-Rings, and the deformation is determined by the depth of the installation groove. Under pressure, the O-ring has a large surface tension like liquid, used for static sealing more. It is only recommended for better conditions in dynamic applications. System lubrication, pressure, temperature, sealing clearance, speed, medium and surface quality of metal parts determine the service life of O-Rings. It is not recommended if the lubrication is not sufficient during rotary motion.

3. Standard materials

NBR / FKM

4. Performance parameter

| | Static Seal | Dynamic Seal |
|------------------|--|---|
| Working Pressure | No support ring, up to 20MPa; With the support ring, up to 40MPa; With special support ring, up to 200MPa. | No support ring, up to 5MPa; With the support ring, higher pressure. |
| Movement Speed | Maximum reciprocating speed up to 0.5m / s; maximum rotation speed up to 2.0m/s. | |
| Temperature | NBR: -30 °C - 100 °C; FKM: -20 °C - 200 °C. | |



O - Ring

5. Wire Diameter Tolerance

| Wire diameter of O-Ring (mm) | Tolerance (\pm mm) |
|------------------------------|-----------------------|
| 0-1.8 | 0.08 |
| 1.80-2.65 | 0.09 |
| 2.65-3.55 | 0.10 |
| 3.55-5.30 | 0.13 |
| 5.30-7.00 | 0.15 |
| 7.00-8.00 | 0.18 |
| 8.00-10.00 | 0.21 |
| 10.00-12.00 | 0.25 |

6. Inner diameter tolerance

| Inner Diameter d_1 mm | Tolerance \pm mm | Inner Diameter d_1 mm | Tolerance \pm mm | Inner Diameter d_1 mm | Tolerance \pm mm |
|----------------------------|-----------------------|----------------------------|-----------------------|----------------------------|-----------------------|
| 0.70-2.50 | 0.13 | 43.70-45.00 | 0.42 | 95.00-97.50 | 0.83 |
| 2.50-4.50 | 0.14 | 46.00-46.20 | 0.43 | 97.50-100.00 | 0.84 |
| 4.50-6.30 | 0.15 | 46.20-47.50 | 0.44 | 100.00-103.00 | 0.87 |
| 6.30-8.50 | 0.16 | 47.50-48.70 | 0.45 | 103.00-106.00 | 0.89 |
| 8.50-10.00 | 0.17 | 48.70-50.00 | 0.46 | 106.00-109.00 | 0.91 |
| 10.00-11.20 | 0.18 | 50.00-51.50 | 0.47 | 109.00-112.00 | 0.93 |
| 11.20-14.00 | 0.19 | 51.50-53.00 | 0.48 | 112.00-115.00 | 0.95 |
| 14.00-16.00 | 0.20 | 53.00-54.50 | 0.50 | 115.00-118.00 | 0.97 |
| 16.00-18.00 | 0.21 | 54.50-56.00 | 0.51 | 118.00-122.00 | 1.00 |
| 18.00-20.00 | 0.22 | 56.00-58.00 | 0.52 | 122.00-125.00 | 1.03 |
| 20.00-21.20 | 0.23 | 58.00-60.00 | 0.54 | 125.00-128.00 | 1.05 |
| 21.20-23.60 | 0.24 | 60.00-61.50 | 0.55 | 128.00-132.00 | 1.08 |
| 23.60-25.00 | 0.25 | 61.50-63.00 | 0.56 | 132.00-136.00 | 1.10 |
| 25.00-26.50 | 0.26 | 63.00-65.00 | 0.58 | 136.00-140.00 | 1.13 |
| 26.50-28.00 | 0.28 | 65.00-67.00 | 0.59 | 140.00-145.00 | 1.17 |
| 28.00-30.00 | 0.29 | 67.00-69.00 | 0.61 | 145.00-150.00 | 1.20 |
| 30.00-31.50 | 0.31 | 69.00-71.00 | 0.63 | 150.00-155.00 | 1.24 |
| 31.50-33.50 | 0.32 | 71.00-73.00 | 0.64 | 155.00-160.00 | 1.27 |
| 33.50-34.50 | 0.33 | 73.00-75.00 | 0.66 | 160.00-165.00 | 1.31 |
| 34.50-35.50 | 0.34 | 75.00-77.50 | 0.67 | 165.00-170.00 | 1.34 |
| 35.50-36.50 | 0.35 | 77.50-80.00 | 0.69 | 170.00-175.00 | 1.38 |
| 36.50-37.50 | 0.36 | 80.00-82.50 | 0.71 | 175.00-180.00 | 1.41 |
| 37.50-38.70 | 0.37 | 82.50-85.00 | 0.73 | 180.00-185.00 | 1.44 |
| 38.70-40.00 | 0.38 | 85.00-87.50 | 0.75 | 185.00-190.00 | 1.48 |
| 40.00-41.20 | 0.39 | 87.50-90.00 | 0.77 | 190.00-195.00 | 1.51 |
| 41.20-42.50 | 0.40 | 90.00-92.50 | 0.79 | 195.00-200.00 | 1.55 |
| 42.50-43.70 | 0.41 | 92.50-95.00 | 0.81 | 200.00-206.00 | 1.59 |




O - Ring

| Inner Diameter d ₁ mm | Tolerance ±mm | Inner Diameter d ₁ mm | Tolerance ±mm | Inner Diameter d ₁ mm | Tolerance ±mm |
|-------------------------------------|------------------|-------------------------------------|------------------|-------------------------------------|------------------|
| 206.00-212.00 | 1.63 | 315.00-325.00 | 2.37 | 485.00-500.00 | 3.45 |
| 212.00-218.00 | 1.67 | 325.00-335.00 | 2.43 | 500.00-515.00 | 3.54 |
| 218.00-224.00 | 1.71 | 335.00-345.00 | 2.49 | 515.00-530.00 | 3.63 |
| 224.00-230.00 | 1.75 | 345.00-355.00 | 2.56 | 530.00-545.00 | 3.72 |
| 230.00-236.00 | 1.79 | 355.00-365.00 | 2.62 | 545.00-560.00 | 3.81 |
| 236.00-243.00 | 1.83 | 365.00-375.00 | 2.68 | 560.00-580.00 | 3.93 |
| 243.00-250.00 | 1.88 | 375.00-387.00 | 2.76 | 580.00-600.00 | 4.05 |
| 250.00-258.00 | 1.93 | 387.00-400.00 | 2.84 | 600.00-615.00 | 4.13 |
| 258.00-265.00 | 1.98 | 400.00-412.00 | 2.91 | 615.00-630.00 | 4.22 |
| 265.00-272.00 | 2.02 | 412.00-425.00 | 2.99 | 630.00-650.00 | 4.34 |
| 272.00-280.00 | 2.08 | 425.00-437.00 | 3.07 | 650.00-670.00 | 4.46 |
| 280.00-290.00 | 2.14 | 437.00-450.00 | 3.15 | | |
| 290.00-300.00 | 2.21 | 450.00-462.00 | 3.22 | | |
| 300.00-307.00 | 2.25 | 462.00-475.00 | 3.30 | | |
| 307.00-315.00 | 2.30 | 475.00-485.00 | 3.37 | | |





1. Installation Recommendation



2. O-Ring Dimensions

| d ₁ | W | Order No. | d ₁ | W | Order No. |
|----------------|------|-----------|----------------|------|-----------|
| 0.74 | 1.02 | AS-001 | 18.77 | 1.78 | AS-018 |
| 1.07 | 1.27 | AS-002 | 20.35 | 1.78 | AS-019 |
| 1.42 | 1.52 | AS-003 | 21.95 | 1.78 | AS-020 |
| 1.78 | 1.78 | AS-004 | 23.52 | 1.78 | AS-021 |
| 2.57 | 1.78 | AS-005 | 25.12 | 1.78 | AS-022 |
| 2.9 | 1.78 | AS-006 | 26.7 | 1.78 | AS-023 |
| 3.68 | 1.78 | AS-007 | 28.3 | 1.78 | AS-024 |
| 4.47 | 1.78 | AS-008 | 29.87 | 1.78 | AS-025 |
| 5.28 | 1.78 | AS-009 | 31.47 | 1.78 | AS-026 |
| 6.07 | 1.78 | AS-010 | 33.05 | 1.78 | AS-027 |
| 7.65 | 1.78 | AS-011 | 34.65 | 1.78 | AS-028 |
| 9.25 | 1.78 | AS-012 | 37.82 | 1.78 | AS-029 |
| 10.82 | 1.78 | AS-013 | 41 | 1.78 | AS-030 |
| 12.42 | 1.78 | AS-014 | 44.17 | 1.78 | AS-031 |
| 14 | 1.78 | AS-015 | 47.35 | 1.78 | AS-032 |
| 15.6 | 1.27 | AS-016 | 50.52 | 1.78 | AS-033 |
| 17.17 | 1.52 | AS-017 | 53.7 | 1.78 | AS-034 |



A S 5 6 8

| d ₁ | W | Order No. | d ₁ | W | Order No. |
|----------------|------|-----------|----------------|------|-----------|
| 56.87 | 1.78 | AS-035 | 34.59 | 2.62 | AS-126 |
| 60.05 | 1.78 | AS-036 | 36.17 | 2.62 | AS-127 |
| 63.22 | 1.78 | AS-037 | 37.77 | 2.62 | AS-128 |
| 66.4 | 1.78 | AS-038 | 39.34 | 2.62 | AS-129 |
| 69.57 | 1.78 | AS-039 | 40.94 | 2.62 | AS-130 |
| 72.75 | 1.78 | AS-040 | 42.52 | 2.62 | AS-131 |
| 75.92 | 1.78 | AS-041 | 44.12 | 2.62 | AS-132 |
| 82.27 | 1.78 | AS-042 | 45.69 | 2.62 | AS-133 |
| 88.62 | 1.78 | AS-043 | 47.29 | 2.62 | AS-134 |
| 94.97 | 1.78 | AS-044 | 48.9 | 2.62 | AS-135 |
| 101.32 | 1.78 | AS-045 | 50.47 | 2.62 | AS-136 |
| 107.67 | 1.78 | AS-046 | 52.07 | 2.62 | AS-137 |
| 114.02 | 1.78 | AS-047 | 53.64 | 2.62 | AS-138 |
| 120.37 | 1.78 | AS-048 | 55.25 | 2.62 | AS-139 |
| 126.72 | 1.78 | AS-049 | 56.82 | 2.62 | AS-140 |
| 133.07 | 1.78 | AS-050 | 58.42 | 2.62 | AS-141 |
| 1.24 | 2.62 | AS-102 | 59.99 | 2.62 | AS-142 |
| 2.06 | 2.62 | AS-103 | 61.6 | 2.62 | AS-143 |
| 2.84 | 2.62 | AS-104 | 63.17 | 2.62 | AS-144 |
| 3.63 | 2.62 | AS-105 | 64.77 | 2.62 | AS-145 |
| 4.42 | 2.62 | AS-106 | 66.34 | 2.62 | AS-146 |
| 5.23 | 2.62 | AS-107 | 67.95 | 2.62 | AS-147 |
| 6.02 | 2.62 | AS-108 | 69.52 | 2.62 | AS-148 |
| 7.59 | 2.62 | AS-109 | 71.12 | 2.62 | AS-149 |
| 9.19 | 2.62 | AS-110 | 72.69 | 2.62 | AS-150 |
| 10.77 | 2.62 | AS-111 | 75.87 | 2.62 | AS-151 |
| 12.37 | 2.62 | AS-112 | 82.22 | 2.62 | AS-152 |
| 13.94 | 2.62 | AS-113 | 88.57 | 2.62 | AS-153 |
| 15.54 | 2.62 | AS-114 | 94.92 | 2.62 | AS-154 |
| 17.12 | 2.62 | AS-115 | 101.27 | 2.62 | AS-155 |
| 18.72 | 2.62 | AS-116 | 107.62 | 2.62 | AS-156 |
| 20.29 | 2.62 | AS-117 | 113.97 | 2.62 | AS-157 |
| 21.89 | 2.62 | AS-118 | 120.32 | 2.62 | AS-158 |
| 23.47 | 2.62 | AS-119 | 126.67 | 2.62 | AS-159 |
| 25.07 | 2.62 | AS-120 | 133.02 | 2.62 | AS-160 |
| 26.64 | 2.62 | AS-121 | 139.37 | 2.62 | AS-161 |
| 28.24 | 2.62 | AS-122 | 145.72 | 2.62 | AS-162 |
| 29.82 | 2.62 | AS-123 | 152.07 | 2.62 | AS-163 |
| 31.42 | 2.62 | AS-124 | 158.42 | 2.62 | AS-164 |
| 32.99 | 2.62 | AS-125 | 164.77 | 2.62 | AS-165 |



A S 5 6 8

| d ₁ | W | Order No. | d ₁ | W | Order No. |
|----------------|------|-----------|----------------|------|-----------|
| 171.12 | 2.62 | AS-166 | 53.57 | 3.53 | AS-227 |
| 177.47 | 2.62 | AS-167 | 56.74 | 3.53 | AS-228 |
| 183.82 | 2.62 | AS-168 | 59.92 | 3.53 | AS-229 |
| 190.17 | 2.62 | AS-169 | 63.09 | 3.53 | AS-230 |
| 196.52 | 2.62 | AS-170 | 66.27 | 3.53 | AS-231 |
| 202.87 | 2.62 | AS-171 | 69.44 | 3.53 | AS-232 |
| 209.22 | 2.62 | AS-172 | 72.62 | 3.53 | AS-233 |
| 215.57 | 2.62 | AS-173 | 75.79 | 3.53 | AS-234 |
| 221.92 | 2.62 | AS-174 | 78.97 | 3.53 | AS-235 |
| 228.27 | 2.62 | AS-175 | 82.14 | 3.53 | AS-236 |
| 234.62 | 2.62 | AS-176 | 85.32 | 3.53 | AS-237 |
| 240.97 | 2.62 | AS-177 | 88.49 | 3.53 | AS-238 |
| 247.32 | 2.62 | AS-178 | 91.67 | 3.53 | AS-239 |
| 253.67 | 2.62 | AS-179 | 94.84 | 3.53 | AS-240 |
| 4.34 | 3.53 | AS-201 | 98.02 | 3.53 | AS-241 |
| 5.94 | 3.53 | AS-202 | 101.19 | 3.53 | AS-242 |
| 7.52 | 3.53 | AS-203 | 104.37 | 3.53 | AS-243 |
| 9.12 | 3.53 | AS-204 | 107.54 | 3.53 | AS-244 |
| 10.69 | 3.53 | AS-205 | 110.72 | 3.53 | AS-245 |
| 12.29 | 3.53 | AS-206 | 113.89 | 3.53 | AS-246 |
| 13.87 | 3.53 | AS-207 | 117.07 | 3.53 | AS-247 |
| 15.47 | 3.53 | AS-208 | 120.24 | 3.53 | AS-248 |
| 17.04 | 3.53 | AS-209 | 123.42 | 3.53 | AS-249 |
| 18.64 | 3.53 | AS-210 | 126.59 | 3.53 | AS-250 |
| 20.22 | 3.53 | AS-211 | 129.77 | 3.53 | AS-251 |
| 21.82 | 3.53 | AS-212 | 132.94 | 3.53 | AS-252 |
| 23.39 | 3.53 | AS-213 | 136.12 | 3.53 | AS-253 |
| 24.99 | 3.53 | AS-214 | 139.29 | 3.53 | AS-254 |
| 26.57 | 3.53 | AS-215 | 142.47 | 3.53 | AS-255 |
| 28.17 | 3.53 | AS-216 | 145.64 | 3.53 | AS-256 |
| 29.74 | 3.53 | AS-217 | 148.82 | 3.53 | AS-257 |
| 31.34 | 3.53 | AS-218 | 151.99 | 3.53 | AS-258 |
| 32.92 | 3.53 | AS-219 | 158.34 | 3.53 | AS-259 |
| 34.52 | 3.53 | AS-220 | 164.69 | 3.53 | AS-260 |
| 36.09 | 3.53 | AS-221 | 171.04 | 3.53 | AS-261 |
| 37.69 | 3.53 | AS-222 | 177.39 | 3.53 | AS-262 |
| 40.87 | 3.53 | AS-223 | 183.74 | 3.53 | AS-263 |
| 44.04 | 3.53 | AS-224 | 190.09 | 3.53 | AS-264 |
| 47.22 | 3.53 | AS-225 | 196.44 | 3.53 | AS-265 |
| 50.39 | 3.53 | AS-226 | 202.79 | 3.53 | AS-266 |



A S 5 6 8

| d ₁ | W | Order No. | d ₁ | W | Order No. |
|----------------|------|-----------|----------------|------|-----------|
| 209.14 | 3.53 | AS-267 | 56.52 | 5.33 | AS-331 |
| 215.49 | 3.53 | AS-268 | 59.69 | 5.33 | AS-332 |
| 221.84 | 3.53 | AS-269 | 62.87 | 5.33 | AS-333 |
| 228.19 | 3.53 | AS-270 | 66.04 | 5.33 | AS-334 |
| 234.54 | 3.53 | AS-271 | 69.22 | 5.33 | AS-335 |
| 240.89 | 3.53 | AS-272 | 72.39 | 5.33 | AS-336 |
| 247.24 | 3.53 | AS-273 | 75.57 | 5.33 | AS-337 |
| 253.59 | 3.53 | AS-274 | 78.74 | 5.33 | AS-338 |
| 266.29 | 3.53 | AS-275 | 81.92 | 5.33 | AS-339 |
| 278.99 | 3.53 | AS-276 | 85.09 | 5.33 | AS-340 |
| 291.69 | 3.53 | AS-277 | 88.27 | 5.33 | AS-341 |
| 304.39 | 3.53 | AS-278 | 91.44 | 5.33 | AS-342 |
| 329.79 | 3.53 | AS-279 | 94.62 | 5.33 | AS-343 |
| 355.19 | 3.53 | AS-280 | 97.79 | 5.33 | AS-344 |
| 380.59 | 3.53 | AS-281 | 100.97 | 5.33 | AS-345 |
| 405.26 | 3.53 | AS-282 | 104.14 | 5.33 | AS-346 |
| 430.66 | 3.53 | AS-283 | 107.32 | 5.33 | AS-347 |
| 456.06 | 3.53 | AS-284 | 110.49 | 5.33 | AS-348 |
| 10.46 | 5.33 | AS-309 | 113.67 | 5.33 | AS-349 |
| 12.07 | 5.33 | AS-310 | 116.84 | 5.33 | AS-350 |
| 13.64 | 5.33 | AS-311 | 120.02 | 5.33 | AS-351 |
| 15.24 | 5.33 | AS-312 | 123.19 | 5.33 | AS-352 |
| 16.81 | 5.33 | AS-313 | 126.37 | 5.33 | AS-353 |
| 18.42 | 5.33 | AS-314 | 129.54 | 5.33 | AS-354 |
| 19.99 | 5.33 | AS-315 | 132.72 | 5.33 | AS-355 |
| 21.59 | 5.33 | AS-316 | 135.89 | 5.33 | AS-356 |
| 23.16 | 5.33 | AS-317 | 139.07 | 5.33 | AS-357 |
| 24.77 | 5.33 | AS-318 | 142.24 | 5.33 | AS-358 |
| 26.34 | 5.33 | AS-319 | 145.42 | 5.33 | AS-359 |
| 27.94 | 5.33 | AS-320 | 148.59 | 5.33 | AS-360 |
| 29.51 | 5.33 | AS-321 | 151.77 | 5.33 | AS-361 |
| 31.12 | 5.33 | AS-322 | 158.12 | 5.33 | AS-362 |
| 32.69 | 5.33 | AS-323 | 164.47 | 5.33 | AS-363 |
| 34.29 | 5.33 | AS-324 | 170.82 | 5.33 | AS-364 |
| 37.47 | 5.33 | AS-325 | 177.71 | 5.33 | AS-365 |
| 40.64 | 5.33 | AS-326 | 183.52 | 5.33 | AS-366 |
| 43.82 | 5.33 | AS-327 | 189.87 | 5.33 | AS-367 |
| 46.99 | 5.33 | AS-328 | 196.22 | 5.33 | AS-368 |
| 50.17 | 5.33 | AS-329 | 202.57 | 5.33 | AS-369 |
| 53.34 | 5.33 | AS-330 | 208.92 | 5.33 | AS-370 |





A S 5 6 8

| d ₁ | W | Order No. | d ₁ | W | Order No. |
|----------------|------|-----------|----------------|---|-----------|
| 215.27 | 5.33 | AS-371 | 158.12 | 7 | AS-438 |
| 221.62 | 5.33 | AS-372 | 164.47 | 7 | AS-439 |
| 227.97 | 5.33 | AS-373 | 170.82 | 7 | AS-440 |
| 234.32 | 5.33 | AS-374 | 177.17 | 7 | AS-441 |
| 240.67 | 5.33 | AS-375 | 183.52 | 7 | AS-442 |
| 247.02 | 5.33 | AS-376 | 189.87 | 7 | AS-443 |
| 253.37 | 5.33 | AS-377 | 196.22 | 7 | AS-444 |
| 266.07 | 5.33 | AS-378 | 202.57 | 7 | AS-445 |
| 278.77 | 5.33 | AS-379 | 215.27 | 7 | AS-446 |
| 291.47 | 5.33 | AS-380 | 227.97 | 7 | AS-447 |
| 304.17 | 5.33 | AS-381 | 240.67 | 7 | AS-448 |
| 329.57 | 5.33 | AS-382 | 253.37 | 7 | AS-449 |
| 354.97 | 5.33 | AS-383 | 266.07 | 7 | AS-450 |
| 380.37 | 5.33 | AS-384 | 278.77 | 7 | AS-451 |
| 405.26 | 5.33 | AS-385 | 291.47 | 7 | AS-452 |
| 430.66 | 5.33 | AS-386 | 304.17 | 7 | AS-453 |
| 456.06 | 5.33 | AS-387 | 316.87 | 7 | AS-454 |
| 481.41 | 5.33 | AS-388 | 329.57 | 7 | AS-455 |
| 506.81 | 5.33 | AS-389 | 342.27 | 7 | AS-456 |
| 532.21 | 5.33 | AS-390 | 354.87 | 7 | AS-457 |
| 557.61 | 5.33 | AS-391 | 367.67 | 7 | AS-458 |
| 582.68 | 5.33 | AS-392 | 380.37 | 7 | AS-459 |
| 608.08 | 5.33 | AS-393 | 393.07 | 7 | AS-460 |
| 633.48 | 5.33 | AS-394 | 405.26 | 7 | AS-461 |
| 658.88 | 5.33 | AS-395 | 417.96 | 7 | AS-462 |
| 113.67 | 7 | AS-425 | 430.66 | 7 | AS-463 |
| 116.84 | 7 | AS-426 | 443.36 | 7 | AS-464 |
| 120.02 | 7 | AS-427 | 456.06 | 7 | AS-465 |
| 123.19 | 7 | AS-428 | 468.76 | 7 | AS-466 |
| 126.37 | 7 | AS-429 | 481.46 | 7 | AS-467 |
| 129.54 | 7 | AS-430 | 494.16 | 7 | AS-468 |
| 132.72 | 7 | AS-431 | 506.86 | 7 | AS-469 |
| 135.89 | 7 | AS-432 | 532.26 | 7 | AS-470 |
| 139.07 | 7 | AS-433 | 557.66 | 7 | AS-471 |
| 142.24 | 7 | AS-434 | 582.68 | 7 | AS-472 |
| 145.42 | 7 | AS-435 | 608.08 | 7 | AS-473 |
| 148.59 | 7 | AS-436 | 633.48 | 7 | AS-474 |
| 151.77 | 7 | AS-437 | 658.88 | 7 | AS-475 |



JIS B 2401

| d ₁ | W | Order No. | d ₁ | W | Order No. |
|----------------|-----|-----------|----------------|-----|-----------|
| 2.8 | 1.9 | P3 | 40.7 | 3.5 | P41 |
| 3.8 | 1.9 | P4 | 41.7 | 3.5 | P42 |
| 4.8 | 1.9 | P5 | 43.7 | 3.5 | P44 |
| 5.8 | 1.9 | P6 | 44.7 | 3.5 | P45 |
| 6.8 | 1.9 | P7 | 45.7 | 3.5 | P46 |
| 7.8 | 1.9 | P8 | 47.7 | 3.5 | P48 |
| 8.8 | 1.9 | P9 | 48.7 | 3.5 | P49 |
| 9.8 | 1.9 | P10 | 49.7 | 3.5 | P50 |
| 9.8 | 2.4 | P10A | 47.6 | 5.7 | P48A |
| 10.8 | 2.4 | P11 | 49.6 | 5.7 | P50A |
| 11 | 2.4 | P11.2 | 51.6 | 5.7 | P52 |
| 11.8 | 2.4 | P12 | 52.6 | 5.7 | P53 |
| 12.3 | 2.4 | P12.5 | 54.6 | 5.7 | P55 |
| 13.8 | 2.4 | P14 | 55.6 | 5.7 | P56 |
| 14.8 | 2.4 | P15 | 57.6 | 5.7 | P58 |
| 15.8 | 2.4 | P16 | 59.6 | 5.7 | P60 |
| 17.8 | 2.4 | P18 | 61.6 | 5.7 | P62 |
| 19.8 | 2.4 | P20 | 62.6 | 5.7 | P63 |
| 20.8 | 2.4 | P21 | 64.6 | 5.7 | P65 |
| 21.8 | 2.4 | P22 | 66.6 | 5.7 | P67 |
| 21.7 | 3.5 | P22A | 69.6 | 5.7 | P70 |
| 22.1 | 3.5 | P22.4 | 70.6 | 5.7 | P71 |
| 23.7 | 3.5 | P24 | 74.6 | 5.7 | P75 |
| 24.7 | 3.5 | P25 | 79.6 | 5.7 | P80 |
| 25.2 | 3.5 | P25.5 | 84.6 | 5.7 | P85 |
| 25.7 | 3.5 | P26 | 89.6 | 5.7 | P90 |
| 27.7 | 3.5 | P28 | 94.6 | 5.7 | P95 |
| 28.7 | 3.5 | P29 | 99.6 | 5.7 | P100 |
| 29.2 | 3.5 | P29.5 | 101.6 | 5.7 | P102 |
| 29.7 | 3.5 | P30 | 104.6 | 5.7 | P105 |
| 30.7 | 3.5 | P31 | 109.6 | 5.7 | P110 |
| 31.2 | 3.5 | P31.5 | 111.6 | 5.7 | P112 |
| 31.7 | 3.5 | P32 | 114.6 | 5.7 | P115 |
| 33.7 | 3.5 | P34 | 119.6 | 5.7 | P120 |
| 34.7 | 3.5 | P35 | 124.6 | 5.7 | P125 |
| 35.2 | 3.5 | P35.5 | 129.6 | 5.7 | P130 |
| 35.7 | 3.5 | P36 | 131.6 | 5.7 | P132 |
| 37.7 | 3.5 | P38 | 134.6 | 5.7 | P135 |
| 38.7 | 3.5 | P39 | 144.6 | 5.7 | P145 |
| 39.7 | 3.5 | P40 | 149.6 | 8.4 | P150 |



JIS B 2401

| d ₁ | W | Order No. | d ₁ | W | Order No. |
|----------------|-----|-----------|----------------|-----|-----------|
| 154.5 | 8.4 | P155 | 24.4 | 3.1 | G25 |
| 159.5 | 8.4 | P160 | 29.4 | 3.1 | G30 |
| 164.5 | 8.4 | P165 | 34.4 | 3.1 | G35 |
| 169.5 | 8.4 | P170 | 39.4 | 3.1 | G40 |
| 174.5 | 8.4 | P175 | 44.4 | 3.1 | G45 |
| 179.5 | 8.4 | P180 | 49.4 | 3.1 | G50 |
| 184.5 | 8.4 | P185 | 54.4 | 3.1 | G55 |
| 189.5 | 8.4 | P190 | 59.4 | 3.1 | G60 |
| 194.5 | 8.4 | P195 | 64.4 | 3.1 | G65 |
| 199.5 | 8.4 | P200 | 69.4 | 3.1 | G70 |
| 204.5 | 8.4 | P205 | 74.4 | 3.1 | G75 |
| 208.5 | 8.4 | P209 | 79.4 | 3.1 | G80 |
| 209.5 | 8.4 | P210 | 84.4 | 3.1 | G85 |
| 214.5 | 8.4 | P215 | 89.4 | 3.1 | G90 |
| 219.5 | 8.4 | P220 | 94.4 | 3.1 | G95 |
| 224.5 | 8.4 | P225 | 99.4 | 3.1 | G100 |
| 229.5 | 8.4 | P230 | 104.4 | 3.1 | G105 |
| 234.5 | 8.4 | P235 | 109.4 | 3.1 | G110 |
| 239.5 | 8.4 | P240 | 114.4 | 3.1 | G115 |
| 244.5 | 8.4 | P245 | 119.4 | 3.1 | G120 |
| 249.5 | 8.4 | P250 | 124.5 | 3.1 | G125 |
| 254.5 | 8.4 | P255 | 129.4 | 3.1 | G130 |
| 259.5 | 8.4 | P260 | 134.4 | 3.1 | G135 |
| 264.5 | 8.4 | P265 | 139.4 | 3.1 | G140 |
| 269.5 | 8.4 | P270 | 144.4 | 3.1 | G145 |
| 274.5 | 8.4 | P275 | 149.3 | 5.7 | G150 |
| 279.5 | 8.4 | P280 | 154.3 | 5.7 | G155 |
| 284.5 | 8.4 | P285 | 159.3 | 5.7 | G160 |
| 289.5 | 8.4 | P290 | 164.3 | 5.7 | G165 |
| 294.5 | 8.4 | P295 | 169.3 | 5.7 | G170 |
| 299.5 | 8.4 | P300 | 174.3 | 5.7 | G175 |
| 314.5 | 8.4 | P315 | 179.3 | 5.7 | G180 |
| 319.5 | 8.4 | P320 | 184.3 | 5.7 | G185 |
| 334.5 | 8.4 | P335 | 189.3 | 5.7 | G190 |
| 339.5 | 8.4 | P340 | 194.3 | 5.7 | G195 |
| 354.5 | 8.4 | P355 | 199.3 | 5.7 | G200 |
| 359.5 | 8.4 | P360 | 209.3 | 5.7 | G210 |
| 374.5 | 8.4 | P375 | 219.3 | 5.7 | G220 |
| 384.5 | 8.4 | P385 | 229.3 | 5.7 | G230 |
| 399.5 | 8.4 | P400 | 239.3 | 5.7 | G240 |



JIS B 2401

| d ₁ | W | Order No. | d ₁ | W | Order No. |
|----------------|-----|-----------|----------------|-----|-----------|
| 249.3 | 5.7 | G250 | 279.3 | 5.7 | G280 |
| 259.3 | 5.7 | G260 | 289.3 | 5.7 | G290 |
| 269.3 | 5.7 | G270 | 299.3 | 5.7 | G300 |

D  First Disign

M First Manufacture

S First Service



DMS SEALS TECHNOLOGY CO.,LIMITED

Address: No. 5, Hegui Mid Road, Hegui Industrial Park,
Lishui Town, Nanhui District, Foshan City,
Guangdong Province, P.R. China 528241

Tel: +86-757-86235767 | Mobile: +86-13318313660

Email: sales@dmsseals.com, dms@dmsseals.com

Email: sales@dmseals.com,
Website: www.dmseals.com